

**BID NO. PUR-1569
INVITATION TO BID
ISSUED ON BEHALF OF
THE BOARD OF COUNTY COMMISSIONERS
OF WASHINGTON COUNTY, MARYLAND**

**BY
THE WASHINGTON COUNTY PURCHASING DEPARTMENT
100 WEST WASHINGTON STREET, SUITE 3200
HAGERSTOWN, MD 21740
PHONE: 240-313-2330
FAX: 240-313-2331**

DATE ISSUED: August 24, 2022

UNIFORMS FOR THE WASHINGTON COUNTY SHERIFF'S OFFICERS

PRE-BID CONFERENCE DATE/TELECONFERENCE

TIME AND LOCATION: **Wednesday, August 31, 2022 at 10:00 A.M., (EDT/EST)**
Washington County Administration Complex
Conference Room 3000
Third Floor, 100 West Washington Street
Hagerstown, MD 21740

DEADLINE FOR QUESTIONS: **4:00 P.M., (EDT/EST), Wednesday, September 7, 2022**

SUBMIT BIDS TO: Washington County Purchasing Department
Washington County Administration Complex
100 West Washington Street
Third Floor, Suite 3200
Hagerstown, MD 21740

**BID SUBMISSION DEADLINE
AND BID OPENING TIME:** No later than **2:00P.M., (EDT/EST), Wednesday, September 21,
2022**

BID OPENING LOCATION: Washington County Administration Complex
100 West Washington Street, Suite 3000, Third Floor
Hagerstown, MD 21740

If indicated below (√) and not waived by the County, Bidders shall be required to provide the following:

- _____ A Bid Bond, in the amount of five (5%) percent of the bid on a bid of \$100,000 or more for construction contracts and on a bid of \$50,000 or more for contracts for services, supplies, or construction related services. See "Bid Bonds – Section 2" of the General Conditions and Instructions to Bidders.
- _____ A Performance Bond for a bid award of \$100,000 or more on construction contracts and on contracts for services, supplies, or construction related services. See "Bid Bonds – Section 2" of the General Conditions and Instructions to Bidders.
- _____ A Labor and Material Bond for a bid award of \$100,000 or more on construction contracts and on contracts for services, supplies, or construction related services. See "Bid Bonds – Section 2" of the General Conditions and Instructions to Bidders.

PUR-1569
UNIFORMS FOR THE
WASHINGTON COUNTY SHERIFF’S OFFICERS

TABLE OF CONTENTS

	<u>PAGE</u>
I. Invitation to Bid	1 - 2
II. General Conditions and Instructions to Bidders	3 - 15
III. Supplemental Terms and Conditions	16 - 18
IV. Scope of Work/Specifications	19 - 93
V. Washington County’s <i>Insurance Requirements for Independent Contractors Policy</i>	94 - 95
VI. Provisions for Other Agencies	96
VII. Signature to Bids	97 - 98
VIII. Form of Proposal	99 – 111
IX. Government Wide Debarment and Suspension	112



Washington County

M A R Y L A N D

PURCHASING DEPARTMENT DIVISION OF BUDGET & FINANCE

PUR-1569 UNIFORMS FOR THE WASHINGTON COUNTY SHERIFF'S OFFICERS

INVITATION TO BID

The Board of County Commissioners of Washington County, Maryland will accept sealed bids for **UNIFORMS FOR WASHINGTON COUNTY SHERIFF'S OFFICERS**. Bid documents are available immediately from the Washington County website: <https://www.washco-md.net/purchasing-department/purch-open-invites/>, for assistance you may contact the Washington County Purchasing Department, Washington County Administration Complex, 100 West Washington Street, Third Floor, Suite 3200, Hagerstown, MD 21740. **Direct all inquiries to Brandi Naugle, CPPB, Buyer, at telephone 240-313-2330 or fax 240-313-2331.**

All bids must be enclosed in a sealed opaque envelope marked "**SEALED BID – (PUR-1569) UNIFORMS FOR THE WASHINGTON COUNTY SHERRIFF'S OFFICERS**" and be received and time stamped by the Washington County Purchasing Department, Washington County Administration Complex, 100 West Washington Street, Third Floor, Suite 3200, Hagerstown, Maryland, 21740, no later than **2:00P.M., (EDT/EST), Wednesday, September 21, 2022** after which time they will be publicly opened in the Third Floor, Conference Room 3000. All interested parties are invited to be present. For those bidders who wish to hear a reading of the bids please call prior to the teleconference 240-313-2330 to receive instructions. *Facsimile Bids or any electronic bid submission will not be accepted.*

A Pre-Bid Conference/Teleconference will be held on **Wednesday, August 31, 2022, at 10:00 A.M., (EDT/EST)** in the Washington County Administration Complex, Third Floor, Conference Room 3000, 100 West Washington Street, Hagerstown, Maryland. All interested bidders are requested to be present. Attendance is not mandatory but is strongly encouraged. Bidders who wish to participate in the teleconference, please call prior to the teleconference 240-313-2330 for further instructions.

NOTE: All Bidders must enter the Washington County Administrative Complex through either the front door at the 100 West Washington Street entrance or through the rear entrance (w/blue canopy roof) which is handicap accessible and must use the elevator to access the Purchasing Department to submit their bid and/or to attend the Pre-Bid Conference. Alternate routes are controlled by a door access system. The general public will be subject to wand search and will be required to remove any unauthorized items from the building prior to entry. Prohibited items include but are not limited to: Weapons of any type; Firearms, ammunition and explosive devices; Cutting instruments of any type - including knives, scissors, box cutters, work tools, knitting needles, or anything with a cutting edge, etc.; Pepper spray, mace or any other chemical defense sprays; and Illegal substances.

100 West Washington Street, Room 3200 | Hagerstown, MD 21740-4748 | P: 240.313.2330 | F: 240.313.2331 | TDD: 711

WWW.WASHCO-MD.NET

Washington County shall make positive efforts to utilize Disadvantaged Business Enterprises for its supplies and services and shall allow these sources to maximum feasible opportunity to compete for contracts. The Board of County Commissioners of Washington County, Maryland does not discriminate on the basis of race, color, national origin, sex, religion, age and disability in employment or the provision of services. Individuals requiring special accommodations are requested to contact the undersigned at 240-313-2330 Voice, TTY Dial 711 to make arrangements no later than five (5) calendar days prior to the Pre-Bid Conference and/or Bid Opening.

The Board of County Commissioners of Washington County, Maryland, reserves the right to accept or reject any or all bids and to waive formalities, informalities, and technicalities therein. The Board reserves the right to contact a Bidder for clarifications and may, at its sole discretion, allow a Bidder to correct any and all formalities, informalities, and technicalities in the best interest of Washington County, Maryland.

By Authority of:



Rick F. Curry, CPPO
Director of Purchasing

**BOARD OF COUNTY COMMISSIONERS
OF WASHINGTON COUNTY, MARYLAND**

GENERAL CONDITIONS AND INSTRUCTIONS TO BIDDERS

Supply and Service Contracts

INTRODUCTION

The general rules and conditions which follow, along with all other documents consisting of this "Bid Document," apply to all purchases and become a definite part of each formal invitation to bid, purchase order, contract, or other award issued by the Washington County's Director of Purchasing (hereinafter "Director of Purchasing"), unless otherwise specified. Bidders or their authorized representatives are expected to fully inform themselves as to the conditions, requirements, and specifications before submitting bids; failure to do so will be at the Bidder's own risk and they cannot secure relief on the plea of error. Bidders are advised that all costs related to preparing and/or submitting a Bid shall be borne by the Bidder.

Satisfactory evidence of authority to bind the firm by the person signing the Bid when submitted by partnerships or corporations may be requested by the County prior to making any award. Anyone signing a Bid as an agent shall include evidence of his/her authority to do so.

Subject to Maryland State and Washington County, Maryland (hereinafter "County") laws and all rules, regulations and limitations imposed by legislation of the Federal Government, bids on all advertisements and invitations issued by the Washington County Purchasing Department shall bind bidders to applicable conditions and requirements set forth herein unless otherwise specified in the Invitation to Bid. Should there be a conflict in laws between states, State of Maryland law shall prevail.

Should there be a conflict between the general bid conditions and the supplemental bid conditions (if any), the supplemental bid conditions shall prevail.

GENERAL CONDITIONS OF BIDDING

1. **Bids Binding for Ninety (90) Days:** Unless otherwise specified all formal bids submitted shall be binding for ninety (90) calendar days following bid opening date, unless the bidder, upon request of the Director of Purchasing, agrees to an extension.
2. **Bids for All or Part:** Unless otherwise specified by the County or by the Bidder, the County reserves the right to make award on all items, or on any of the items according to the best interests of the County. Bidder may restrict his/her bid to consideration in the aggregate by so stating but should name a unit price on each item bid upon; any bid in which the bidder names a total price for all the articles without quoting a price on each and every separate item, may be rejected at the option of the County.
3. **Catalogs:** Each Bidder shall submit where necessary or when requested by the Director of Purchasing, catalogs, descriptive literature, and detailed drawings, fully detailing features, designs, construction, finishes and the like necessary to fully describe the materials or work they propose to furnish.

4. **Collusive Bidding:** The Bidder certifies that his/her bid is made without any previous understanding, agreement or connection with any person firm, or corporation making a bid for the same project, without unlawful prior knowledge of competitive prices, and is in all respects fair, without outside control, collusion, fraud, or otherwise illegal action.
5. **Competency of Bidder:** No proposal shall be accepted from, or contract awarded to any person, firm or corporation that is in arrears or is in default to Washington County, Maryland upon any debt or contract, or that is a defaulter, as surety or otherwise, upon any obligation to said County, or had failed to perform faithfully any previous contract with the County. The Bidder, if requested, must present within forty-eight (48) hours evidence satisfactory to the Director of Purchasing of performance ability and possession of necessary facilities, pecuniary resources, and adequate insurance to comply with the terms of these specifications and contract documents.

The successful Bidder shall actively cooperate in all matters pertaining to the proper compliance of this contract and shall come to the office of the Director of Purchasing whenever requested in connection with the performance of this contract.

The successful Bidder shall inform the Director of Purchasing of any and all circumstances which may impede the progress of the work or inhibit the performance of the contract including, but not limited to bankruptcy, dissolution or liquidation, merger, sale of business, assignment, etc.

The County may examine the Bidder's and any first-tier subcontractor's records to determine and verify compliance with the contract. The Bidder and any first-tier subcontractor must grant the County access to these records at all reasonable times during the contract term and for three (3) years after final payment. If the contract is supported to any extent by Federal or State funds, the appropriate Federal or State authorities may also examine these records. The Bidder must include the preceding language of this paragraph in all first-time subcontracts.

6. **Completeness:** All information required by Invitation to Bid must be supplied to constitute a proper bid. The County shall not be responsible for the premature opening of Bids if not properly addressed or identified.
7. **Conditional Bids:** Qualified bids are subject to rejection in whole or in part.
8. **Confidentiality:** Firms shall give specific attention to the identification of those portions of their bids that they deem to be confidential, proprietary information or trade secrets and provide any justification why such materials, upon request, should not be disclosed by the County under the Access to Public Records Act, State Government Article, Title 10, Sections 10-611 to 10-628, Annotated Code of Maryland.
9. **Errors in Bids:** When an error is made in extending total prices, the written unit bid price shall govern. In the absence of written prices, the unit bid price shall govern. Carelessness in quoting prices, or in preparation of bid, otherwise, will not relieve the Bidder. *Erasures or changes in bids must be initialed.*
10. **General Guaranty:** Bidder agrees to:

- a. Save the County, its agents, and employees harmless from liability of any nature or kind for the use of any copyrighted or un-copyrighted composition, secret process, patented or unpatented, invention, article or appliance furnished or used in the performance of the contract which the Bidder is not the patentee, assignee, licensee or owner.
- b. Protect the County against latent defective material or workmanship and to repair or replace any damages or marring occasioned in transit or delivery.
- c. Furnish adequate protection against damage to all work and to repair damages of any kind, to the building or equipment, to their own work or to the work of other contractors, for which their worker is responsible due to the negligence in the course and scope of the employment.
- d. Pay for all permits, licenses and fees and give all notices and comply with all laws, ordinances, rules and regulations of the County and State of Maryland.

11. Illegal Immigrants:

- a. The Bidder shall comply with the Immigration and Nationality Act (INA) which includes provisions addressing employment eligibility, employment verification, and nondiscrimination. Under the INA, the Bidder may hire only persons who may legally work in the United States (i.e., citizens and nationals of the U.S.) and aliens authorized to work in the U.S. The Bidder shall verify the identity and employment eligibility of anyone employed or to be employed, including completion of the Employment Eligibility Verification Form (I-9). The Bidder shall establish appropriate procedures and controls to ensure that no services under this Contract will be performed by any worker who is not legally eligible to perform such services or for employment.
- b. Failure by the Bidder or his/her Sub-Contractors to comply with the provisions of Section 11.a. herein will be grounds for termination of the Contract.

12. Insurance: Liability insurance on all major divisions of coverage for each and every Bidder and subcontractor shall be required for the length of the contract. Bidder and subcontractor must supply evidence of insurance upon request. Each Bidder agrees to assist in every manner possible in the reporting and investigation of any accident, and upon request, agrees to cooperate with all interested insurance carriers in the handling of any claims by securing and giving evidence and obtaining the attendance of witnesses as required for any claim or suit. The Bidder shall be prepared to show evidence of insurance as required under Washington County's *Insurance Requirements for Independent Contractors Policy*, included herein, prior to the execution of any contract. The Bidder, if requested, shall provide the Certificate of Insurance to the Purchasing Department within ten (10) calendar days after receiving a request for it. Failure to provide an acceptable Certificate of Insurance within the time frame stated above shall be cause to terminate the contract(s). The certificate shall state that such insurance is in force and cannot be cancelled or released except upon thirty (30) days prior written notice to the County. If any of the stated coverages expire during the term of this contract, the Bidder shall deliver renewal certificates to the County at least ten (10) calendar days prior to the expiration.

13. **Interpretations, Discrepancies, Omissions:** Should any Bidder find discrepancies in, or omissions from the documents or be in doubt of their meaning, he/she should at once request, in writing, an interpretation from:

Brandi Naugle, CPPB – Buyer
Washington County Purchasing Department
Washington County Administration Complex
100 West Washington Street, Suite 3200
Hagerstown, MD 21740
FAX: 240-313-2331; or send in Microsoft Word
platform via email to: purchasingquestions@washco-md.net

All necessary interpretations will be issued to all Bidders in the form of addenda to the specifications, and such addenda shall become part of the contract documents. Exceptions as taken in no way obligates the County to change the specifications. Failure of any Bidder to receive any such addendum or interpretation shall not relieve such Bidder from any obligation under his/her bid as submitted. The County shall assume no responsibility for oral instructions or suggestions. ORAL ANSWERS WILL NOT BE BINDING ON THE COUNTY. Requests received after 4:00 P.M. on the date included in the Supplemental Terms and Conditions may not be considered.

14. **Landfill Tipping Fees:** Disposal of items shall be at an approved sanitary landfill and any fees for same must be included in the Bidder's proposal.
15. **Late Bids:** Formal bids or amendments thereto received by the County after the time specified for bid opening will not be considered. Bids received after the time specified for bid opening will be returned unopened.
16. **Mailing of Bids:** The County assumes no responsibility for the timely deliverance of mailed bids. Ample time should be allowed for the transmittal of bids by mail, and postmarks indicating the date of mailing will not be considered as evidence of intent to submit bids in proper time for the opening. If an emergency or unanticipated event interrupts normal County processes so as to cause postponement of the scheduled bid opening, the time specified for receipt of bids will be deemed to be extended to the same time of day specified in the solicitation on the first workday on which normal County processes resume or to such other date and time as may be provided by the Purchasing Department in a written notice to bidders.
17. **Maryland Buy American Steel Act:** In accordance with the Annotated Code of Maryland-State Finance and Procurement Article, Sections 17-301 – 17-306, Washington County is defined as a Public Body and as such shall require a Bidder or subcontractor to use or supply only American Steel products in the performance of a contract as stated in the above referenced Sections.
18. **Multiple Bids:** No Bidder shall be allowed to offer more than one (1) price on each item even though he/she may feel that there are two (2) or more types or styles that will meet specifications. Bidders must determine for themselves which to offer. If said Bidder should submit more than one (1) price on any item, all prices for that item may be rejected at the discretion of the Director of Purchasing.

19. **Officers Not to Benefit:** No member of the elected governing body of Washington County, Maryland, or members of his or her immediate family, including spouse, parents, or children, or any person representing, or purporting to represent any member or members of the elected governing body shall receive or be promised directly or indirectly, any financial benefit, by way of fee, political contribution, or any other similar form of remuneration and/or on the account of awarding and/or executing the contract and that upon request of the County, as a prerequisite to payment pursuant to the terms of this contract, there will be furnished to the requester, under oath, answers to any interrogatories related to a possible conflict of interest as herein embodied. The Bidder, to the best of his/her knowledge, whether he/she be an officer, director, partner or any of its employees directly involved in obtaining contracts with the State, or any County or other subdivision of the State, has not been convicted of bribery or conspiracy to bribe under the laws of any State or Federal Government. Any contract made or entered into where it is discovered that violation of the intent of this provision exists shall be declared null and void and all monies received by the Bidder shall be returned to the County.
20. **Payment Terms:** Bid prices are to be net thirty (30) calendar days; all discounts are to be deducted and reflected in net prices. Term discounts of less than twenty (20) calendar days will not be considered in connection with any prompt payment discount offered, time will be computed from date of receipt of correct invoice or receipt and acceptance of shipment, whichever is later.
21. **Procurement Policy Manual:** This bid is administered according to Washington County, Maryland's Procurement Policy Manual adopted by the Board of County Commissioners of Washington County, Maryland on June 25, 2013 and effective July 1, 2013. The contents of the aforementioned Manual may be requested from the Washington County Purchasing Department at 240-313-2330 or may be found on the web site at: <https://www.washco-md.net/wp-content/uploads/ProcurementPolicyManual2013FinalDraftrevised3-5-2020.pdf>.
22. **Proposal Forms:** Bids shall be submitted only on the forms provided by the County. The Bidder shall submit one (1) original bid on the forms provided with original signature, sealed to the County for that purpose. All bids must be enclosed in a sealed, opaque envelope marked with the title of the bid, company name and address, and be received in the Washington County Purchasing Department promptly on or before, time, date, and place stipulated on the Invitation to Bid. ***NO*** bids received after such stipulated time and date will be considered by the County. ***Facsimile Bids or any electronic bid submission will not be accepted.***
23. **Registration with Maryland Department of Assessments and Taxation:** Prior to contracting, private corporations must either be incorporated in the State of Maryland or registered with the Maryland Department of Assessments and Taxation as a foreign corporation and must be in good standing. Proof of such standing is required prior to the start of the contracting process and good standing shall be maintained for the duration of the contract. The website for the State Department of Assessments and Taxation is: <http://dat.maryland.gov/Pages/sdatforms.aspx#BNE>, email address is sdat.charterhelp@maryland.gov, and phone numbers are: (410) 767-1340 or (888) 246-5941.
24. **Reservations:** The County or its authorized agent reserves the right to reject any or all bids and to waive any informality or deficiency in bids received whenever such rejection or waiver is in the best interest of the County. The County also reserves the right to reject the bid of a Bidder who has previously failed to perform properly or complete on time contracts of a similar nature, or the Bid of a Bidder who investigation shows is not in a position to perform the contract. The County

reserves the right to waive minor differences in specifications provided these differences do not violate the specifications intent nor affect the operation for which the items are being purchased, nor increase estimated maintenance and repair cost to the County. The County reserves the right to award contracts or place orders on a lump sum or individual item basis, or such combination as shall, in its judgment, be in the best interest of the County.

25. **Response to Invitation:** In the event you cannot submit a bid on our requirements, as set forth in the “Invitation to Bid”, please return the Bid with an explanation as to why you are unable to bid on these requirements. Because of the large number of firms listed on the County’s lists of Bidders, it is necessary to delete from these lists the names of those persons, firms or corporations who fail to respond after having been invited to bid on a commodity or commodities for three (3) successive bid openings.
26. **Substitutions:** All equipment is to be supplied in exact accordance with the specifications. Any Bidder who contemplates offering a product that differs from that specified must obtain the County’s written approval prior to bid opening. Substitution requests must be received in the Purchasing Department no later than the date/time specified in the Supplemental Terms and Conditions. Requests received after the specified date/time will not be considered. All such decisions will be considered final and not subject to further recourse.
27. **Taxes-Responsibility for Payment, Exemptions, Forms to be Filed, etc.:**
 - a. The County is exempt from State of Maryland Sales Tax. The County’s Maryland Sales Tax Exemption Number is 3000129 2. However, the Bidder is responsible for making any necessary inquiries and investigations with regulating state agencies to obtain a determination of tax exemptions in his/her bid.
 - b. The Bidder is responsible for and by submitting a Bid agrees to pay all retail sales, income, real estate, sales and use, transportation, and special taxes applicable to and assessable against any materials, equipment, processes and operations incident to or involved in the Project. The Bidder is responsible for ascertaining and acquainting himself/herself with such taxes and making all necessary arrangements to pay same.
 - c. The Successful Bidder shall complete a W-9 Vendor Information form (provided by the County) and return it to the Director of Purchasing.
 - d. The County hereby reserves the right to withhold payment under this Contract until the Bidder and any subcontractor performing any duties under this Contract have furnished or caused to be furnished the Comptroller of the State of Maryland with all properly completed forms required by the said Comptroller and until all of said retail sales and/or use taxes due the State of Maryland by the Bidder have been paid and the Bidder exhibits a release or receipt from the Comptroller evidencing such payment.
 - e. The Bidder is hereby advised of Section 1-106(b)(3) of the Code of Public Local Laws of Washington County, MD: "If a bidder has not paid all taxes owed to the County or a municipal corporation in the County, the County Commissioners may reject the bidder’s bid."

28. **Withdrawal of Bids:** A written request for the withdrawal of a bid or any part thereof may be granted if the request is received by the County prior to the specified time of opening.

BID BONDS

1. **Bid Deposit - Bid Bond, Certified or Cashier's Check:** When required, each bid shall be accompanied by a bid bond signed by a surety company licensed to do business in the State of Maryland, or by a cashier's check, certified check or Treasurer's check drawn on a responsible bank doing business in the United States in the amount of five (5%) percent of the total Bid and shall be made payable to the Board of County Commissioners of Washington County, Maryland. When computing the amount of Bid for Check purposes, DO NOT deduct for trade-ins. U.S. Postal Money Orders are acceptable in lieu of checks.
2. **Performance/Labor and Material Bonds:** The successful Bidder(s) on this bid must furnish the required bonds as indicated on the bid cover, made out to the Board of County Commissioners of Washington County, Maryland, prepared on forms contained herein, or in his/her absence, on an approved form, as security for the faithful performance of his/her contract, within ten (10) calendar days of his/her notification that his/her bid has been accepted. The surety thereon must be such surety company or companies as are authorized and licensed to transact business in the State of Maryland. Attorneys in fact who sign bonds must file with each bond a certified copy of his/her power of attorney to sign bonds. The successful Bidder or Bidders upon failure or refusal to furnish within ten (10) calendar days after his/her notification the required bonds shall forfeit to the County, as liquidated damages his/her bid deposit. The Performance Bond shall be in the amount of one hundred (100%) percent of the contract price covering faithful performance of the contract; and the Labor and Materials Payment Bond shall be in the amount of one hundred (100%) percent of the contract price as security for payment of all persons performing labor and furnishing materials in connection therewith.

SPECIFICATIONS REFERENCES

1. **Formal Specifications:** The Bidder shall abide by and comply with the true intent of the specifications and not take advantage of any unintentional error or omission but shall fully complete every part as the true intent and meaning of the specifications and drawings. Whenever mention is made herein, of any article, material, or workmanship to be in accordance with laws, ordinances, building codes, underwriter's codes, A.S.T.M. regulations or similar expressions, the requirements of these laws, ordinances, etc., shall be construed to meet or exceed specification requirements and current established noise levels for specific equipment, materials, and/or services being furnished under this contract. All deviations from the specifications must be noted in detail by the Bidder, in writing, at the time of submittal of the formal bid. The absence of a written list of specification deviations at the time of submittal of the bid will hold the Bidder strictly accountable to the County to the specifications as written. Any deviation from the specifications as written not previously submitted, as required by the above, will be grounds for rejection of the material and/or equipment when delivered.
2. **Samples:** The Purchasing Department reserves the right to retain or destroy the samples submitted for the purpose of evaluation and will be free from any redress or claim on the part of the Bidder if any samples are lost or destroyed. Bidders shall make all arrangements for delivery of samples to the place designated, as well as the removal of samples. Cost of delivery and removal of samples

shall be borne by the Bidder. Upon notification by the Purchasing Department that a sample is available for pickup, it shall be removed within thirty (30) calendar days at the Bidder's expense, or the Director of Purchasing shall dispose of same at his/her discretion. All sample packages shall be marked "Sample for Purchasing Department" and each sample shall bear the name of the Bidder, item number, bid number, and shall be carefully tagged or marked in a substantial manner. Failure of the Bidder to clearly identify samples as indicated may be considered sufficient reason for rejection of bid.

- 3. Trade Names/Substitutions:** In cases where an item is identified by a manufacturer's name, trade name, catalog number, or reference it is understood that the Bidder proposes to furnish the item so identified and does not propose to furnish an "equal/substitution" unless submission of an "equal/substitution" is stated otherwise as permissible. Any Bidder who contemplates offering a product that differs from that specified must obtain the County's written approval by submission of his/her request no later than the deadline for receipt of substitution requests as stated in the Supplemental Terms and Conditions. The reference to the above catalog is intended to be descriptive but not restrictive and only to indicate to the prospective Bidder articles that will be satisfactory. Bids on makes and catalogs will be considered, provided each Bidder clearly states on the face of his/her proposal exactly what he/she proposes to furnish, and forwards with his/her bid, a cut, illustration, or other descriptive matter which will clearly indicate the character of the article covered by his/her bid. The Director of Purchasing hereby reserves the right to approve as an equal, or to reject as not being an equal, any article the Bidder proposes to furnish which contains major or minor variations from specification requirements but may comply substantially therewith. If no particular brand, model, or make is specified, and if no data are required to be submitted with the bid, and after award and before manufacture or shipment, the successful Bidder may be required to submit working drawings or detailed descriptive data sufficient to enable the Director of Purchasing to judge if each requirement of the specifications is being complied with.

AWARD

- 1. Award or Rejection of Bids:** For contracts of purchase, the contract shall be awarded to the lowest, responsive, and responsible Bidder complying with all the provisions of the Invitation, provided the bid price is reasonable and it is to the best interest of the County to accept it. For contracts of sale, the contract shall be awarded to the highest, responsive, and responsible Bidder complying with all the provisions of the Invitation, provided the bid price is to the best interest of the County to accept it.
- 2. Notice of Award:** A written award (or Acceptance of Bid) mailed (or otherwise furnished) to the successful Bidder within the time for acceptance as specified herein shall be deemed to result in a binding contract without further action by either party. The bid with respect to all items accepted and all papers accompanying the same, the general conditions and instructions to Bidders, the specifications, and other papers and documents referred to in any of the foregoing shall constitute the formal contract, unless otherwise specified, between the Bidder and the County.
- 3. Political Contribution Disclosure:** In accordance with Maryland Code, State Finance and Procurement Article, §17-402, the Bidder shall comply with Maryland Code, Election Law Article, Title 14, which requires that every person that enters into contracts, leases, or other agreements with the State, a county, or any incorporated municipality, or their agencies during a calendar year in which the person receives in the aggregate \$100,000 or more, shall file with the State

Administrative Board of Election Laws a statement disclosing contributions in excess of \$500 made during the reporting period to a candidate for elective office in any primary or general election. The statement shall be filed with the State Administrative Board of Election Laws: (1) before a purchase or execution of a lease or contract by the State, a county, an incorporated municipality or their agencies, and shall cover the preceding two (2) calendar years; and (2) if the contribution is made after the execution of a lease or contract, then twice a year, throughout the contract term, on: (a) February 5, to cover the 6-month period ending January 31; and (b) August 5, to cover the 6-month period ending July 31.

4. **“Requirements” Contract Bid Quantities:** On “Requirements” bids, acceptance shall bind the County to pay for, at unit bid prices, only quantities ordered and satisfactorily delivered. All stated quantities are estimated requirements and do not constitute a minimum or maximum.
5. **Responsibility/Qualifications of Bidder:** The County may make such investigations as it deems necessary to determine the ability of the Bidder to perform the work, and the Bidder shall furnish to the County all such information and data for this purpose as the County may request. The County reserves the right to reject any bid if the evidence submitted by, or investigation of, such Bidder fails to satisfy the County that such Bidder is properly qualified to carry out the obligation of the contract and to complete the work contemplated therein. Conditional bids will not be accepted. In determining responsibility, the following qualifications, in addition to price, shall be considered by the Director of Purchasing on contracts of purchase and on contracts of sale (if applicable):
 - a. The ability, capacity, and skill of the Bidder to perform the service required.
 - b. The character, integrity, reputation, judgment, experience, and efficiency of the Bidder.
 - c. The quality of performance of previous contracts or services.
 - d. The Bidder’s previous and present compliance with laws and ordinances relating to the contract or service.
 - e. The sufficiency of the financial resources and ability of the Bidder to perform the contract or provide the service.
 - f. The quality, availability and adaptability of the supplies, or services, to the particular use required.
 - g. The ability of the Bidder to provide future maintenance and service for the use of the subject of the contract.
 - h. Whether the Bidder is in arrears to the County on a debt or contract or is a defaulter on surety to the County.
 - i. Such other information as may be secured having a bearing on the decision to make the award.

In determining a Bidder's responsiveness, the Director of Purchasing shall consider material deviations from the advertised specifications which materially affect price, quantity, quality or limit the Bidder's liability.

6. **Specific Bid Quantities:** Where quantities are specifically stated, acceptance will bind the County to order quantities specified and to pay for, at contract prices, all such supplies or services delivered that meet specifications and conditions of the contract. However, the County will not be required to accept delivery of any balances unordered, as of the contract expiration date, unless Bidder furnishes the Director of Purchasing with a statement of unordered balances not later than ten (10) calendar days after the termination date of the contract.
7. **Tie Bids:** If two (2) or more Bidders shall be tied for the lowest bid on a purchase contract, quality and service being equal, the contract shall be awarded to a local Bidder. If there is no local Bidder, or more than one local Bidder, the County shall award the contract to one (1) of the Bidders by drawing lots in public.

CONTRACT PROVISIONS

1. **Availability of Funds:** A contract shall be deemed executory only to the extent of appropriations available to each County department/agency for the purchase of such articles. The County's extended obligation on those contracts that envision extended funding through successive fiscal periods shall be contingent upon actual appropriations for the succeeding fiscal year.
2. **Contract Alterations:** No alterations or variables in the terms of a contract shall be valid or binding upon the County unless made in writing and signed by the County or its authorized agent.
3. **Default:** The contract may be cancelled or annulled by the County in whole or in part by written notice of default to the Bidder upon non-performance or violation of contract terms. An award may be made to the next low Bidder, or articles specified may be purchased on the open market similar to those so terminated. In either event, the defaulting Bidder (or their surety) shall be liable to the County for costs to the County in excess of the defaulted contract prices: Provided, that the Bidder shall continue the performance of this contract to the extent not terminated under the provisions of this clause. Failure of the Bidder to deliver materials or services within the time stipulated on his/her bid, unless extended in writing by the Director of Purchasing, shall constitute contract default. In the event that a Bidder exempted from posting a Bid or Performance Guarantee fails to execute and perform any contract awarded to them, they shall forfeit the right to Bid on any future County contract for a period of time determined by the Director of Purchasing and they shall be liable for any costs incurred by the County as a result of his/her default.
4. **Guarantee:** All work, supplies, and/or materials and requirements described in the specifications including any modifications thereto which may be made in accordance with the direction and/or approval of the County Director of Purchasing shall be Guaranteed/Warranted for a period of one (1) year from the date of final acceptance by the County as follows, unless indicated otherwise in this contract:
 - a. Against all faulty or imperfect materials and/or equipment and against all imperfect, careless and/or unskilled workmanship.

- b. Against injury or undue deterioration from proper and usual use of the goods and/or services.
- c. Removal and replacement with proper materials, equipment, and/or services and re-execute, correct, or repair without cost to the County, any materials, equipment, and/or services found to be improper, imperfect, defective or fails to perform as specified.
- d. Make good all damage caused to other work, materials and/or equipment due to such required removal, replacement and/or re-execution.
- e. Shall comply with any and all guarantee/warranties of whatever nature referred to in other portions of the contract specifications.

Any warranties whether expressed or implied shall not reduce the risk of the seller's/manufacture's obligation to the County against latent defect which may be found during the rated life of the supplies and/or materials and requirements described in the specifications including any approved modifications.

- 5. **Intergovernmental Purchasing:** The following Agencies/Jurisdictions shall be able to purchase, if applicable, directly from contracts resulting from this Invitation to Bid (ITB): Washington County Public Schools and all of its public schools, Hagerstown Community College, Municipalities of Washington County, and public or quasi-public agencies that receive County money and are exempt from taxation under Section 501(c)(3) of the Internal Revenue Code, i.e., Washington County Volunteer Fire and Rescue Companies. While this ITB is prepared on behalf of the County, it is intended to apply for the benefit of the above-named agencies/jurisdictions as though they were expressly named throughout the document. Each of these agencies/jurisdictions may purchase from the successful Bidder under the same terms and conditions of the contract with the County, in accordance with each agencies/jurisdiction's respective laws and regulations, or an agency may choose not to procure from the successful Bidder at the agency's sole discretion. If one of the above-named agencies/jurisdictions elects to purchase under the contract, the price shall be determined by using unit costs and other pertinent costs provided in the offer. Any special discounts unique to a particular agency/jurisdiction shall be stated. Bidder shall also submit the attached "Provisions for Other Agencies" form, if included in this bid.
- 6. **New Goods, Fresh Stock:** All contracts, unless otherwise specifically stated, shall produce new commodities, fresh stock, latest model, design, or pack.
- 7. **Non-Discrimination:** No Bidder who is the recipient of County funds or who proposes to perform any work or furnish any goods under this agreement shall discriminate against any worker, employee or applicant or any member of the public because of religion, race, sex, color or national origin, age, marital status, physical or mental handicap, nor otherwise commit an unfair employment practice. Bidder further agrees that this article will be incorporated by Bidder in all contracts entered into with suppliers of materials or services, Bidders and subcontractors and all labor organizations, furnishing skilled, unskilled and craft union skilled labor, or who may perform any such labor or services in connection with this contract.
- 8. **Non-Liability:** The Bidder shall not be liable in damages for delay in shipment or failure to deliver when such delay or failure is the result of fire, flood, strike, act of God, act of government, act of

an alien enemy or by any other circumstances which, in the Director of Purchasing's opinion, is beyond the control of the Bidder. Under the circumstances, however, the County may in its discretion, cancel the contract.

9. **Placing of Orders:** Orders against contracts shall be placed with the Bidder on a Purchase Order executed and released by the Director of Purchasing.
10. **Subletting of Contract:** It is mutually understood and agreed that the Bidder shall not assign, transfer, convey, sublet, or otherwise dispose of their contract or their rights, title or interest therein, or their power to execute such contract, to any other person, firm or corporation, without the previous written consent of the County Director of Purchasing, but in no case shall such consent relieve the Bidder from his/her obligations, or change the terms of the contract.
11. **Termination of Contracts:** Contracts shall remain in force for full periods specified and until all articles ordered before date of termination shall have been satisfactorily delivered and accepted and thereafter until all requirements and conditions shall have been met, unless:
 - a. Terminated prior to expiration date by satisfactory deliveries of entire contract requirements.
 - b. Extended upon written authorization of the Director of Purchasing and accepted by Bidder, to permit ordering of unordered balances or additional quantities at contract prices and in accordance with contract terms.
12. **Termination for Convenience:** The performance of work under this Contract may be terminated by the County in accordance with this clause in whole, or from time to time in part, whenever the County shall determine that such termination is in the best interest of the County. The County shall pay all reasonable expenses associated with this Contract that the Contractor has incurred up to the date of termination, and all reasonable expenses associated with termination of the Contract; provided, however, the Contractor shall not be reimbursed for any anticipatory profits that have not been earned up to the date of termination.

DELIVERY PROVISIONS

1. **Delivery:** Delivery shall be required to the place designated in the specifications or on the proposal form. All prices must be FOB Destination, Inside Delivery. The weight, count, measure, etc. shall be determined at the points of delivery. The Bidder shall be required to furnish proof of delivery in every instance. Bulk materials are to be placed on skids or pallets. No help for unloading shall be provided by the County. Suppliers shall notify their shippers accordingly.
2. **Delivery Failures:** Failure of a Bidder to deliver within the time specified, or within a reasonable time as interpreted by the Director of Purchasing or failure to make replacements of rejected articles when so requested, immediately or as directed by the Director of Purchasing shall constitute authority for the Director of Purchasing to purchase in the open market articles of comparable grade to replace the articles rejected or not delivered. On all such purchases, the Bidder shall reimburse the County, within a reasonable time specified by the Director of Purchasing, for any expense incurred in excess of contract prices or the County may deduct such

amount from monies owed the defaulting Bidder. Such purchases shall be deducted from contract quantities.

3. **Inspections:** Inspection and acceptance of materials or supplies shall be made after delivery. Final inspection shall be conclusive except as regards latent defects, fraud, or such gross mistakes as amount to fraud. Final inspection and acceptance or rejection of the materials or supplies shall be made as promptly as practicable, but failure to inspect and accept or reject materials or supplies shall not impose liability on the County for such materials or supplies as are not in accordance with the specifications. All delivered materials shall be accepted subject to inspection and physical count.
4. **Hazardous Safety Data Sheets:** Any hazardous substances as defined under the Department of Labor Occupational Safety and Health Standard for General Industry (29-CFR-1910.1200) and State of Maryland Law and Regulations on "Access to Information About Hazardous and Toxic Substances", MDSH Article 89, Section 28-49-D, being delivered to Washington County, Maryland as a result of this Invitation to Bid shall be accompanied by a current "Hazardous Data Safety Sheet" or item may not be accepted.
5. **Packing Slips or Delivery Tickets:** All shipments or deliveries shall be accompanied by Packing Slips or Delivery Tickets and shall contain the following information for each item delivered. Bidders are cautioned that failure to comply with these conditions shall be considered sufficient reason for refusal to accept the goods.
 - The Purchase Order Number
 - The Name of the Article and Stock Number (Supplier's)
 - The Quantity Ordered
 - The Quantity Back Ordered
 - The Name of the Contractor
6. **Responsibility for Materials Shipped:** The Bidder shall be responsible for the materials or supplies covered by this contract until they are delivered at the designated point and the Bidder shall bear all risk on rejected materials or supplies after notice of rejection. Rejected materials or supplies must be removed by and at the expense of the Bidder promptly after notification of rejection unless public health and safety require immediate destruction or other disposal of rejected delivery. Upon failure of the Bidder to remove materials or supplies within ten (10) calendar days after date of notification, the County may return the rejected materials or supplies to the Bidder at the Bidder's risk and expense or dispose of them as its own property.
7. **Testing:** The cost of testing a representative sample of an order or shipment for acceptance shall be borne by the County. However, if the order and shipment is rejected for failure to meet the requirements of the specifications or purchase description, the cost of testing shall be charged to the Bidder.
8. **Time of Delivery:** Deliveries shall be accepted between 8:00 A.M. and 3:00 P.M. on weekdays only, unless stated otherwise in the bid document. No deliveries shall be accepted on Saturdays, Sundays or County Holidays, unless otherwise arranged by an individual Department/Agency.

PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF'S OFFICERS

SUPPLEMENTAL TERMS AND CONDITIONS

1. **Award:** Award of a contract shall be made to the responsive, responsible bidder with the lowest total sum bid. The successful Bidder(s) shall be notified of the award within sixty (60) consecutive calendar days from the date of the bid opening and shall complete successful delivery within forty-two (42) consecutive calendar days after receipt of any order.
2. **Competition:** To better ensure fair competition and to permit determination of lowest bidder, the name of the manufacturer, trade name, or manufacturer or vendor catalog number mentioned in the specifications is for the purpose of designating a standard or quality and type and for no other.
3. **Compliance:** If the Bidder fails to comply with the specifications, terms, and conditions, he/she will be given seven (7) consecutive calendar days' notice to render satisfactory service. If at the expiration of such seven (7) consecutive calendar days' notice, the unsatisfactory conditions have not been corrected, Owner reserves the right to cancel the contract.
4. **Contract Term:** The term of this Contract is for a one (1) year period beginning on the date of award by the Board with an option by the County to renew the contract for up to five (5) additional consecutive one (1) year periods subject to written notice given by the County at least sixty (60) consecutive calendar days before the expiration date of any one (1) year period. If the Bidder wishes to renew the contract, he/she must submit a letter of intent to the Director of Purchasing at least ninety (90) consecutive calendar days prior to the expiration of each contract period. Consideration for renewal shall be given on the basis of cost and performance. Bid prices must remain in effect through the first contract period and must include all costs for alterations and exchanges due to unsatisfactory workmanship or incorrect measurements. The County reserves the right to accept or reject any request for renewal and any increase in costs for each specified item that the Bidder may request at that time. All other terms and conditions shall remain unchanged.
5. **Delivery:**
 - a. Delivery shall be completed within forty-two (42) consecutive calendar days after receipt of any order. It is expressly understood that in the case of the failure of the vendor to complete the Performance of Contract within the specified time, liquidated damages will be assessed at the rate of one (1%) percent of the unit price per day for each day a unit of equipment exceeds the stipulated time for delivery.
 - b. All items shall be delivered, F.O.B., Destination, Inside Delivery to the Washington County Sheriff's Department, 500 Western Maryland Parkway, Hagerstown, Maryland, 21740 within forty-two (42) consecutive calendar days after order is placed. All items must be delivered on individual clothes hangers and must be identified as to the individual by tags or packages.

6. **Disputes:** In cases of disputes as to whether-or-not an item or service quoted or delivered meets specifications, the decision of the County Commissioners or authorized representative shall be final and binding on both parties. The County Purchasing Director may request in writing, the recommendation of the head of the County agency using the item or materials, or other objective sources.
7. **Estimated Quantities:** Quantities listed are based on current estimated annual needs but may be increased/decreased on the basis of additional seasonal needs and/or budgetary restrictions. Orders shall be placed for individual items by the County at any time during the contract period.
8. **Exceptions:** The submission of a bid shall be considered an agreement to all the items, conditions, and specifications provided herein and in the various bid documents unless specifically noted otherwise in the proposal.
9. **Interpretations, Discrepancies, Omissions:** Refer to General Conditions and Instructions to Bidders – General Conditions of Bidding, Section 13; requests received **after 4:00 P.M. on Wednesday, September 7, 2022** may not be considered. All correspondence in regard to this bid shall be directed to and issued by the Washington County Purchasing Department. **Direct all inquiries to Brandi Naugle, CPPB, County Buyer.**
10. **Payment:** Payment will be made within thirty (30) calendar days after satisfactory acceptance of uniforms upon invoices submitted in duplicate to the Washington County Sheriff's Department, 500 Western Maryland Parkway, Hagerstown, MD 21740. Liquidated damages will be assessed at the rate of one (1%) percent per day based on the unit price for each item not delivered within the stipulated time for delivery.
11. **Pre-Bid Conference/Teleconference:** Attendance at the Pre-Bid Conference on **Wednesday, August 31, 2022 at 10:00 A.M., (EDT/EST)** in the Washington County Administration Complex 100 West Washington Street, Third Floor Conference Room 3000, Hagerstown, Maryland is requested. Attendance is not mandatory but is strongly encouraged. Bidders who wish to participate in the teleconference, please call prior to the teleconference 240-313-2330 for further instructions.
12. **Quantities:** All stated quantities are estimated annual requirements and do not constitute a minimum or maximum. Prices, however, shall remain in effect for additional quantities for one (1) year from date of award. Unit prices shall also remain in effect if a lesser quantity than specified has to be ordered due to budgetary restraints. The vendor shall offer a price break on Star, Rank, and Shoulder patch order quantities of 250 or more.
13. **Substitutions:** Refer to General Conditions and Instructions to Bidders – General Conditions of Bidding, Section 26; all equipment is to be supplied in exact accordance with the specifications. Samples of "equivalent" uniform items must be supplied for the County's consideration as an "approved equal" to the Purchasing Director no later than **4:00 P.M., (EDT/EST) Wednesday, September 7, 2022**. Vendors will be informed in writing as to the acceptance of their proposed equivalents. All such decisions will be considered final and not subject to further recourse. Bids will only be considered by the County for the brand items as specified or the "County-approved" equals. Sample uniform items will not be returned at the County's expense. Vendors must bear all costs involved in the return of samples.

14. **Warranty:** One (1) year against workmanship or fabric defects except as specified otherwise herein except as stated otherwise in the Specifications contained herein. Warranted for life on the creases.
15. **Uniform Color and Quality:** The Washington County Sheriff's Department, at its sole discretion reserves the right to determine acceptance/rejection of the color and/or quality of any product supplied by the Bidder.
16. **Repair of Garments:** Bidders shall attach to the Form of Proposal information stating pricing per item for repairs, (i.e., trousers repair, seam repair). All repair work shall be returned to the Washington County Sheriff's Department no later than four (4) months from the initial pick up of the garment(s). If the garment is not repaired and delivered within four (4) months, there shall be no charge for the repair work.
17. **Responsibility of Bidder:** The vendor is responsible for taking the measurement of the individuals and providing measure to fit garments with alterations that includes shirt tampering and pants hemming for those individuals. All measurements shall be taken in the presence of an official designed by the Quartermaster. This official shall also be present at the try-on in the baste, shall approve alterations and acceptance of the finished product. Measurements shall be recorded, and the Washington County, Maryland representative shall retain one copy until acceptance of the final garment, at which time it will be surrendered upon demand by contractor. Acceptance or rejection of the garment shall be at the discretion of the above-designated official. One try-on in the baste is required and one alteration is permitted. If the uniform is judged to be unacceptable after one alteration, it will be rejected, and a new garment shall be produced. A rejected uniform may not be accepted after one alteration for any other individual. The vendor will within three weeks of notification respond to the Sheriff's Office for sizing/measuring of employees. The County cannot direct the vendor as to how to achieve this.
 - a. Prior to contracting, private corporations must either be incorporated in the State of Maryland or registered with the Maryland Department of Assessments and Taxation as a foreign corporation and must be in good standing. Proof of such standing is required prior to the start of the contracting process and shall remain in good standing during the contract period.
18. A copy of the 2020 bid tabulation (PUR-1453) can be viewed at:
<https://www.washco-md.net/wp-content/uploads/purch-pur-1453-bidtab.pdf>.
19. All clothing must be machine washable.

PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF'S OFFICERS

SCOPE OF WORK / SPECIFICATIONS

I. Uniform Dress Blouses

A. Scope:

1. This specification covers the requirements for the Uniform Blouses made from first quality 55% Dacron polyester and 45% worsted wool elastique fabric for Washington County Sheriff's and Correctional Officers.
2. The garments shall be custom made to measure according to individual measurements and fittings. Dress blouses must be manufactured in the USA.

B. Requirements:

1. First Quality 55% Dacron polyester and 45% worsted wool elastique fabric as detailed in specifications.
2. The production of the blouse shall be first class in every respect. All materials necessary to produce the blouse must be first quality and the garments shall be clean, well finished and pressed.
3. The Blouse is custom made. Measured sizing will be required. Custom fit blouses are to be made to individual measurements and fittings. Measurements are to be taken at Washington County Sheriff's Department.
4. All garments shall be manufactured in one establishment where sanitary conditions shall prevail. During normal working hours, the vendor's plant shall be open for inspection of work by duly authorized representatives of the Washington County Sheriff's Department.
5. The vendor shall demonstrate that facilities are available for promptly making necessary alterations, adjustments, and repairs.

C. Fabric Specifications:

1. Weave – Elastique
2. Weight – 16.5 Ounces per linear yard
3. Fiber Content – 55% Dacron Polyester / 45% Wool Worsted
4. Ply of Yarn – 2 Ply warp and filling

5. Uniform Dress Blouse Material – Raeford Mills #646-114

D. Blouse Fabrication:

1. Style: Four Button single breasted, button stand, notch lapel, form fitted, cut snug at waist, flare in shirt (Sam Browne Belt to be worn with all blouses, except for Captain and above in rank) cent vent omitted. Notch Lapel shall be 3-3/8" long from break and 1-3/8" top collar.
2. Collar: Shall be rolled to first button and shall have under collar 100% polyester needle punch felt, color to match outer shell cloth. Under collar shall be basted and felled at bottom.
3. Pockets: Blouse shall have two outside breast pockets with pleats and flaps which button down. The corners of the pockets shall be slightly round. The pleat in each pocket shall be 1-1/2" wide. The blouse shall also have two lower besom pockets with flaps, which will button down with 24 ligne buttons. Uniformity and spacing shall be maintained at the bottom of waist. The blouse shall also be constructed with two inside breast pockets. They shall be 5-3/4" wide by 6" deep. The pockets opening shall be neatly piped. Dimension for breast pockets and lower pockets shall be scaled in accordance with garment size and length. Please note that the upper breast pockets will have a scalloped flap and the lower pocket flaps will have straight flaps.
4. Back: Shall be constructed with double bi-swing back and a 1" elastic retractor. Two black belt hooks will be placed on the right and left rear below the bi-swing back. The ranks of Captain and above will not get belt hooks.
5. Lining: Full lining of polyester twill fabric, black in color. Front inner cloth shall be the best grade of non-woven fusible Pellon. There shall be no substitute for Pellon. Chest and shoulder of coat to be padded with hymo haircloth and felt, and to be sewn with two rows of blind stitching including one inch woven bridle tape.
6. Sleeve: The lining shall be the same as the body lining. Washington County Sheriff's Office or Correctional Emblems shall be placed on each sleeve 1" down from shoulder seam. No chevrons are required on the dress blouses.
7. Epaulets: Shall be 2-1/4" wide at shoulder seam and tapered to 1-1/2" and the point extending well under the collar. Each Button shall button near collar with a 24 ligne button. Epaulets to be boxed stitched. Please note that the Correctional Dress Blouse will have dark blue epaulets to match the class A-B trousers.
8. Seam: Outside body seams shall be plain. Shoulder seams shall be stayed around armhole with tape from back notch to front notch.

9. Outlets: Side Seams, 3/4" each side, 3/4" under seam. The turn up at the bottom of cuff shall be no less than 2-1/2". The turn up at the bottom of the coat shall be no less than 1-1/4".
10. Buttons: Front closure, four (4) 36 ligne metal buttons, pocket flaps and epaulets, six (6) 24 ligne. Maryland State Seal buttons as manufactured by the Waterbury Button Company will be required in gold finish for lieutenants and above, silver for all other ranks.
11. Buttonholes: Shall be cut first or after type, positioned 1/2" from edge of coat and finished with separate bar tacks.
12. Shoulder Pads: Shall be 1/2" thick needle punch type with 100% cotton padding fill.
13. Sewing Threads: All sewing threads shall be the best quality nylon, cotton polyester and blends of polyester and cotton as is applicable to specific seams. The manufacturer shall certify that the seams, sewing threads, tensile strength elongation and number of stitches per inch will withstand the stresses exerted in the performance of the normal duties of a law enforcement officer.
14. Top and Edge Stitching: Uniform 1/4" double stitching shall be used on all flaps, epaulets, breast pockets and at hem of blouses.
15. Cutting: Garments are to be cut from computerized patterns.
16. Fittings: All uniform garments, except Class C uniforms, shall be custom made to the measurements taken of the individual. All measurements shall be taken in the presence of an official designed by the quartermaster. This official shall also be present at the try-on in the baste, shall approve alterations and acceptance of the finished product. Measurements shall be recorded, and the Washington County representative shall retain one copy until acceptance of the final garment, at which time it will be surrendered upon demand by contractor. Acceptance or rejection of the garment shall be at the discretion of the above-designated official. One try-on in the baste is required and one alteration is permitted. If the uniform is judged to be unacceptable after one alteration, it will be rejected, and a new garment shall be produced. A rejected uniform may not be accepted after one alteration for any other individual.
17. Color: The color shall be French blue or as indicated on the fabric specification.
18. Labeling: All blouses are to be custom made for each individual officer. To be produced and filed in cad computer system, all blouses are to have a care label permanently affixed, with the Department name, Officer Name, Name of Manufacture, Specification, Size, and to have a tracking code, which corresponds to the packing slip and invoice number.

19. Cloth Badge Holder: There shall be a cloth badge holder sewn above the left breast pocket, 2” long and 1” wide, with two brass eyelets. Badge holder to be sewn all the way around.
20. Sleeve Stripes:
 - a. 1 row of 3/4” P&F serge, which will match the Sheriff’s Office trousers, will be placed on each sleeve for the rank of deputy, DFC, Cpl., and Sgt.
 - b. 1/2” gold vellum braid will be required on each sleeve for the rank of lieutenant (1 row), Captain (2 rows), Major (3 rows), Colonel (4 rows), and Sheriff (5 rows). When an Officer change rank the 1/2” gold vellum braid shall be sewn on each sleeve of the Dress Blouse at no extra charge and shall be provided by the vendor.
21. Certification: The vendor shall be responsible for all requirements, specification, standards, and shall certify compliance with all the above.
22. Emblems: On all Deputy Sheriffs uniform dress coats, a regulation Washington County Sheriff Emblem shall be attached to each sleeve, set 1" below shoulder seam. The emblem will match the current emblem in all ways and will be provided by the vendor. On all Corrections Officers uniform dress coats, a regulation Washington County Detention Emblem shall be attached to each sleeve, set 1” below shoulder seam. The emblem will match the current emblem in all ways, except the background field will be dark blue to match the class “A-B” trousers and the writing will be white. All emblems must be attached at no extra charge and shall be provided by the vendor.

II. Class “A-B” Trousers – Patrol, Judicial & Detention

Men’s Trouser Specifications, Option 1

Flying Cross by Fechheimer Item# F1 47780 86, Justice Hidden Cargo Trousers with 1” French Blue Stripe.

A. Fabric Specifications:

1. Content: 75% Polyester / 25% Wool
2. Weight: 12 oz. per linear yard
3. Weave: Serge
4. Color: LAPD Navy
5. Stripe: 1” French Blue

- B. Style: Trouser shall be manufactured from an up-to-date men's uniform trouser pattern. The trouser styling shall be T-1: plain front, two (2) quarter top front pockets, two (2) hip pockets professionally finished with no visible topstitching, two (2) club pockets and two (2) concealed cargo pockets. Work wear industrial style construction is unacceptable and shall be cause for rejection.
- C. Lining Material: The pocketing and fly lining material shall be 70% Polyester / 30% Cotton, 2.9 oz. per square yard (60" width) with a minimum 78 x 48 count. Pocketing must have a durable press finish and the color of the pocketing must be black.
- D. Freedom-Flex Waistband System: Trouser shall be made with a special Freedom-Flex Waistband System that will allow the wearer waist expansion of 2-1/2" to 3". The waistband shall measure a minimum of 1-7/8" wide when finished. The flexible expansion split portion of the waistband shall be to the front of the trouser side seam and there shall be a 3/4" wide side belt loop positioned to "hide" the expansion split of the waistband.

The waistband curtain shall consist of two different styles for maximum waistband expansion to enhance wearer comfort, fit, and appearance. The front of the trouser (to the expansion split) waistband curtain style shall consist of a 2" wide elastic section that incorporates Tru-Grip, a 1/2" surface area composed of thin 55-gauge rubber for maximum comfort and performance. The Tru-Grip acts to help keep shirts tucked in securely. (Use of a single silicone strip or strips instead of 1/2" wide rubberized surface area shall be cause for rejection.)

The back half of the trouser waistband curtain shall finish a minimum 2-1/8" wide and is to be made of black pocketing material and shall be attached to the top of the trouser with a zigzag stitch. The waistband curtain must also contain Tru-Grip and will line up with the Tru-Grip on the front of the expansion split. (Substitution of a silicone strip or strips in place of Tru-Grip shall not be acceptable and shall be cause for rejection.) The waistband curtain is composed of a wet laid non-woven canvas weighing 3.3 oz. per square yard. The canvas is covered in the same color and material as the pocketing. The 1/2" rubberized surface area is positioned 1-1/4" up from the bottom of the curtain.

The specifications for the rubberized Tru-Grip curtain are as follows:

1. Width: 1-1/8"
2. Warp: 300 Denier Texturized Polyester
3. Filling: 300 Denier Texturized Polyester
4. Rubber: 55 Gauge
5. Count: 32-36 yarns per inch
6. Contents: 59% Polyester / 41% Rubber

To complete the Freedom-Flex Waistband System, there shall be a 1-1/4" wide elastic component sewn into the back half of the waistband curtain to allow for the stretch and recovery of the waistband to comfortably fit the wearer's waist size. There shall be a bartack for strength and durability sewn at the stress point on the waistband where it joins the front elasticized waistband curtain joining stitching (positioned, on the waistband above the front pocket.)

The waistband closure shall be accomplished with one crush proof hook and eye centered on the waistband for wearer comfort. The hook and eye shall be reinforced with a 7/8" non-woven tape that is anchored with topstitching through and through to the top of the waistband (bartacks in place of topstitching shall be cause for rejection). In addition to the stitching of the waistband when it is set onto the trouser, the waistband must also be topstitched below the waistband seam of the trouser to be finished to allow for alterations (with ample fabric and curtain material to allow trouser size to be increased at least one size). The outlet in the seat is to be proportional to the waist outlet so the seat may also be let out. Seat seam must be sewn with a tandem needle machine (double-needle stitch) for maximum stretch.

- E. Belt loops: There shall be a minimum of seven (7) belt loops 3/4" in width of double thickness. Each loop must have a non-woven interlining for added durability. All loops (except back center) must be sewn into the top and bottom of the waistband ("dropped" belt loops that are tacked to the outside of the trouser all-around waist shall be cause for rejection). The top of the belt loops (except back center) shall be sewn into the waistband curtain seam with a Rocap machine using a zigzag stitch.

The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband to allow for easier waist alteration.

- F. Fly: Trouser shall have a brass metal zipper with memory lock brass slider secured by metal stopper at base. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic trouser fabric (tabs made of pocketing material or a "grown on" French Fly will be cause for rejection). The right fly shall be lined with the same material and color as the pocketing. The fly lining shall be sewn to the left fly continuing below the zipper into the crotch area in a neat and durable manner. A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. Topstitching of fly to be installed with automatic "J" stitch equipment eliminating puckering and providing a clean finish. There shall be a firm straight bartack at the bottom of the fly going through the zipper tape for maximum strength. Bartack shall line up with starting point of "J" stitch.

- G. Pockets: A specially designed front pocket shall be used so that it will expand and work in conjunction with the Freedom Flex Waistband System. There will be a 1/2" wide elastic attached to the front pockets and the waistband allowing for the recovery of the front pocket to wearer's most comfortable waist size position.

The two (2) front pockets will be quarter top style with a minimum opening of 6" and a minimum depth of 5-3/4" measured from the bottom of the opening. Front pockets to have

firm straight bartacks at top and bottom of pocket openings. Pockets shall be constructed using the stitch, turn, and topstitch method. Front pocket facing and barrier to be made of the basic trouser fabric. Facing shall be a minimum of 1" and barrier shall measure a minimum of 2" (measured to the inside edge of pocket lining).

The two (2) hip pockets shall have a minimum 5-3/8" wide (bartack to bartack) opening and a minimum depth of 5-3/4" measured from the bottom of the pocket opening. Hip pockets shall be constructed using the double welt method on an automatic welt machine. The welts shall be finished in such a manner that there is no topstitching (topstitched hip pockets shall be cause for rejection). The corners of the hip pocket openings shall have straight bartacks for reinforcement (use of triangular bartacks shall be cause for rejection). Hip pocket facing and barrier are to be made of basic trouser fabric. Facing shall be a minimum of 3/4" and the barrier shall be a minimum of 1-1/2". The left hip pocket shall have a centered tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of the tab to form an opening for a button. A button shall be located below the bottom welt corresponding in location with the tab, which shall be interlined with non-woven for added durability.

There shall be a dart centered above each hip pocket to waistband. Dart shall be approximately 2-3/4" long tapered from 3/8" at waistband and shall be installed with automatic equipment for a clean non-puckered finish.

The watch pocket shall be located on the right front. The front of the pocket shall be made of pocketing fabric and the back of the pocket shall be made of basic fabric and the two (2) pieces are securely stitched together. Each corner of the pocket opening shall have straight bartacks.

There shall be club pockets located 3-1/2" (plus or minus 1/4") below each hip pocket. The club pockets shall be 1-1/2" (plus or minus 1/4") from the side seam with a minimum opening of 3-1/2" and a minimum depth of 8". Pocketing material to be the same as side and hip pockets. Club pockets shall be constructed using the double welt method on a REECE PW machine and finished in such a manner that there is no topstitching (topstitched club pockets shall be cause for rejection). The corners of the club pockets shall have straight bartacks for reinforcing strength.

There shall be two (2) route book cargo pockets, one on each side seam. The pockets will be centered across the side seam and placed approximately 2" below the bottom of the front quarter-top pocket. Pocket opening shall close with a black nylon zipper. The measurements of the pocket shall be a minimum of 7" wide and a minimum of 8" deep.

- H. Seat: Seat must be sewn with a Tandem Needle Machine (double-needle stitch) for maximum durability.
- I. Creases: The leg creases, front and back will have a silicone bead put in by using the Super crease process.

- J. **Stitching, Pressing & Finishing:** Trouser must be stitched with matching thread. Trouser must be neatly pressed on Hothead Presses and properly shaped. Outseam and inseams are edge surged on automatic equipment for uniformity of quality and shall be pressed open for a smooth pucker-free finish with repeated cleaning and pressing. Trouser must be cleaned and finished to eliminate loose threads.
- K. **Stock Sizes:** Trouser must be available from stock in the following sizes:
 - 1. Short Rise: 28 - 42 (Even Only)
 - 2. Regular Rise: 28 - 64 (Even Only Over 38)
 - 3. Long Rise: 32 - 48 (Even Only)
- L. **Labels:** Trouser must have a permanent label providing care instructions and small woven label indicating waist size. A removable paper ticket showing the size, fabric content, cut number, and WPL or RN number must be on the outside of the waistband. Ticket to be matchbook style installed with plastic staples for easy removal without damaging trouser material and showing size when trousers are stacked.

III. Women's Trouser Specifications, Option 1

Flying Cross by Fechheimer Item# F1 47780W 86, Justice Hidden Cargo Trousers with 1" French Blue Stripe

- A. **Fabric:** Content: 75% Polyester / 25% Wool
Weight: 12 oz. per linear yard
Weave: Serge
Color: LAPD Navy
Stripe: 1" French Blue
- B. **Style:** Trouser shall be manufactured from an up-to-date women's uniform trouser pattern. The trouser styling shall be T-1: plain front, two (2) quarter top front pockets, two (2) hip pockets professionally finished with no visible topstitching, two (2) club pockets and two (2) concealed cargo pockets. Work wear industrial style construction is unacceptable and shall be cause for rejection.
- C. **Lining Material:** The pocketing and fly lining material shall be 70% Polyester / 30% Cotton, 2.9 oz. per square yard (60" width) with a minimum 78 x 48 count. Pocketing must have a durable press finish and the color of the pocketing must be black.
- D. **Freedom-Flex Waistband System:** Trouser shall be made with a special Freedom-Flex Waistband System that will allow the wearer waist expansion of 2-1/2" to 3". The waistband shall measure a minimum of 1-7/8" wide when finished. The flexible expansion split portion of the waistband shall be to the front of the trouser side seam and there shall be a 3/4" wide side belt loop positioned to "hide" the expansion split of the waistband.

The waistband curtain shall consist of two different styles for maximum waistband expansion to enhance wearer comfort, fit, and appearance. The front of the trouser (to the expansion split) waistband curtain style shall consist of a 2" wide elastic section that incorporates Tru-Grip, a 1/2" surface area composed of thin 55-gauge rubber for maximum comfort and performance. The Tru-Grip acts to help keep shirts tucked in securely. (Use of a single silicone strip or strips instead of 1/2" wide rubberized surface area shall be cause for rejection.)

The back half of the trouser waistband curtain shall finish a minimum 2-1/8" wide and is to be made of black pocketing material and shall be attached to the top of the trouser with a zigzag stitch. The waistband curtain must also contain Tru-Grip and will line up with the Tru-Grip on the front of the expansion split. (Substitution of a silicone strip or strips in place of Tru-Grip shall not be acceptable and shall be cause for rejection.)

The waistband curtain is composed of a wet laid non-woven canvas weighing 3.3 oz. per square yard. The canvas is covered in the same color and material as the pocketing. The 1/2" rubberized surface area is positioned 1-1/4" up from the bottom of the curtain.

The specifications for the rubberized Tru-Grip curtain are as follows:

Width: 1-1/8"

Warp: 300 Denier Texturized Polyester

Filling: 300 Denier Texturized Polyester

Rubber: 55 Gauge

Count: 32-36 yarns per inch

Contents: 59% Polyester / 41% Rubber

To complete the Freedom-Flex Waistband System, there shall be a 1-1/4" wide elastic component sewn into the back half of the waistband curtain to allow for the stretch and recovery of the waistband to comfortably fit the wearer's waist size. There shall be a bartack for strength and durability sewn at the stress point on the waistband where it joins the front elasticized waistband curtain joining stitching (positioned, on the waistband above the front pocket.)

The waistband closure shall be accomplished with one crush proof hook and eye centered on the waistband for wearer comfort. The hook and eye shall be reinforced with a 7/8" non-woven tape that is anchored with topstitching through and through to the top of the waistband (bartacks in place of topstitching shall be cause for rejection). In addition to the stitching of the waistband when it is set onto the trouser, the waistband must also be topstitched below the waistband seam of the trouser to be finished to allow for alterations (with ample fabric and curtain material to allow trouser size to be increased at least one size). The outlet in the seat is to be proportional to the waist outlet so the seat may also be let out. Seat seam must be sewn with a tandem needle machine (double-needle stitch) for maximum stretch.

- E. Belt Loops: There shall be a minimum of seven belt loops 3/4" in width of double thickness. Each loop must have a non-woven interlining for added durability. All loops (except back center) must be sewn into the top and bottom of the waistband ("dropped"

belt loops that are tacked to the outside of the trouser all-around waist shall be cause for rejection). The top of the belt loops (except back center) shall be sewn into the waistband curtain seam with a Rocap machine using a zigzag stitch. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband to allow for easier waist alteration.

- F. Fly: Trouser shall have a brass metal zipper with memory lock brass slider secured by metal stopper at base. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic trouser fabric (tabs made of pocketing material or a "grown on" French Fly will be cause for rejection). The right fly shall be lined with the same material and color as the pocketing. The fly lining shall be sewn to the left fly continuing below the zipper into the crotch area in a neat and durable manner. A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. Topstitching of fly to be installed with automatic "J" stitch equipment eliminating puckering and providing a clean finish. There shall be a firm straight bartack at the bottom of the fly going through the zipper tape for maximum strength. Bartack shall line up with starting point of "J" stitch.
- G. Pockets: A specially designed front pocket shall be used so that it will expand and work in conjunction the Freedom Flex Waistband System. There will be a 1/2" wide elastic attached to the front pockets and the waistband allowing for the recovery of the front pocket to wearer's most comfortable waist size position.

The two (2) front pockets will be quarter top style with a minimum opening of 6" and a minimum depth of 5-3/4" measured from the bottom of the opening. Front pockets to have firm straight bartacks at top and bottom of pocket openings. Pockets shall be constructed using the stitch, turn, and topstitch method. Front pocket facing and barrier to be made of the basic trouser fabric. Facing shall be a minimum of 1" and barrier shall measure a minimum of 2" (measured to the inside edge of pocket lining).

The two (2) hip pockets shall have a minimum 5-3/8" wide (bartack to bartack) opening and a minimum depth of 5-3/4" measured from the bottom of the pocket opening. Hip pockets shall be constructed using the double welt method on an automatic welt machine. The welts shall be finished in such a manner that there is no topstitching (topstitched hip pockets shall be cause for rejection). The corners of the hip pocket openings shall have straight bartacks for reinforcement (use of triangular bartacks shall be cause for rejection). Hip pocket facing and barrier are to be made of basic trouser fabric. Facing shall be a minimum of 3/4" and the barrier shall be a minimum of 1-1/2". The left hip pocket shall have a centered tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of the tab to form an opening for a button. A button shall be located below the bottom welt corresponding in location with the tab, which shall be interlined with non-woven for added durability. There shall be a dart centered above each hip pocket to waistband. Dart shall be approximately 2-3/4" long tapered from 3/8" at waistband and shall be installed with automatic equipment for a clean non-puckered finish.

The watch pocket shall be located on the right front. The front of the pocket shall be made of pocketing fabric and the back of the pocket shall be made of basic fabric and the two

pieces are securely stitched together. Each corner of the pocket opening shall have straight bartacks.

There shall be club pockets located 3 1/2" (plus or minus 1/4") below each hip pocket. The club pockets shall be 1 1/2" (plus or minus 1/4") from the side seam with a minimum opening of 3 1/2" and a minimum depth of 8". Pocketing material to be the same as side and hip pockets. Club pockets shall be constructed using the double welt method on a REECE PW machine and finished in such a manner that there is no topstitching (topstitched club pockets shall be cause for rejection). The corners of the club pockets shall have straight bartacks for reinforcing strength.

There shall be two route book cargo pockets, one on each side seam.

The pockets will be centered across the side seam and placed approximately 2" below the bottom of the front quarter-top pocket. Pocket opening shall close with a black nylon zipper. The measurements of the pocket shall be a minimum of 7" wide and a minimum of 8" deep.

- H. Seat: Seat must be sewn with a Tandem Needle Machine (double-needle stitch) for maximum durability.
- I. Creases: The leg creases, front and back will have a silicone bead put in by using the Super crease process.
- J. Stitching, Pressing & Finishing: Trouser must be stitched with matching thread. Trouser must be neatly pressed on Hothead Presses and properly shaped. Outseam and inseams are edge serged on automatic equipment for uniformity of quality and shall be pressed open for a smooth pucker-free finish with repeated cleaning and pressing. Trouser must be cleaned and finished to eliminate loose threads.
- K. Stock Sizes: Trouser must be available from stock in the following sizes:
Short Rise: 4 - 14
Regular Rise: 2 - 28
Long Rise: 14 – 20
- L. Labels: Trouser must have a permanent label providing care instructions and small woven label indicating waist size. A removable paper ticket showing the size, fabric content, cut number, and WPL or RN number must be on the outside of the waistband. Ticket to be matchbook style installed with plastic staples for easy removal without damaging trouser material and showing size when trousers are stacked.

IV. Men's Trouser Specifications, Option 2

Flying Cross by Fechheimer Item# 47280, Justice Four (4) Pocket Trousers with 1" French Blue Stripe

- A. Fabric: Raeford 05329-0SS-2851
Content: 75% Polyester / 25% Wool

Scope of Work / Specifications

Uniforms for Washington County Sheriff's Officers

PUR-1569

Page 29

Weight: 12oz. per linear yard
Weave: Serge
Color: LAPD Navy
Stripe: 1" French Blue

- B. Style: Trouser shall be manufactured from an up-to-date men's uniform trouser pattern. The trouser styling shall be T-1: plain front, two (2) quarter top front pockets, and two (2) hip pockets professionally finished with no visible topstitching. Work wear industrial style construction is unacceptable and shall be cause for rejection.
- C. Lining Material: The pocketing and fly lining material shall be 70% Polyester / 30% Cotton, 2.9 oz. per square yard (60" width) with a minimum 78 x 48 count. Pocketing must have a durable press finish and the color of the pocketing must be black.
- D. Freedom-Flex Waistband System: Trouser shall be made with a special Freedom-Flex Waistband System that will allow the wearer waist expansion of 2 1/2" to 3". The waistband shall measure a minimum of 1-7/8" wide when finished. The flexible expansion split portion of the waistband shall be to the front of the trouser side seam and there shall be a 3/4" wide side belt loop positioned to 'hide' the expansion split of the waistband.

The waistband curtain shall consist of two different styles for maximum waistband expansion to enhance wearer comfort, fit, and appearance.

The front of the trouser (to the expansion split) waistband curtain style shall consist of a 2" wide elastic section that incorporates Tru-Grip, a 1/2" surface area composed of thin 55-gauge rubber for maximum comfort and performance. The Tru-Grip acts to help keep shirts tucked in securely. (Use of a single silicone strip or strips instead of 1/2" wide rubberized surface area shall be cause for rejection).

The back half of the trouser waistband curtain shall finish a minimum 2-1/8" wide and is to be made of black pocketing material and shall be attached to the top of the trouser with a zigzag stitch. The waistband curtain must also contain Tru-Grip and will line up with the Tru-Grip on the front of the expansion split. (Substitution of a silicone strip or strips in place of Tru-Grip shall not be acceptable and shall be cause for rejection.)

The waistband curtain is composed of a wet laid non-woven canvas weighing 3.3 oz. per square yard. The canvas is covered in the same color and material as the pocketing. The 1/2" rubberized surface area is positioned 1-1/4" up from the bottom of the curtain.

The specifications for the rubberized Tru-Grip curtain are as follows:

Width: 1-1/8"
Warp: 300 Denier Texturized Polyester
Filling: 300 Denier Texturized Polyester
Rubber: 55 Gauge
Count: 32-36 yams per inch

To complete the Freedom-Flex Waistband System, there shall be a 1-1/4" wide elastic component sewn into the back half of the waistband curtain to allow for the stretch and recovery of the waistband to comfortably fit the wearer's waist size. There shall be a bartack for strength and durability sewn at the stress point on the waistband where it joins the front elasticized waistband curtain joining stitching (positioned, on the waistband above the front pocket.)

The waistband closure shall be accomplished with one crush proof hook and eye centered on the waistband for wearer comfort. The hook and eye shall be reinforced with a 7/8" non-woven tape that is anchored with topstitching through and through to the top of the waistband (bartacks in place of topstitching shall be cause for rejection).

In addition to the stitching of the waistband when it is set onto the trouser, the waistband must also be topstitched below the waistband seam of the trouser to be finished to allow for alterations (with ample fabric and curtain material to allow trouser size to be increased at least one size). The outlet in the seat is to be proportional to the waist outlet so the seat may also be let out. Seat seam must be sewn with a tandem needle machine (double-needle stitch) for maximum stretch.

- E. Belt Loops: There shall be a minimum of seven belt loops 3/4" in width of double thickness. Each loop must have a non-woven interlining for added durability. All loops (except back center) must be sewn into the top and bottom of the waistband ("dropped" belt loops that are tacked to the outside of the trouser all-around waist shall be cause for rejection). The top of the belt loops (except back center) shall be sewn into the waistband curtain seam with a Rocap machine using a zigzag stitch. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband to allow for easier waist alteration.
- F. Fly: Trouser shall have a brass metal zipper with memory lock brass slider secured by metal stopper at base. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic trouser fabric (tabs made of pocketing material or a "grown on" French Fly will be cause for rejection). The right fly shall be lined with the same material and color as the pocketing. The fly lining shall be sewn to the left fly continuing below the zipper into the crotch area in a neat and durable manner. A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. Topstitching of fly to be installed with automatic "J" stitch equipment eliminating puckering and providing a clean finish. There shall be a firm straight bartack at the bottom of the fly going through the zipper tape for maximum strength. Bartack shall line up with starting point of "J" stitch.
- G. Pockets: The two (2) front pockets will be quarter top style with a minimum opening of 7" and a minimum depth of 5-3/4" measured from the bottom of the opening. Front pockets to have firm straight bartacks at top and bottom of pocket openings. Pockets shall be constructed using the stitch, turn, and topstitch method. Front pocket facing and barrier to be made of the basic trouser fabric. Facing shall be a minimum of 1" and barrier shall measure a minimum of 2" (measured to the inside edge of pocket lining).

The two (2) hip pockets shall have a minimum 5-3/8" wide (bartack to bartack) opening and a minimum depth of 5-3/4" measured from the bottom of the pocket opening. Hip pockets shall be constructed using the double welt method on an automatic welt machine. The welts shall be finished in such a manner that there is no topstitching (topstitched hip pockets shall be cause for rejection). The corners of the hip pocket openings shall have straight bartacks for reinforcement (use of triangular bartacks shall be cause for rejection). Hip pocket facing and barrier are to be made of basic trouser fabric. Facing shall be a minimum of 3/4" and the barrier shall be a minimum of 1-1/2". The left hip pocket shall have a centered tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of the tab to form an opening for a button.

A button shall be located below the bottom welt corresponding in location with the tab, which shall be interlined with non-woven for added durability. There shall be a dart centered above each hip pocket to waistband. Dart shall be approximately 2-3/4" long tapered from 3/8" at waistband and shall be installed with automatic equipment for a clean non-puckered finish.

The watch pocket shall be located on the right front at the waistband. This pocket shall have a minimum opening of 2-5/8" and a minimum depth of 2-7/8". The front of the pocket shall be made of pocketing fabric and the back of the pocket shall be made of basic fabric and the two pieces are securely stitched together. Each corner of the pocket opening shall have firm straight bartacks.

- H. Seat: Seat must be sewn with a Tandem Needle Machine (double-needle stitch) for maximum durability.
- I. Creases: The leg creases, front and back will have a silicone bead put in by using the Lintrak process.
- J. Stitching, Pressing & Finishing: Trouser must be stitched with matching thread. Trouser must be neatly pressed on Hothead Presses and properly shaped.

Outseam and inseams are edge serged on automatic equipment for uniformity of quality and shall be pressed open for a smooth pucker-free finish with repeated cleaning and pressing. Trouser must be cleaned and finished to eliminate loose threads.

- K. Stock Sizes: Trouser must be available from stock in the following sizes:

Short Rise: 28 – 42 (Even Only)
Regular Rise: 28 – 60 (Even Only Over 38)
Long Rise: 32 – 48 (Even Only)

- L. Labels: Trouser must have a permanent label providing care instructions and small woven label indicating waist size. A removable paper ticket showing the size, fabric content, cut number, and WPL or RN number must be on the outside of the waistband. Ticket to be matchbook style installed with plastic staples for easy removal without damaging trouser material and showing size when trousers are stacked.

V. Women's Trouser Specifications, Option 2

Flying Cross by Fechheimer Item# F1 47280W, Justice Four (4) Pocket Trousers

- A. Fabric: Raeford 05329-0SS-2851
Content: 75% Polyester / 25% Wool
Weight: 12oz. per linear yard
Weave: Serge
Color: LAPD Navy
Stripe: 1" French Blue
- B. Style: Garment shall be manufactured from an up-to-date women's ProX pattern for comfort and easier sizing. The trouser styling shall be T-1: plain front, two (2) quarter top front pockets, and two (2) hip pockets professionally finished with no visible topstitching. Work wear industrial style construction is unacceptable and shall be cause for rejection.
- C. Lining Material: The pocketing and fly lining material shall be 70% Polyester / 30% Cotton, 2.9 oz. per square yard (60" width) with a minimum 78 x 48 count. Pocketing must have a durable press finish and the color of the pocketing must be black.
- D. Freedom-Flex Waistband System: Trouser shall be made with a special Freedom-Flex Waistband System that will allow the wearer waist expansion of 2 1/2" to 3". The waistband shall measure a minimum of 1-7/8" wide when finished. The flexible expansion split portion of the waistband shall be to the front of the trouser side seam and there shall be a 3/4" wide side belt loop positioned to 'hide' the expansion split of the waistband.

The waistband curtain shall consist of two different styles for maximum waistband expansion to enhance wearer comfort, fit, and appearance. The front of the trouser (to the expansion split) waistband curtain style shall consist of a 2-inch-wide elastic section that incorporates Tru-Grip, a 1/2" surface area composed of thin 55-gauge rubber for maximum comfort and performance. The Tru-Grip acts to help keep shirts tucked in securely. (Use of a single silicone strip or strips instead of 1/2" wide rubberized surface area shall be cause for rejection).

The back half of the trouser waistband curtain shall finish a minimum 2-1/8" wide and is to be made of black pocketing material and shall be attached to the top of the trouser with a zigzag stitch. The waistband curtain must also contain Tru-Grip and will line up with the Tru-Grip on the front of the expansion split. (Substitution of a silicone strip or strips in place of Tru-Grip shall not be acceptable and shall be cause for rejection.)

The waistband curtain is composed of a wet laid non-woven canvas weighing 3.3 oz. per square yard. The canvas is covered in the same color and material as the pocketing. The 1/2" rubberized surface area is positioned 1-1/4" up from the bottom of the curtain.

The specifications for the rubberized Tru-Grip curtain are as follows:

Width: 1-1/8"

Warp: 300 Denier Texturized Polyester
Filling: 300 Denier Texturized Polyester
Rubber: 55 Gauge
Count: 32-36 yams per inch
Contents: 59% Polyester / 41% Rubber

To complete the Freedom-Flex Waistband System, there shall be a 1-1/4" wide elastic component sewn into the back half of the waistband curtain to allow for the stretch and recovery of the waistband to comfortably fit the wearer's waist size. There shall be a bartack for strength and durability sewn at the stress point on the waistband where it joins the front elasticized waistband curtain joining stitching (positioned, on the waistband above the front pocket.)

The waistband closure shall be accomplished with one crush proof hook and eye centered on the waistband for wearer comfort. The hook and eye shall be reinforced with a 7/8" non-woven tape that is anchored with topstitching through and through to the top of the waistband (bartacks in place of topstitching shall be cause for rejection). In addition to the stitching of the waistband when it is set onto the trouser, the waistband must also be topstitched below the waistband seam of the trouser to be finished to allow for alterations (with ample fabric and curtain material to allow trouser size to be increased at least one size). The outlet in the seat is to be proportional to the waist outlet so the seat may also be let out. Seat seam must be sewn with a tandem needle machine (double-needle stitch) for maximum stretch.

- E. Belt Loops: There shall be a minimum of seven belt loops 3/4" in width of double thickness. Each loop must have a non-woven interlining for added durability. All loops (except back center) must be sewn into the top and bottom of the waistband ("dropped" belt loops that are tacked to the outside of the trouser all-around waist shall be cause for rejection). The top of the belt loops (except back center) shall be sewn into the waistband curtain seam with a Rocap machine using a zigzag stitch. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband to allow for easier waist alteration.
- F. Fly: Trouser shall have a brass metal zipper with memory lock brass slider secured by metal stopper at base. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic trouser fabric (tabs made of pocketing material or a "grown on" French Fly will be cause for rejection). The right fly shall be lined with the same material and color as the pocketing. The fly lining shall be sewn to the left fly continuing below the zipper into the crotch area in a neat and durable manner.

A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. Topstitching of fly to be installed with automatic "J" stitch equipment eliminating puckering and providing a clean finish. There shall be a firm straight bartack at the bottom of the fly going through the zipper tape for maximum strength. Bartack shall line up with starting point of "J" stitch.

- G. Seat: Seat must be sewn with a Tandem Needle Machine (double-needle stitch) for maximum durability.
- H. Pockets: The two (2) front pockets will be quarter top style with a minimum opening of 6" and a minimum depth of 4-1/2" measured from the bottom of the opening. Front pockets to have firm straight bartacks at bottom of pocket openings. Pockets shall be constructed using the stitch, turn, and topstitch method. Front pocket facing and barrier to be made of the basic trouser fabric. Facing shall be a minimum of 1" and barrier shall measure a minimum of 2" (measured to the inside edge of pocket lining).

The two (2) hip pockets shall have a minimum 5-3/8" wide (bartack to bartack) opening and a minimum depth of 5-3/4 " measured from the bottom of the pocket opening. Hip pockets shall be constructed using the double welt method on an automatic welt machine. The welts shall be finished in such a manner that there is no topstitching (topstitched hip pockets shall be cause for rejection). The corners of the hip pocket openings shall have straight bartacks for reinforcement (use of triangular bartacks shall be cause for rejection). Hip pocket facing and barrier to be made of basic trouser fabric. Facing shall be a minimum of 3/4" and the barrier shall be a minimum of 1-1/2". The left hip pocket shall have a centered tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of the tab to form an opening for a button. A button shall be located below the bottom welt corresponding in location with the tab, which shall be interlined with non-woven for added durability. There shall be a dart centered above each hip pocket to waistband. Dart shall be approximately 2-3/4" long tapered from 3/8" at waistband and shall be installed with automatic equipment for a clean non-puckered finish.

- I. Creases: The leg creases, front and back will have a silicone bead put in by using the Lintrak process.
- J. Stitching, Pressing & Finishing: Trouser must be stitched with matching thread. Trouser must be neatly pressed on Hothead Presses and properly shaped. Outseam and inseams are edge serged on automatic equipment for uniformity of quality and shall be pressed open for a smooth pucker-free finish with repeated cleaning and pressing. Trouser must be cleaned and finished to eliminate loose threads.
- K. Stock Sizes: Trouser must be available from stock in the following sizes:

Short Rise: 4 – 14 (Even Only)
Regular Rise: 2 – 26 (Even Only)
- L. Labels: Trouser must have a permanent label providing care instructions and small woven label indicating waist size. A removable paper ticket showing the size, fabric content, cut number, and WPL or RN number must be on the outside of the waistband. Ticket to be matchbook style installed with plastic staples for easy removal without damaging trouser material and showing size when trousers are stacked.

VI. Class "A-B" Men's Shirt Specifications – Patrol, Judicial & Detention

Men's Long Sleeve Shirt Specifications

Flying Cross by Fechheimer Item# 05W84, Justice Shirts

A. Fabric:

Content: Stock Dyed 75% Dacron Polyester / 25% Wool with Natural Stretch

Weight: 9.0 to 9.50 oz. / linear yard

Color: French Blue

B. Style: To be Flying Cross Model 05W8426. Dress style, top center placket front, full cut tapered fit, Freedom collar, long sleeves with barrel cuffs, and dress shirttail. Two pleated breast pockets with topstitched scalloped flaps. Topstitched shoulder straps. Exterior badge holder with metal eyelets. Matching inside yoke and collar band of high lustre PolyTwill. Work wear industrial style shirt construction is unacceptable and shall be cause for rejection.

C. Collar & Stand: Collar points to measure 3" long with ultrasonically fused-in Mylar stays. Collar to have woven interlining of #250 Dacron. Stays to be 2-3/4" long, 3/8" minimum width, and to be fused to underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar height at rear 1-1/2". Collar topstitched 1/4" off the edge. Collar stand to measure 1-5/16" at rear and band to be interlined with "Crease N Tack." collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.

D. Freedom Collar Feature: Material consisting of self-goods and lining material forming the neckband and the collar must be arranged with the weave thereof on a bias so that it is stretchable in the direction parallel to the circumferential direction of the collar. This expandable collar will allow for slight variations in neck size and make it easier to button because of the stretch or yield of the material.

E. Front: The shirt is to have a hidden zipper front, which is to be molded flat. The left front shall have a top center placket 1-1/2" wide with two rows of stitches 7/8" apart. The shirt will have seven (7) buttons and buttonholes on the front; spacing between each will be 3-3/4" except the spacing between the neck button and the first button on the front, which will be approximately 3-1/4".

Top center placket to have woven interlining of #250 Dacron. Non-woven interlining unacceptable and shall be cause for rejection. The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable.

F. Shoulder Straps: Shoulder straps to be two-piece pointed, 1/4" topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched

approximately 2" from sleeve seam. Shoulder strap to be interlined with #250 Dacron. Shoulder strap to have functional buttonhole to attach to metal button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable.

Shoulder straps will accommodate a removable 24 ligne metal button, (Silver for Deputy, Deputy First Class, Master Deputy, Corporal & Sergeant and Brass for Lieutenant, Captain, Major, Colonel & Sheriff).

Detention Division – Shoulder Straps are same color as issued pants, LAPD Navy.

- G. Badge Reinforcement: Exterior holder to finish 1-1/8" wide by 2-1/4" deep with two metal eyelets positioned vertically 1-1/4" apart with bottom eyelet centered 1-1/4" above left pocket flap.
- H. Pockets: Two breast patch pockets with mitered corners and 1-1/2" stitched pleats. Pleats shall be stitched top and bottom and full length of pleat to prevent spreading. Pocket to measure 5-5/8" wide, 6" deep. Left breast pocket to have 1- 1/2" pencil stitch. Each pocket to have hook Velcro, 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.
- I. Flaps: Two piece deep scalloped design to measure 5-7/8" across and 2-3/4" in depth at center point, 2-1/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Left flap to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.) Flaps to be 1/4" topstitched. Flaps to have woven interlining of #250 Dacron. Creased and edge stitched pocket flap construction unacceptable. Under side of the flap to have looped Velcro 3/4" long by 1/2" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.
- J. Sleeves: Sleeve vent shall be a minimum of 4-1/2" long with one-piece top and bottom facings. Facing to measure 1-1/8" wide point blocked at top.
- K. Cuffs: Two-piece 1/2" hemmed cuff with 1/4" topstitching. Cuffs to measure 3" in depth with rounded corners (barrel cuffs). Cuffs to have two buttons and corresponding buttonholes set vertically with one button and buttonhole in center of facing. Cuffs to have woven interlining of #250 Dacron.
- L. Buttons: First grade 20-ligne melamine buttons for shirt, with exception of the epaulets and flaps. Metal buttons to be Maryland State Seal type as manufactured by the Waterbury Button Company. Rank of Lieutenant, and above are to have gold finish, all others to have silver finish.
- M. Emblems: A regulation Washington County Sheriff Emblem shall be attached to each sleeve, set 1" below shoulder seam. The emblem will match the current emblem division in all ways and will be provided by the vendor (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve an emblem that is acceptable to

the Sheriff's Office). All emblems must be attached at no extra charge. Where needed, a regulation Washington County Sheriff's Office Chevron shall be attached to both sleeves, placed directly below the shoulder emblem. The Chevron will match the current Chevron in all ways and will be provided by the vendor (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve a Chevron that is acceptable to the Sheriff's Office). The emblems and chevrons must be attached at no extra charge and shall be provided by the vendor. (See Attachments for illustration).

- N. Sewing: Collar, shoulder straps, pocket flaps and cuffs to be topstitched 1/4" off the edge. Sleeve inserting and side close felling seams are to be safety stitched.
- O. Thread: All sewing threads to be color fast polyester wrap to match.
- P. Interlinings: Collar, cuffs, pocket flaps, straps, and top center to be interlined with #250 Dacron. Collar band interlining to be Crease-N-Tack.
- Q. Military Creases: There shall be five sharp silicone military creases on all shirts. One crease on each front to be centered vertically. Front creases shall be through pockets and flaps. Spacing for three military creases across shirt back to be proportionate to the size of the shirt.
- R. Construction: Collars, flaps, shoulder straps, and cuffs are made with conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned right side out and finally topstitched.
- S. Stock Sizes:

Shirts must be available in the following sizes:

Sleeve lengths: 32-37 inches
Neck sizes: 14-1/2 to 18-1/2, 19, 20, 21, 22

VII. Women's Long Sleeve Shirt Specifications

Flying Cross by Fechheimer Item# 105W84, Justice Shirts

- A. Fabric:

Content: Stock Dyed 75% Dacron Polyester / 25% Wool with Natural Stretch
Weight: 9.0 to 9.50 oz. / linear yard
Color: French Blue
- B. Style: To be Flying Cross Model 105W8426. Dress style, top center placket front, full cut tapered fit, Freedom collar, long sleeves with barrel cuffs, and dress shirttail. Two (2) pleated breast pockets with topstitched scalloped flaps. Topstitched shoulder straps. Exterior badge holder with metal eyelets. Matching inside yoke and collar band of high

lustre PolyTwill. Work wear industrial style shirt construction is unacceptable and shall be cause for rejection.

- C. Collar & Stand: Collar points to measure 2 7/8" long with ultrasonically fused-in Mylar stays. Collar to have woven interlining of #250 Dacron. Stays to be 2-1/2" long, 3/8" minimum width, and to be fused to underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar height at rear 1-1/2". Collar topstitched 1/4" off the edge. Collar stand to measure 1-5/16" at rear and band to be interlined with "Crease N Tack." Collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.
- D. Freedom Collar Feature: Material consisting of self-goods and lining material forming the neckband and the collar must be arranged with the weave thereof on a bias so that it is stretchable in the direction parallel to the circumferential direction of the collar. This expandable collar will allow for slight variations in neck size and make it easier to button because of the stretch or yield of the material.
- E. Front: The shirt is to have a hidden zipper front, which is to be molded flat. The right front shall have a top center placket 1-1/2" wide with two(2) rows of stitches 7/8" apart. The shirt will have six (6) buttons and buttonholes on the front; spacing between each will be 3-1/2" except the spacing between the neck button and the first button on the front, which will be 3-1/4". Top center placket to have woven interlining of #250 Dacron. Non-woven interlining unacceptable and shall be cause for rejection.

The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three (3) are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable.

- F. Shoulder Straps: Shoulder straps to be two-piece pointed, 1/4" topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched approximately 2" from sleeve seam. Shoulder strap to be interlined with #250 Dacron. Shoulder strap to have functional buttonhole to attach to metal button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable. Shoulder straps will accommodate a removable 24 ligne metal button, (Silver for Deputy, Deputy First Class, Master Deputy, Corporal & Sergeant and Brass for Lieutenant, Captain, Major, Colonel & Sheriff). Detention Division – Shoulder Straps are same color as issued pants, LAPD Navy.
- G. Badge Reinforcement: Exterior holder to finish 1-1/8" wide by 2-1/4" deep with two metal eyelets positioned vertically 1-1/4" apart with bottom eyelet centered 1-1/4" above left pocket flap.
- H. Pockets: Two breast patch pockets with mitered corners and 1-1/4" stitched pleats. Pleats shall be stitched top and bottom and full length of pleat to prevent spreading.

Pocket to measure 5" wide, 5" deep. Each pocket to have hook Velcro, 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as

specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.

- I. Flaps: Two piece deep scalloped design to measure 5-1/4" across and 2-1/4" in depth at center point, 1-3/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Left flap to have invisible pencil opening 1-1/4". (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.) Flaps to be 1/4" topstitched. Flaps to have woven interlining of #250 Dacron. Creased and edge stitched pocket flap construction unacceptable. Under side of the flap to have looped Velcro 3/4" long by 1/2" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.
- J. Sleeves: Sleeve vent shall be a minimum of 4-1/2" long with one-piece top and bottom facings. Facing to measure 1-1/8" wide point blocked at top.
- K. Cuffs: Two-piece 1/2" hemmed cuff with 1/4" topstitching. Cuffs to measure 2 1/2" in depth with rounded corners (barrel cuffs). Cuffs to be two button adjustable. Cuffs to have woven interlining of #250 Dacron.
- L. Buttons: First grade 20-ligne melamine buttons for shirt, with exception of the epaulets and flaps. Metal buttons to be Maryland State Seal type as manufactured by the Waterbury Button Company. Rank of Lieutenant, and above are to have gold finish, all others to have silver finish.
- M. Emblems: A regulation Washington County Sheriff Emblem shall be attached to each sleeve, set 1" below shoulder seam. The emblem will match the current emblem division in always and will be provided by the vendor (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve an emblem that is acceptable to the Sheriff's Office). All emblems must be attached at no extra charge. Where needed, a regulation Washington County Sheriff's Office Chevron shall be attached to both sleeves, placed directly below the shoulder emblem. The Chevron will match the current Chevron in all ways and will be provided by the vendor (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve a Chevron that is acceptable to the Sheriff's Office). The emblems and chevrons must be attached at no extra charge and shall be provided by the vendor. (See Attachments for illustration).
- N. Sewing: Collar, shoulder straps, pocket flaps and cuffs to be topstitched 1/4" off the edge. Sleeve inserting and side close felling seams are to be safety stitched.
- O. Thread: All sewing threads to be color fast polyester wrap to match.
- P. Interlinings: Collar, cuffs, pocket flaps, straps, and top center to be interlined with #250 Dacron. Collar band interlining to be Crease-N-Tack.
- Q. Military Creases: There shall be five (5) sharp silicone military creases on all shirts. One crease on each front to be centered vertically. Front creases shall be through pockets and

flaps. Spacing for three military creases across shirt back to be proportionate to the size of the shirt.

R. Construction: Collars, flaps, shoulder straps, and cuffs are made with conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned right side out and finally topstitched.

S. Stock Sizes:

Shirts must be available in the following sizes:

Bust sizes: 28-52

Long Sleeve Lengths:

28, 30 Regular = 30"

32, 34 Regular = 30" Long = 31"

36, 38 Regular = 31" Long = 32"

40, 42 Regular = 32" Long = 33"

44, 46 Regular = 33" Long = 34"

48 & Up Regular = 34" Long = 35"

VIII. Men's Short Sleeve Shirt Specifications

Flying Cross by Fechheimer Item# 55R84, Justice Shirts

A. Fabric:

Content: Stock Dyed 75% Dacron Polyester / 25% Wool with Natural Stretch

Weight: 9.0 to 9.50 oz. / linear yard

Color: French Blue

B. Style: To be Flying Cross Model 55R8426. Dress style, top center placket front, full cut tapered fit, convertible collar, short sleeves, and dress shirttail. Two pleated breast pockets with topstitched scalloped flaps. Topstitched shoulder straps. Exterior badge holder with metal eyelets. Matching inside yoke and banana band of high lustre PolyTwill. Work wear industrial style shirt construction is unacceptable and shall be cause for rejection.

C. Collar: Convertible collar shall be one piece. Collar points to measure 3" long with ultrasonically fused-in Mylar stays. Collar to have woven interlining of #250 Dacron. Stays to be 2 3/4" long, 3/8" minimum width, and to be fused to underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar topstitched 1/4" off the edge. Collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.

D. Front: The shirt is to have a hidden zipper front, which is to be molded flat. Each front shall have a facing approximately 3" in width. The left front shall have a top center placket

1-1/2" wide with two rows of stitches 7/8" apart. Stitching on top center not to be visible on the turn-back facing. The shirt will have 7 buttons and buttonholes on the front; spacing between each will be 3-3/4" except the spacing between the neck button and the first button on the front, which will be 3-1/4". Top center placket to have woven interlining of #250 Dacron. Non-woven interlining unacceptable and shall be cause for rejection.

The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable.

- E. **Shoulder Straps:** Shoulder straps to be two-piece pointed, 1/4" topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched approximately 2" from sleeve seam. Shoulder strap to be interlined with #250 Dacron. Shoulder strap to have functional buttonhole to attach to metal button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable. Shoulder straps will accommodate a removable 24 ligne metal button, (Silver for Deputy, Deputy First Class, Master Deputy, Corporal & Sergeant and Brass for Lieutenant, Captain, Major, Colonel & Sheriff).

Detention Division – Shoulder Straps are same color as issued pants, LAPD Navy.

- F. **Badge Reinforcement:** Badge Reinforcement Exterior holder to finish 1-1/8" wide by 2-1/4" deep with two (2) metal eyelets positioned vertically 1-1/4" apart with bottom eyelet centered 1-1/4" above left pocket flap.
- G. **Pockets:** Two breast patch pockets with mitered corners and 1-1/2" stitched pleats. Pleats shall be stitched top and bottom and full length of pleat to prevent spreading. Pocket to measure 5-5/8" wide, 6" deep. Left breast pocket to have 1- 1/2" pencil stitch. Each pocket to have hook Velcro, 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.
- H. **Flaps:** Two (2) piece deep scalloped design to measure 5-7/8" across and 2-3/4" in depth at center point, 2-1/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Left flap to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.) Flaps to be 1/4" topstitched. Flaps to have woven interlining of #250 Dacron. Creased and edge stitched pocket flap construction unacceptable. Under side of the flap to have looped Velcro 3/4" long by 1/2" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.
- I. **Sleeves:** Sleeves are to be straight and whole and to have a 3/4" hem and to finish at a minimum of 9 1/2" long from shoulder seam.
- J. **Buttons:** First grade 20-ligne melamine buttons for shirt, with exception of the epaulets and flaps. Metal buttons to be Maryland State Seal type as manufactured by the Waterbury

Button Company. Rank of Lieutenant, and above are to have gold finish, all others to have silver finish.

- K. Emblems: A regulation Washington County Sheriff Emblem shall be attached to each sleeve, set 1" below shoulder seam. The emblem will match the current emblem division in all ways and will be provided by the vendor (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve an emblem that is acceptable to the Sheriff's Office). All emblems must be attached at no extra charge. Where needed, a regulation Washington County Sheriff's Office Chevron shall be attached to both sleeves, placed directly below the shoulder emblem. The Chevron will match the current Chevron in all ways and will be provided by the vendor (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve a Chevron that is acceptable to the Sheriff's Office). The emblems and chevrons must be attached at no extra charge and shall be provided by the vendor. (See Attachments for illustration).
- L. Sewing: Collar, shoulder straps and pocket flaps to be topstitched 1/4" off the edge. Sleeve inserting and side close felling seams are to be safety stitched.
- M. Thread: All sewing threads to be color fast polyester wrap to match.
- N. Interlinings: Collar, pocket flaps, straps, and top center to be interlined with #250 Dacron.
- O. Military Creases: There shall be five (5) sharp silicone military creases on all shirts. One (1) crease on each front to be centered vertically. Front creases shall be through pockets and flaps. Spacing for three (3) military creases across shirt back to be proportionate to the size of the shirt.
- P. Construction: Collars, flaps, and shoulder straps are made with conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned right side out and finally topstitched.
- Q. Stock Sizes: Shirts must be available in the following sizes:

Neck sizes: 14-1/2 to 18-1/2, 19, 20, 21, 22

IX. Women's Short Sleeve Shirt Specifications

Flying Cross by Fechheimer Item# 155R84, Justice Shirts

A. Fabric:

Content: Stock Dyed 75% Dacron Polyester / 25% Wool with Natural Stretch

Weight: 9.0 to 9.50 oz. / linear yard

Color: French Blue

- B. Style: To be Flying Cross Model 155R8426. Dress style, top center placket front, full cut tapered fit, convertible collar, short sleeves, and dress shirttail. Two pleated breast pockets with topstitched scalloped flaps. Topstitched shoulder straps. Exterior badge holder with metal eyelets. Matching inside yoke and banana band of high lustre PolyTwill. Work wear industrial style shirt construction is unacceptable and shall be cause for rejection.
- C. Collar: Convertible collar shall be one piece. Collar points to measure 2 7/8" long with ultrasonically fused-in Mylar stays. Collar to have woven interlining of #250 Dacron. Stays to be 2-1/2" long, 3/8" minimum width, and to be fused to underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar topstitched 1/4" off the edge. Collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.
- D. Front: The shirt is to have a hidden zipper front, which is to be molded flat. Each front shall have a facing approximately 3" in width. The right front shall have a top center placket 1-1/2" wide with two rows of stitches 7/8" apart. Stitching on top center is not to be visible on the turn-back facing. The shirt will have six (6) buttons and buttonholes on the front; spacing between each will be 3-1/2" except the spacing between the neck button and the first button on the front, which will be 2-1/2". Top center placket to have woven interlining of #250 Dacron. Non-woven interlining unacceptable and shall be cause for rejection. The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable.
- E. Shoulder Straps: Shoulder straps to be two-piece pointed, 1/4" topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched approximately 2" from sleeve seam. Shoulder strap to be interlined with #250 Dacron. Shoulder strap to have functional buttonhole to attach to metal button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable. Shoulder straps will accommodate a removable 24 ligne metal button, (Silver for Deputy, Deputy First Class, Master Deputy, Corporal & Sergeant and Brass for Lieutenant, Captain, Major, Colonel & Sheriff).

Detention Division – Shoulder Straps are same color as issued pants, LAPD Navy.

- F. Badge Reinforcement: Exterior holder to finish 1-1/8" wide by 2-1/4" deep with two metal eyelets positioned vertically 1-1/4" apart with bottom eyelet centered 1-1/4" above left pocket flap.
- G. Two breast patch pockets with mitered corners and 1-1/4" stitched pleats. Pleats shall be stitched top and bottom and full length of pleat to prevent spreading. Pocket to measure 5" wide, 5" deep. Each pocket to have hook Velcro, 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.
- H. Flaps: Two piece deep scalloped design to measure 5-1/4" across and 2-1/4" in depth at center point, 1-3/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Left

flap to have invisible pencil opening 1-1/4". (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.) Flaps to be 1/4" topstitched. Flaps to have woven interlining of #250 Dacron. Creased and edge stitched pocket flap construction unacceptable. Under side of the flap to have looped Velcro 3/4" long by 1/2" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.

- I. Sleeves: Sleeves are to be straight and whole and to have a 3/4" hem and to finish at a minimum of 8 1/2" long from shoulder seam.
- J. Buttons: First grade 19-ligne pearlescent buttons for shirt, with exception of the epaulets and flaps. Metal buttons to be Maryland State Seal type as manufactured by the Waterbury Button Company. Rank of Lieutenant, and above are to have gold finish, all others to have silver finish.
- K. Emblems: A regulation Washington County Sheriff Emblem shall be attached to each sleeve, set 1" below shoulder seam. The emblem will match the current emblem division in all ways and will be provided by the vendor (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve an emblem that is acceptable to the Sheriff's Office). All emblems must be attached at no extra charge. Where needed, a regulation Washington County Sheriff's Office Chevron shall be attached to both sleeves, placed directly below the shoulder emblem.

The Chevron will match the current Chevron in all ways and will be provided by the vendor (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve a Chevron that is acceptable to the Sheriff's Office). The emblems and chevrons must be attached at no extra charge and shall be provided by the vendor. (See Attachments for illustration).
- L. Sewing: Collar, shoulder straps and pocket flaps to be topstitched 1/4" off the edge. Sleeve inserting and side close felling seams are to be safety stitched.
- M. Thread: All sewing threads to be color fast polyester wrap to match.
- N. Interlinings: Collar, pocket flaps, straps, and top center to be interlined with #250 Dacron.
- O. Military Creases: There shall be five (5) sharp silicone military creases on all shirts. One (1) crease on each front to be centered vertically. Front creases shall be through pockets and flaps. Spacing for three (3) military creases across shirt back to be proportionate to the size of the shirt.
- P. Construction: Collars, flaps, and shoulder straps are made with conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned right side out and finally topstitched.

Q. Stock Sizes:

Shirts must be available in the following sizes:

Bust sizes: 28-52

X. Class “C” Men’s Trousers Specifications – Detention

Men’s Trousers Specifications, Option 1

Flying Cross by Fechheimer Item# FX77400, FX STAT Hidden Cargo Trousers

A. Fabric:

Content: 65% Polyester / 35% Cotton Stretch

Weight: 5.8-6 oz. per square yard

Weave: Ripstop

Colors: LAPD Navy (F1 FX77400 86) & Black (F1 FX77400 10)

B. Style: Trousers shall be manufactured from an up-to-date men’s uniform trouser pattern. The trouser styling shall be two (2) knife notch front pockets, two (2) hip pockets professionally finished with no visible topstitching and two (2) concealed zipper cargo pockets. Gusseted crotch with folded front lining.

C. Lining Material: The pocketing and fly lining material shall be 70% Polyester / 30% Cotton, 2.9 oz. per square yard (60" width) with a minimum 78 x 48 count. Pocketing must have a durable press finish and the color of the pocketing must be black.

D. Freedom-Flex Waistband System: Trousers shall be made with a special Freedom-Flex Waistband System that will allow the wearer waist expansion of 2 1/2" to 3". The waistband shall measure a minimum of 1-7/8" wide when finished. The flexible expansion split portion of the waistband shall be to the front of the trouser side seam and there shall be a 3/4" wide side belt loop positioned to “hide” the expansion split of the waistband.

The waistband curtain shall consist of two (2) different styles for maximum waistband expansion to enhance wearer comfort, fit, and appearance. The front of the trousers (to the expansion split) waistband curtain style shall consist of a 2" wide elastic section that incorporates Tru-Grip, a 1/2" surface area composed of thin 55-gauge rubber for maximum comfort and performance. The Tru-Grip acts to help keep shirts tucked in securely. (Use of a single silicone strip or strips instead of 1/2" wide rubberized surface area shall be cause for rejection.)

The back half of the trousers waistband curtain shall finish a minimum 2-1/8" wide and is to be made of black pocketing material and shall be attached to the top of the trousers with a zigzag stitch. The waistband curtain must also contain Tru-Grip and will line up with the Tru-Grip on the front of the expansion split. (Substitution of a silicone strip or strips in place of Tru-Grip shall not be acceptable and shall be cause for rejection.)

The waistband curtain is composed of a wet laid non-woven canvas weighing 3.3 oz. per square yard. The canvas is covered in the same color and material as the pocketing. The 1/2" rubberized surface area is positioned 1-1/4" up from the bottom of the curtain.

The specifications for the rubberized Tru-Grip curtain are as follows:

Width: 1-1/8"
Warp: 300 Denier Texturized Polyester
Filling: 300 Denier Texturized Polyester
Rubber: 5 5 Gauge
Count: 32-36 yarns per inch
Contents: 59% Polyester / 41% Rubber

To complete the Freedom-Flex Waistband System, there shall be a 1-1/4" wide elastic component sewn into the back half of the waistband curtain to allow for the stretch and recovery of the waistband to comfortably fit the wearer's waist size. There shall be a bartack for strength and durability sewn at the stress point on the waistband where it joins the front elasticized waistband curtain joining stitching (positioned, on the waistband above the front pocket).

The waistband closure shall be accomplished with one crush proof hook and eye centered on the waistband for wearer comfort. The hook and eye shall be reinforced with a 7/8" non-woven tape that is anchored with topstitching through and through to the top of the waistband (bartacks in place of topstitching shall be cause for rejection). In addition to the stitching of the waistband when it is set onto the trouser, the waistband must also be topstitched below the waistband seam of the trouser to be finished to allow for alterations (with ample fabric and curtain material to allow trouser size to be increased at least one size). The outlet in the seat is to be proportional to the waist outlet so the seat may also be let out. Seat seam must be sewn with a tandem needle machine (double-needle stitch) for maximum stretch.

- E. Belt Loops: There shall be a minimum of seven (7) dropped belt loops 1" in width of double thickness with a 2 1/2" opening. Each loop must have a non-woven interlining for added durability. All loops (except back center) must be sewn into the top and bottom of the waistband. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband to allow for easier waist alteration.
- F. Fly: Trouser shall have a brass metal zipper with memory lock brass slider secured by metal stopper at base. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic trouser fabric (tabs made of pocketing material or a "grown on" French Fly will be cause for rejection). The right fly shall be lined with the same material and color as the pocketing. The fly lining shall be sewn to the left fly continuing below the zipper into the crotch area in a neat and durable manner. A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. Topstitching of fly to be installed with automatic "J" stitch equipment eliminating puckering and providing a clean finish. There shall be a firm

straight bartack at the bottom of the fly going through the zipper tape for maximum strength. Bartack shall line up with starting point of "J" stitch.

- G. Pockets: The two (2) front pockets will be knife notch style with a minimum opening of 7" and a minimum depth of 5-3/4" measured from the bottom of the opening. Front pocket facing and barrier to be made of the basic trouser fabric. Facing shall be a minimum of 1" and barrier shall measure approximately 4" (measured to the inside edge of pocket lining).

The two (2) hip pockets shall have a minimum 5-3/8" wide (bartack to bartack) opening and a minimum depth of 5-3/4" measured from the bottom of the pocket opening. Hip pockets shall be constructed using the double welt method on an automatic welt machine. The welts shall be finished in such a manner that there is no topstitching (topstitched hip pockets shall be cause for rejection). The corners of the hip pocket openings shall have straight bartacks for reinforcement (use of triangular bartacks shall be cause for rejection). Hip pocket facing and barrier are to be made of basic trouser fabric. Facing shall be a minimum of 3/4" and the barrier shall be a minimum of 1-1/2". The left hip pocket shall have a centered tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of the tab to form an opening for a button. A button shall be located below the bottom welt corresponding in location with the tab, which shall be interlined with non-woven for added durability. There shall be a dart centered above each hip pocket to waistband. Dart shall be approximately 2-3/4" long tapered from 3/8" at waistband and shall be installed with automatic equipment for a clean non-puckered finish.

- H. Concealed Cargo Pockets: There shall be two single welt concealed cargo pockets, one on each side seam. The pockets will be centered across the side seam and placed approximately 1 1/2" below the bottom of the front knife notch pocket. Pocket opening shall close with a black nylon zipper. The measurements of the pocket shall be a minimum of 7" wide and a minimum of 7 3/4" deep. Each concealed cargo pocket shall have a hidden cell phone compartment set on the front side of the pocket lining.

- I. Creases: The leg creases, front and back will have a silicone bead put in by using the Lintrak process.

- J. Seat: Seat must be sewn with a Tandem Needle Machine (double-needle stitch) for maximum durability.

- K. Stitching, Pressing & Finishing: Trouser must be stitched with matching thread. Trouser must be neatly pressed on Hothead Presses and properly shaped. Inseams are edge serged on automatic equipment for uniformity of quality and shall be pressed open for a smooth pucker-free finish with repeated cleaning and pressing. Outseam shall be finished with 1/8" double needle construction. Trouser must be cleaned and finished to eliminate loose threads.

- L. Labels: Trouser must have a permanent label providing care instructions and waist size. A removable paper ticket showing the size, fabric content, cut number, and WPL or RN number must be on the outside of the waistband. Ticket to be matchbook style installed

with plastic staples for easy removal without damaging trouser material and showing size when trousers are stacked.

XI. Women's Trouser Specifications, Option 1

Flying Cross by Fechheimer Item# FX77400W, FX STAT Hidden Cargo Trousers

A. Fabric:

Content: 65% Polyester / 35% Cotton Stretch

Weight: 5.8-6 oz. per square yard

Weave: Ripstop

Colors: LAPD Navy (F1 FX77400 86) & Black (F1 FX77400 10)

B. Style: Trouser shall be manufactured from an up-to-date lady's uniform trouser pattern. The trouser styling shall be two (2) knife notch front pockets, two (2) hip pockets professionally finished with no visible topstitching and two (2) concealed zipper cargo pockets. Gusseted crotch with folded front lining.

C. Lining Material: The pocketing and fly lining material shall be 70% Polyester / 30% Cotton, 2.9 oz. per square yard (60" width) with a minimum 78 x 48 count. Pocketing must have a durable press finish and the color of the pocketing must be black.

D. Freedom-Flex Waistband System: Trouser shall be made with a special Freedom-Flex Waistband System that will allow the wearer waist expansion of 2 1/2" to 3". The waistband shall measure a minimum of 1-7/8" wide when finished. The flexible expansion split portion of the waistband shall be to the front of the trouser side seam and there shall be a 3/4" wide side belt loop positioned to "hide" the expansion split of the waistband.

The waistband curtain shall consist of two (2) different styles for maximum waistband expansion to enhance wearer comfort, fit, and appearance.

The front of the trouser (to the expansion split) waistband curtain style shall consist of a 2" wide elastic section that incorporates Tru-Grip, a 1/2" surface area composed of thin 55-gauge rubber for maximum comfort and performance. The Tru-Grip acts to help keep shirts tucked in securely. (Use of a single silicone strip or strips instead of 1/2" wide rubberized surface area shall be cause for rejection.)

The back half of the trouser waistband curtain shall finish a minimum 2-1/8" wide and is to be made of black pocketing material and shall be attached to the top of the trouser with a zigzag stitch. The waistband curtain must also contain Tru-Grip and will line up with the Tru-Grip on the front of the expansion split. (Substitution of a silicone strip or strips in place of Tru-Grip shall not be acceptable and shall be cause for rejection.)

The waistband curtain is composed of a wet laid non-woven canvas weighing 3.3 oz. per square yard. The canvas is covered in the same color and material as the pocketing. The 1/2" rubberized surface area is positioned 1-1/4" up from the bottom of the curtain.

The specifications for the rubberized Tru-Grip curtain are as follows:

Width: 1-1/8"
Warp: 300 Denier Texturized Polyester
Filling: 300 Denier Texturized Polyester
Rubber: 55 Gauge
Count: 32-36 yarns per inch
Contents: 59% Polyester / 41% Rubber

To complete the Freedom-Flex Waistband System, there shall be a 1-1/4" wide elastic component sewn into the back half of the waistband curtain to allow for the stretch and recovery of the waistband to comfortably fit the wearer's waist size. There shall be a bartack for strength and durability sewn at the stress point on the waistband where it joins the front elasticized waistband curtain joining stitching (positioned, on the waistband above the front pocket).

The waistband closure shall be accomplished with one (1) crush proof hook and eye centered on the waistband for wearer comfort. The hook and eye shall be reinforced with a 7/8" non-woven tape that is anchored with topstitching through and through to the top of the waistband (bartacks in place of topstitching shall be cause for rejection).

In addition to the stitching of the waistband when it is set onto the trouser, the waistband must also be topstitched below the waistband seam of the trouser to be finished to allow for alterations (with ample fabric and curtain material to allow trouser size to be increased at least one size). The outlet in the seat is to be proportional to the waist outlet so the seat may also be let out. Seat seam must be sewn with a tandem needle machine (double-needle stitch) for maximum stretch.

- E. Belt Loops: There shall be a minimum of seven (7) dropped belt loops 1" in width of double thickness with a 2 1/2" opening. Each loop must have a non-woven interlining for added durability. All loops (except back center) must be sewn into the top and bottom of the waistband. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband to allow for easier waist alteration.
- F. Fly: Trouser shall have a brass metal zipper with memory lock brass slider secured by metal stopper at base. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic trouser fabric (tabs made of pocketing material or a "grown on" French Fly will be cause for rejection). The right fly shall be lined with the same material and color as the pocketing. The fly lining shall be sewn to the left fly continuing below the zipper into the crotch area in a neat and durable manner. A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. Topstitching of fly to be installed with automatic "J" stitch equipment eliminating puckering and providing a clean finish. There shall be a firm straight bartack at the bottom of the fly going through the zipper tape for maximum strength. Bartack shall line up with starting point of "J" stitch.

- G. Pockets: The two (2) front pockets will be knife notch style with a minimum opening of 7" and a minimum depth of 5-3/4" measured from the bottom of the opening. Front pocket facing and barrier to be made of the basic trouser fabric. Facing shall be a minimum of 1" and barrier shall measure approximately 4" (measured to the inside edge of pocket lining).

The two (2) hip pockets shall have a minimum 5-3/8" wide (bartack to bartack) opening and a minimum depth of 5-3/4" measured from the bottom of the pocket opening. Hip pockets shall be constructed using the double welt method on an automatic welt machine. The welts shall be finished in such a manner that there is no topstitching (topstitched hip pockets shall be cause for rejection). The corners of the hip pocket openings shall have straight bartacks for reinforcement (use of triangular bartacks shall be cause for rejection). Hip pocket facing and barrier are to be made of basic trouser fabric. Facing shall be a minimum of 3/4" and the barrier shall be a minimum of 1-1/2". The left hip pocket shall have a centered tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of the tab to form an opening for a button. A button shall be located below the bottom welt corresponding in location with the tab, which shall be interlined with non-woven for added durability. There shall be a dart centered above each hip pocket to waistband. Dart shall be approximately 2-3/4" long tapered from 3/8" at waistband and shall be installed with automatic equipment for a clean non-puckered finish.

- H. Concealed Cargo Pockets: There shall be two single welt concealed cargo pockets, one (1) on each side seam. The pockets will be centered across the side seam and placed approximately 1 1/2" below the bottom of the front knife notch pocket. Pocket opening shall close with a black nylon zipper. The measurements of the pocket shall be a minimum of 7" wide and a minimum of 7 3/4" deep. Each concealed cargo pocket shall have a hidden cell phone compartment set on the front side of the pocket lining.
- I. Creases: The leg creases, front and back will have a silicone bead put in by using the Lintrak process.
- J. Seat: Seat must be sewn with a Tandem Needle Machine (double-needle stitch) for maximum durability.
- K. Stitching, Pressing & Finishing: Trouser must be stitched with matching thread. Trouser must be neatly pressed on Hothead Presses and properly shaped. Inseams are edge serged on automatic equipment for uniformity of quality and shall be pressed open for a smooth pucker-free finish with repeated cleaning and pressing. Outseam shall be finished with 1/8" double needle construction. Trouser must be cleaned and finished to eliminate loose threads.
- L. Labels: Trouser must have a permanent label providing care instructions and waist size. A removable paper ticket showing the size, fabric content, cut number, and WPL or RN number must be on the outside of the waistband. Ticket to be matchbook style installed with plastic staples for easy removal without damaging trouser material and showing size when trousers are stacked.

XII. Men's Trouser Specifications, Option 2

Flying Cross by Fechheimer Item# FX77300, FX STAT External Cargo Trousers

A. Fabric:

Content: 65% Polyester / 35% Cotton Stretch

Weight: 5.8-6 oz. per square yard

Weave: Ripstop

Available Colors:

LAPD Navy (F1 FX77300 86)

Black (F1 FX77300 10)

O.D. Green (F1 FX77300 27)

Oxford Grey (F1 FX77300 71)

Brown (F1 FX77300 94)

- B. Style: Trouser shall be manufactured from an up-to-date men's uniform trouser pattern. The trouser styling shall be two (2) knife notch front pockets, two (2) hip pockets professionally finished with no visible topstitching, two (2) club pockets and two (2) cargo pockets. Gusseted crotch with folded front lining.
- C. Lining Material: The pocketing and fly lining material shall be 70% Polyester / 30% Cotton, 2.9 oz. per square yard (60" width) with a minimum 78 x 48 count. Pocketing must have a durable press finish and the color of the pocketing must be black.
- D. Freedom-Flex Waistband System: Trouser shall be made with a special Freedom-Flex Waistband System that will allow the wearer waist expansion of 2 ½" to 3". The waistband shall measure a minimum of 1-7/8" wide when finished. The flexible expansion split portion of the waistband shall be to the front of the trouser side seam and there shall be a 3/4" wide side belt loop positioned to hide the expansion split of the waistband.

The waistband curtain shall consist of two (2) different styles for maximum waistband expansion to enhance wearer comfort, fit, and appearance. The front of the trouser (to the expansion split) waistband curtain style shall consist of a 2" wide elastic section that incorporates Tru-Grip, a 1/2" surface area composed of thin 55-gauge rubber for maximum comfort and performance. The Tru-Grip acts to help keep shirts tucked in securely. (Use of a single silicone strip or strips instead of 1/2" wide rubberized surface area shall be cause for rejection.) The back half of the trouser waistband curtain shall finish a minimum 2-1/8" wide and is to be made of black pocketing material and shall be attached to the top of the trouser with a zigzag stitch. The waistband curtain must also contain Tru-Grip and will line up with the Tru-Grip on the front of the expansion split. (Substitution of a silicone strip or strips in place of Tru-Grip shall not be acceptable and shall be cause for rejection.)

The waistband curtain is composed of a wet laid non-woven canvas weighing 3.3 oz. per square yard. The canvas is covered in the same color and material as the pocketing. The 1/2" rubberized surface area is positioned 1-1/4" up from the bottom of the curtain.

The specifications for the rubberized Tru-Grip curtain are as follows:

Width: 1-1/8"
Warp: 300 Denier Texturized Polyester
Filling: 300 Denier Texturized Polyester
Rubber: 55 Gauge
Count: 32-36 yarns per inch
Contents: 59% Polyester / 41% Rubber

To complete the Freedom-Flex Waistband System, there shall be a 1-1/4" wide elastic component sewn into the back half of the waistband curtain to allow for the stretch and recovery of the waistband to comfortably fit the wearer's waist size. There shall be a bartack for strength and durability sewn at the stress point on the waistband where it joins the front elasticized waistband curtain joining stitching (positioned, on the waistband above the front pocket).

The waistband closure shall be accomplished with one crush proof hook and eye centered on the waistband for wearer comfort. The hook and eye shall be reinforced with a 7/8" non-woven tape that is anchored with topstitching through and through to the top of the waistband (bartacks in place of topstitching shall be cause for rejection). In addition to the stitching of the waistband when it is set onto the trouser, the waistband must also be topstitched below the waistband seam of the trouser to be finished to allow for alterations (with ample fabric and curtain material to allow trouser size to be increased at least one size).

The outlet in the seat is to be proportional to the waist outlet so the seat may also be let out. Seat seam must be sewn with a tandem needle machine (double-needle stitch) for maximum stretch.

- E. Belt Loops: There shall be a minimum of seven (7) dropped belt loops 1" in width of double thickness with a 2 1/2" opening. Each loop must have a non-woven interlining for added durability. All loops (except back center) must be sewn into the top and bottom of the waistband. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband to allow for easier waist alteration.
- F. Fly: Trouser shall have a brass metal zipper with memory lock brass slider secured by metal stopper at base. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic trouser fabric (tabs made of pocketing material or a "grown on" French Fly will be cause for rejection). The right fly shall be lined with the same material and color as the pocketing. The fly lining shall be sewn to the left fly continuing below the zipper into the crotch area in a neat and durable manner. A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. Topstitching of fly to be installed with automatic "J" stitch equipment

eliminating puckering and providing a clean finish. There shall be a firm straight bartack at the bottom of the fly going through the zipper tape for maximum strength. Bartack shall line up with starting point of "J" stitch.

- G. Pockets: The two (2) front pockets will be knife notch style with a minimum opening of 7" and a minimum depth of 5-3/4" measured from the bottom of the opening. Front pocket facing and barrier to be made of the basic trouser fabric. Facing shall be a minimum of 1" and barrier shall measure approximately 4" (measured to the inside edge of pocket lining).

The two (2) hip pockets shall have a minimum 5-3/8" wide (bartack to bartack) opening and a minimum depth of 5-3/4" measured from the bottom of the pocket opening. Hip pockets shall be constructed using the double welt method on an automatic welt machine. The welts shall be finished in such a manner that there is no topstitching (topstitched hip pockets shall be cause for rejection). The corners of the hip pocket openings shall have straight bartacks for reinforcement (use of triangular bartacks shall be cause for rejection). Hip pocket facing and barrier are to be made of basic trouser fabric. Facing shall be a minimum of 3/4" and the barrier shall be a minimum of 1-1/2". The left hip pocket shall have a centered tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of the tab to form an opening for a button. A button shall be located below the bottom welt corresponding in location with the tab, which shall be interlined with non-woven for added durability. There shall be a dart centered above each hip pocket to waistband. Dart shall be approximately 2-3/4" long tapered from 3/8" at waistband and shall be installed with automatic equipment for a clean non-puckered finish.

There shall be club pockets located 4-1/2" (plus or minus 1/4") and in line with each hip pocket. The club pockets shall be 2-1/4" (plus or minus 1/4") from the side seam with a minimum opening of 3-1/2" and a minimum depth of 8". Pocketing material to be the same as side and hip pockets. Club pockets shall be constructed using the double welt method on a REECE PW machine and finished in such a manner that there is no topstitching (topstitched club pockets shall be cause for rejection). The corners of the club pockets shall have straight bartacks for reinforcing strength.

- H. Cargo Pockets: There shall be two cargo pockets, one on each side seam. Pockets shall have two inverted pleated bellows in back patch pockets with mitered corner flaps. The pockets will be centered across the side seam and placed approximately 3-1/4" below the bottom of the front side pocket, measuring from the top of the pocket flap. The pocket shall be constructed of the shell fabric. The top edge of the pocket shall be turned and stitched down 1". The outside measurements of the pocket shall be a minimum of 8" wide and a minimum of 9" deep with mitered bottom corners.

There shall be two inverted pleats on each pocket. The inverted pleat nearest to the front of the trouser shall have a vertical zipper pocket built into the cargo pocket with a 6" opening. The cargo pockets shall have a 2" wide piece of black elastic inside at center of each cargo pocket with vertical stitching halfway through and to allow for 5/8" bubble to be able to insert and hold items. The pocket flap shall have mitered corners and measure a minimum of 8-1/4" wide, a minimum of 2-1/4" deep at the center. The flap shall be 1/8" double needle stitched across the top to the inner pocket, covering the top edge of the outer

pocket. The flaps shall have a 1-1/4" pencil opening at top of each flap with vertical bartacks at each end. At the corners there shall be a 1" wide x 1" high piece of Velcro (loop side) sewn to the inner ply of the flap and a corresponding piece of Velcro (hook side) sewn on the pocket. There shall be straight vertical bartacks at the top corners of each pocket flap.

- I. Creases: The leg creases, front and back will have a silicone bead put in by using the Lintrak process.
- J. Seat: Seat must be sewn with a Tandem Needle Machine (double-needle stitch) for maximum durability.
- K. Stitching, Pressing & Finishing: Trouser must be stitched with matching thread. Trouser must be neatly pressed on Hothead Presses and properly shaped. Inseams are edge serged on automatic equipment for uniformity of quality and shall be pressed open for a smooth pucker-free finish with repeated cleaning and pressing. Outseam shall be finished with 1/8" double needle construction. Trouser must be cleaned and finished to eliminate loose threads.
- L. Labels: Trouser must have a permanent label providing care instructions and waist size. A removable paper ticket showing the size, fabric content, cut number, and WPL or RN number must be on the outside of the waistband. Ticket to be matchbook style installed with plastic staples for easy removal without damaging trouser material and showing size when trousers are stacked.

XIII. Women's Trouser Specifications, Option 2

Flying Cross by Fechheimer Item# FX77300W, FX STAT External Cargo Trousers

A. Fabric:

Content: 65% Polyester / 35% Cotton Stretch
Weight: 5.8-6 oz. per square yard
Weave: Ripstop

Available Colors:

LAPD Navy (F1 FX77300W 86)
Black (F1 FX77300W 10)
O.D. Green (F1 FX77300W 27)
Oxford Grey (F1 FX77300W 71)
Brown (F1 FX77300W 94)

- B. Style: Trouser shall be manufactured from an up-to-date lady's uniform trouser pattern. The trouser styling shall be two (2) knife notch front pockets, two (2) hip pockets professionally finished with no visible topstitching, two (2) club pockets and two (2) cargo pockets. Gusseted crotch with folded front lining.

- C. Lining Material: The pocketing and fly lining material shall be 70% Polyester / 30% Cotton, 2.9 oz. per square yard (60" width) with a minimum 78 x 48 count. Pocketing must have a durable press finish and the color of the pocketing must be black.
- D. Freedom-Flex Waistband System: Trousers shall be made with a special Freedom-Flex Waistband System that will allow the wearer waist expansion of 2-1/2" to 3". The waistband shall measure a minimum of 1-7/8" wide when finished. The flexible expansion split portion of the waistband shall be to the front of the trouser side seam and there shall be a 3/4" wide side belt loop positioned to "hide" the expansion split of the waistband.

The waistband curtain shall consist of two (2) different styles for maximum waistband expansion to enhance wearer comfort, fit, and appearance.

The front of the trouser (to the expansion split) waistband curtain style shall consist of a 2" wide elastic section that incorporates Tru-Grip, a 1/2" surface area composed of thin 55-gauge rubber for maximum comfort and performance. The Tru-Grip acts to help keep shirts tucked in securely. (Use of a single silicone strip or strips instead of 1/2" wide rubberized surface area shall be cause for rejection.)

The back half of the trouser waistband curtain shall finish a minimum 2-1/8" wide and is to be made of black pocketing material and shall be attached to the top of the trouser with a zigzag stitch. The waistband curtain must also contain Tru-Grip and will line up with the Tru-Grip on the front of the expansion split. (Substitution of a silicone strip or strips in place of Tru-Grip shall not be acceptable and shall be cause for rejection.)

The waistband curtain is composed of a wet laid non-woven canvas weighing 3.3 oz. per square yard. The canvas is covered in the same color and material as the pocketing. The 1/2" rubberized surface area is positioned 1-1/4" up from the bottom of the curtain.

The specifications for the rubberized Tru-Grip curtain are as follows:

Width: 1-1/8"
Warp: 300 Denier Texturized Polyester
Filling: 300 Denier Texturized Polyester
Rubber: 55 Gauge
Count: 32-36 yarns per inch
Contents: 59% Polyester / 41% Rubber

To complete the Freedom-Flex Waistband System, there shall be a 1-1/4" wide elastic component sewn into the back half of the waistband curtain to allow for the stretch and recovery of the waistband to comfortably fit the wearer's waist size.

There shall be a bartack for strength and durability sewn at the stress point on the waistband where it joins the front elasticized waistband curtain joining stitching (positioned, on the waistband above the front pocket.)

The waistband closure shall be accomplished with one crush proof hook and eye centered on the waistband for wearer comfort. The hook and eye shall be reinforced with a 7/8" non-woven tape that is anchored with topstitching through and through to the top of the waistband (bartacks in place of topstitching shall be cause for rejection). In addition to the stitching of the waistband when it is set onto the trouser, the waistband must also be topstitched below the waistband seam of the trouser to be finished to allow for alterations (with ample fabric and curtain material to allow trouser size to be increased at least one size). The outlet in the seat is to be proportional to the waist outlet so the seat may also be let out. Seat seam must be sewn with a tandem needle machine (double-needle stitch) for maximum stretch.

E. Belt Loops:

There shall be a minimum of seven (7) dropped belt loops 1" in width of double thickness with a 2-1/2" opening. Each loop must have a non-woven interlining for added durability. All loops (except back center) must be sewn into the top and bottom of the waistband. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband to allow for easier waist alteration.

F. Fly: Trouser shall have a brass metal zipper with memory lock brass slider secured by metal stopper at base. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic trouser fabric (tabs made of pocketing material or a "grown on" French Fly will be cause for rejection). The right fly shall be lined with the same material and color as the pocketing. The fly lining shall be sewn to the left fly continuing below the zipper into the crotch area in a neat and durable manner. A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. Topstitching of fly to be installed with automatic "J" stitch equipment eliminating puckering and providing a clean finish. There shall be a firm straight bartack at the bottom of the fly going through the zipper tape for maximum strength. Bartack shall line up with starting point of "J" stitch.

G. Pockets: The two (2) front pockets will be knife notch style with a minimum opening of 7" and a minimum depth of 5-3/4" measured from the bottom of the opening. Front pocket facing and barrier to be made of the basic trouser fabric. Facing shall be a minimum of 1" and barrier shall measure approximately 4" (measured to the inside edge of pocket lining).

The two (2) hip pockets shall have a minimum 5-3/8" wide (bartack to bartack) opening and a minimum depth of 5-3/4" measured from the bottom of the pocket opening. Hip pockets shall be constructed using the double welt method on an automatic welt machine. The welts shall be finished in such a manner that there is no topstitching (topstitched hip pockets shall be cause for rejection). The corners of the hip pocket openings shall have straight bartacks for reinforcement (use of triangular bartacks shall be cause for rejection). Hip pocket facing and barrier are to be made of basic trouser fabric. Facing shall be a minimum of 3/4" and the barrier shall be a minimum of 1-1/2".

The left hip pocket shall have a centered tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of the tab to form an opening for a button. A button

shall be located below the bottom welt corresponding in location with the tab, which shall be interlined with non-woven for added durability.

There shall be a dart centered above each hip pocket to waistband. Dart shall be approximately 2-3/4" long tapered from 3/8" at waistband and shall be installed with automatic equipment for a clean non-puckered finish.

There shall be club pockets located 4-1/2" (plus or minus 1/4") and in line with each hip pocket. The club pockets shall be 2-1/4" (plus or minus 1/4") from the side seam with a minimum opening of 3-1/2" and a minimum depth of 8". Pocketing material to be the same as side and hip pockets. Club pockets shall be constructed using the double welt method on a REECE PW machine and finished in such a manner that there is no topstitching (topstitched club pockets shall be cause for rejection). The corners of the club pockets shall have straight bartacks for reinforcing strength.

- H. Cargo Pockets: There shall be two (2) cargo pockets, one (1) on each side seam. Pockets shall have two (2) inverted pleated bellows in back patch pockets with mitered corner flaps. The pockets will be centered across the side seam and placed approximately 2-1/2" below the bottom of the front side pocket, measuring from the top of the pocket flap. The pocket shall be constructed of the shell fabric. The top edge of the pocket shall be turned and stitched down 1".

The outside measurements of the pocket shall be a minimum of 8-1/4" wide and a minimum of 9" deep with mitered bottom corners. There shall be two inverted pleats on each pocket. The inverted pleat nearest to the front of the trouser shall have a vertical zipper pocket built into the cargo pocket with a 6" opening.

The cargo pockets shall have a 2" wide piece of black elastic inside at center of each cargo pocket with vertical stitching halfway through and to allow for 5/8" bubble to be able to insert and hold items. The pocket flap shall have mitered corners and measure a minimum of 8-1/2" wide, a minimum of 2-1/4" deep at the center. The flap shall be 1/8" double needle stitched across the top to the inner pocket, covering the top edge of the outer pocket. The flaps shall have a 1-1/4" pencil opening at top of each flap with vertical bartacks at each end. At the corners there shall be a 1" wide x 1" high piece of Velcro (loop side) sewn to the inner ply of the flap and a corresponding piece of Velcro (hook side) sewn on the pocket. There shall be straight vertical bartacks at the top corners of each pocket flap.

- I. Creases: The leg creases, front and back will have a silicone bead put in by using the Lintrak process.
- J. Seat: Seat must be sewn with a Tandem Needle Machine (double-needle stitch) for maximum durability.
- K. Stitching, Pressing & Finishing: Trouser must be stitched with matching thread. Trouser must be neatly pressed on Hothead Presses and properly shaped. Inseams are edge serged on automatic equipment for uniformity of quality and shall be pressed open for a smooth pucker-free finish with repeated cleaning and pressing. Outseam shall be finished with

1/8" double needle construction. Trouser must be cleaned and finished to eliminate loose threads.

- L. Labels: Trouser must have a permanent label providing care instructions and waist size. A removable paper ticket showing the size, fabric content, cut number, and WPL or RN number must be on the outside of the waistband. Ticket to be matchbook style installed with plastic staples for easy removal without damaging trouser material and showing size when trousers are stacked.

XIV. Class "C" Detention Shirts Specifications

Men's Long Sleeve Shirt Specifications

Flying Cross by Fechheimer Item# F1 FX7020, FX STAT

Vendor will be asked to size employees while providing a complete fit for customer to submit proper sizing.

- A. Emblems: On all Sheriff's Detention class "C" uniform shirts, a regulation Washington County Sheriff Emblem shall be attached to each sleeve, set 1" below shoulder seam. The emblem will match the current emblem in all ways and will be provided by the vendor. On all Corrections Officers class "C" uniform shirts, a regulation Washington County Detention Emblem shall be attached to each sleeve, set 1" below shoulder seam. The emblem will match the current emblem in all ways, except the background field will be dark blue to match the class "C" trousers and the writing will be white. All emblems must be attached at no extra charge. Where needed, a regulation Washington County Sheriff's Chevron shall be attached to both sleeves, placed directly below shoulder emblem. The emblem will match the current emblem in all ways and will be provided by the vendor. The emblems and chevrons must be attached at no extra charge and shall be provided by the vendor.
- B. Star Emblems: On all class "C" uniform shirts, a Washington County Sheriff Star Emblem shall be attached to the left breast, center above the pocket, and centered in the space. The emblem shall be a six-point star; it shall have a light blue background field that matches the class "C" uniform shirt. There will be a dark blue sewn boarder around the edge of the star, with a sewn ball on each point of the star. The sewn boarder shall match the color of the class "C" uniform trousers. In the center of the star there will be a sewn circle border, gold in color, inside the center of the circle shall be a field that shows the center part of the Maryland Flag, in its normal colors. Around the circle of the state flag, it shall state the STATE OF MARYLAND, gold in color, in a medium blue field, around these words and the medium blue field, there shall be a second sewn circle, gold in color. Above the circle there shall be a banner in dark blue, to match the dark blue class "C" trousers, in the banner shall be DEPUTY SHERIFF, in light blue to match the color of the class "C" uniform shirt. Below the circle of the state flag, there shall be a second banner in dark blue, in the banner

shall state WASHINGTON, below that shall be a third banner in dark blue in the banner shall state CO. The sewn edge of the star, balls of the star, and the banners shall be dark blue to match the class "C" trousers. The DEPUTY SHERIFF and WASHINGTON and CO. shall be light blue to match the background of the star and the color of the class "C" shirt. The STATE OF MARYLAND and the circles around the Maryland flag shall be gold in color. The center of the Maryland flag shall reflect the normal colors of the Maryland Flag. The background of the circle, which states the STATE OF MARYLAND, shall be a medium blue. All-star emblems must be attached at no extra charge and shall be provided by the vendor.

C. Name Strip: On all Class "C" uniform shirts there will be an embroidered name strip with ID# attached above the right pocket of the shirt. The name strip will be made of the same material and color as the shirt with navy writing to include the name and ID#. At no extra charge to the County, all name strips must be approved by the County and attached to the uniform part.

D. Fabric:

Content: 65% Polyester / 35% Cotton
Weight: 5.8 oz. / square yard
Weave: Mini Ripstop with Stretch
COLOR: French Blue

E. Style:

To be Flying Cross Model F1 FX7020. Dress style, top center placket front, knit underarm gussets, full cut tapered fit, Freedom collar, long sleeves with barrel cuffs and dress shirttail. Two pleated breast pockets with topstitched scalloped flaps. Topstitched shoulder straps.

Full badge reinforcement. Wire Pass-through openings. Matching inside yoke and collar band of high luster Poly / Twill. Back yoke to be 1/8" double needle topstitched. Work wear industrial style shirt construction is unacceptable and shall be cause for rejection.

F. Collar & Stand: Collar points to measure 2-1/2" long with ultrasonically fused-in Mylar stays. Collar stays are positioned along the leading edge of the collar. Collar to have woven interlining of #250 Dacron. Stays to be 2" long, 3/8" minimum width, and to be fused to underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar height at rear 1-1/2". Collar is 1/8" double needle topstitched. Collar stand to measure 1-5/16" at rear and band to be interlined with "Crease N Tack". Collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.

G. Freedom Collar Feature: Material consisting of self-goods and lining material forming the neckband and the collar must be arranged with the weave thereof on a bias so that it is stretchable in the direction parallel to the circumferential direction of the collar. This

expandable collar will allow for slight variations in neck size and make it easier to button because of the stretch or yield of the material.

- H. Front: The left front shall have a top center placket 1-1/2" wide with two double rows of stitching. The shirt will have seven (7) buttons and buttonholes on the front; spacing between each will be 3-3/4" except the spacing between the neck button and the first button on the front, which will be approximately 3-1/4". Top center placket to have woven interlining of #250 Dacron. Non-woven interlining unacceptable and shall be cause for rejection.

The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/8" double needle stitch. Safety stitch joining unacceptable. A 15" nylon zipper, to be set below the second button and buttonhole, shall accomplish front closure. The top, second and bottom buttons to be attached to the right front, the balance to be sewn over the buttonholes on the left front.

- I. Shoulder Straps: Shoulder straps to be two-piece pointed, 1/8" double needle topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched approximately 2" from sleeve seam. Shoulder strap to have functional buttonhole to attach to sewn button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable.

Detention Division – Shoulder Straps are same color as issued pants, LAPD Navy.

- J. Badge Reinforcement: Two-ply sling 1" wide centered over left pocket and stitched to shoulder seam and flap setting stitch. It shall have 2 (two) buttonhole eyelets 1-1/4" from top of pocket flap spaced 1-1/4" apart and centered on sling.
- K. Loose Microphone and Camera Tab: Each shirt shall have a loose microphone and camera tab included that may be installed by the user if needed.
- L. Wire Pass Through Openings: Each front shall have an 11/16" horizontal buttonhole to be centered vertically and horizontally between the top of the pocket and the bottom of the open flap. Each shoulder shall have an 11/16" horizontal buttonhole to be centered under the shoulder straps and sewn through the shoulder of the shirt.
- M. Underarm Gusset with Wire Pass Through: Wearer's Right & Left Side Seam. Knight Diamond Gusset and Underarm Gusset with Wire Pass Through. Knight stretch panel & gusset. Wire pass through, no Velcro, secured with bartacks only. 1" Wire pass through.
- N. Pockets: Two breast patch pockets with mitered corners and 1-1/2" stitched pleats. Pleats shall be stitched top and bottom and full length of pleat to prevent spreading. Pockets are set to the shirt front with 1/8" double needle stitching. Pocket to measure 5-5/8" wide, 6" deep. Each breast pocket to have 1- 1/2" pencil stitch. Each pocket to have hook Velcro, 1" long by 1" wide, positioned on both edges of pocket to correspond with outer scalloped

flap points as specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.

- O. Flaps: Two piece deep scalloped design to measure 5-7/8" across and 2-3/4" in depth at center point, 2-1/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Each flap to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.) Flaps to be 1/8" double needle topstitched. Flaps to have woven interlining of #250 Dacron. Creased and edge stitched pocket flap construction unacceptable. Under side of the flap to have looped Velcro 1" long by 1" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.
- P. Sleeves: Sleeve vent shall be a minimum of 4-1/2" long with one-piece top and bottom facings. Facing to measure 1-1/8" wide point blocked at top.
- Q. Cuffs: Two-piece 1/2" hemmed cuff with 1/8" double needle topstitching. Cuffs to measure 3" in depth with rounded corners (barrel cuffs). Cuffs to be two button adjustable with one button and buttonhole in center of facing. Cuffs to have woven interlining of #250 Dacron.
- R. Buttons: First grade 22-ligne melamine.
- S. Sewing: Collar, shoulder straps, cuffs, and pocket flaps to be topstitched with 1/8" double needle stitching. Sleeve inserting is with 1/8" double needle seams. Side close felling seams are to be safety stitched.
- T. Thread: All sewing threads to be color fast polyester wrap to match.
- U. Interlinings: Collar, Pocket flaps, Cuffs, Shoulder straps and top center to be interlined with #250 Dacron. Collar band to be interlined with Crease-N-Tac.
- V. Military Creases: There shall be five sharp silicone military creases on all shirts. One crease on each front to be centered vertically. Front creases shall be through pockets and flaps. Spacing for three military creases across shirt back to be proportionate to the size of the shirt.
- W. Construction: Collar, cuffs, flaps, and shoulder straps are made with conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned right side out and finally topstitched.
- X. Stock Sizes: Shirts must be available in the following sizes:

<u>Neck Size</u>	<u>Sleeve Lengths</u>
14.0/14.5 Through 18.5 Then 19.0/19.5, 20.0/20.5	32/33
14.0/14.5 Through 18.5 Then 19.0/19.5, 20.0/20.5, 21.0/21.5, 22.0/22.5	34/35

Neck Size
15.0 Through 18.5 Then 19.0/19.5, 20.0/20.5,
21.0/21.5, 22.0/22.5

Sleeve Lengths
36/37, 38/39

XV. Women’s Long Sleeve Shirt Specifications

Flying Cross by Fechheimer Item# F1 FX7020W

A. Fabric:

Content: 65% Polyester / 35% Cotton
Weight: 5.8 oz. / square yard
Weave: Mini Ripstop with Stretch

B. Color:

French Navy

Female shirts shall be constructed the same as the male shirts but cut on female patterns.

C. Stock Sizes:

Shirts must be available in the following sizes:

Bust Sizes 30-54

Long Sleeve Lengths:

26, 28, 30, 32, 34	Regular = 30”	Long = 31”
36, 38	Regular = 31”	Long = 32”
40	Regular = 32”	Long = 33”
44 & Up	Regular = 33”	Long = 34”

XVI. Men’s Short Sleeve Shirt Specifications

Flying Cross by Fechheimer Item: F1 FX7000

Vendor will be asked to size employees while providing a complete fit for customer to submit proper sizing.

- A. Emblems: On all Sheriff’s Detention class “C” uniform shirts, a regulation Washington County Sheriff Emblem shall be attached to each sleeve, set 1" below shoulder seam. The emblem will match the current emblem in all ways and will be provided by the vendor. On all Corrections Officers class “C” uniform shirts, a regulation Washington County Detention Emblem shall be attached to each sleeve, set 1” below shoulder seam. The emblem will match the current emblem in all ways, except the background field will be

dark blue to match the class “C” trousers and the writing will be white. All emblems must be attached at no extra charge.

Where needed, a regulation Washington County Sheriff’s Chevron shall be attached to both sleeves, placed directly below shoulder emblem. The emblem will match the current emblem in always and will be provided by the vendor. The emblems and chevrons must be attached at no extra charge and shall be provided by the vendor.

- B. **Star Emblems:** On all class “C” uniform shirts, a Washington County Sheriff Star Emblem shall be attached to the left breast, center above the pocket, and centered in the space. The emblem shall be a six-point star; it shall have a light blue background field that matches the class “C” uniform shirt. There will be a dark blue sewn boarder around the edge of the star, with a sewn ball on each point of the star. The sewn boarder shall match the color of the class “C” uniform trousers. In the center of the star there will be a sewn circle border, gold in color, inside the center of the circle shall be a field that shows the center part of the Maryland Flag, in its normal colors. Around the circle of the state flag, it shall state the STATE OF MARYLAND, gold in color, in a medium blue field, around these words and the medium blue field, there shall be a second sewn circle, gold in color.

Above the circle there shall be a banner in dark blue, to match the dark blue class “C” trousers, in the banner shall be DEPUTY SHERIFF, in light blue to match the color of the class “C” uniform shirt.

Below the circle of the state flag, there shall be a second banner in dark blue, in the banner shall state WASHINGTON, below that shall be a third banner in dark blue in the banner shall state CO. The sewn edge of the star, balls of the star, and the banners shall be dark blue to match the class “C” trousers. The DEPUTY SHERIFF and WASHINGTON and CO. shall be light blue to match the background of the star and the color of the class “C” shirt.

The STATE OF MARYLAND and the circles around the Maryland flag shall be gold in color. The center of the Maryland flag shall reflect the normal colors of the Maryland Flag. The background of the circle, which states the STATE OF MARYLAND, shall be a medium blue. All-star emblems must be attached at no extra charge and shall be provided by the vendor.

- C. **Name Strip:** On all Class “C” uniform shirts there will be an embroidered name patch with ID# attached above the right pocket of the shirt. The switching of the patch will be the same color as the Class “C” trousers.
- D. The background of the patch will match the color of the class “C” shirt. At no extra charge to the County, all patches must be approved by the County and attached to the uniform part.

- E. Fabric:
- Content: 65% Polyester / 35% Cotton
Weight: 5.8 oz. / square yard
Weave: Mini Ripstop with Stretch
- F. Color: French Navy
- G. Style: To be Flying Cross Model F1 FX7000. Dress style, top center placket front, knit underarm gussets, full cut tapered fit, convertible collar, short sleeves, and dress shirrtail. Two (2) pleated breast pockets with topstitched scalloped flaps. Topstitched shoulder straps. Full badge reinforcement. Wire Pass-through openings. Matching inside yoke and banana band of high luster Poly/Twill. Back yoke to be 1/8" double needle topstitched. Work wear industrial style shirt construction is unacceptable and shall be cause for rejection.
- H. Collar: Convertible collar shall be one piece. Collar points to measure 2-1/2" long with ultrasonically fused-in Mylar stays. Collar stays are positioned along the leading edge of the collar. Collar to have woven interlining of #250 Dacron. Stays to be 2" long, 3/8" minimum width, and to be fused to underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar is 1/8" Double Needle topstitched. Collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.
- I. Front: Each front shall have a facing approximately 3" in width. The left front shall have a top center placket 1-1/2" wide with two double rows of stitching. Stitching on top center is not to be visible on the turn-back facing. The shirt will have seven (7) buttons and buttonholes on the front; spacing between each will be 3-3/4" except the spacing between the neck button and the first button on the front, which will be approximately 2-1/2". Top center placket to have woven interlining of #250 Dacron. Non-woven interlining unacceptable and shall be cause for rejection. The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/8" double needle stitch. Safety stitch joining unacceptable.
- A 15" nylon zipper, to be set below the second button and buttonhole, shall accomplish front closure. The top, second and bottom buttons to be attached to the right front, the balance to be sewn over the buttonholes on the left front.
- J. Shoulder Straps: Shoulder straps to be two-piece pointed, 1/8" double needle topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched approximately 2" from sleeve seam. Shoulder strap to have functional buttonhole to attach to sewn button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable.

Detention Division – Shoulder Straps are same color as issued pants, LAPD Navy.

- K. Badge Reinforcement: Two-ply sling 1" wide centered over left pocket and stitched to shoulder seam and flap setting stitch. It shall have 2 (two) buttonhole eyelets 1-1/4" from top of pocket flap spaced 1-1/4" apart and centered on sling.
- L. Loose Microphone and Camera Tab: Each shirt shall have a loose microphone and camera tab included that may be installed by the user if needed.
- M. Wire Pass Through Openings: Each front shall have an 11/16" horizontal buttonhole to be centered vertically and horizontally between the top of the pocket and the bottom of the open flap. Each shoulder shall have an 11/16" horizontal buttonhole to be centered under the shoulder straps and sewn through the shoulder of the shirt.
- N. Underarm Gusset with Wire Pass Through: Wearer's Right & Left Side Seam. Knit Diamond Gusset and Underarm Gusset with Wire Pass Through. Wire Pass Through No Velcro, secured with bartacks only. 1" Wire Pass Through. Knit stretch panel & gusset.
- O. Pockets: Two breast patch pockets with mitered corners and 1-1/2" stitched pleats. Pleats shall be stitched top and bottom and full length of pleat to prevent spreading. Pockets are set to the shirt front with 1/8" double needle stitching. Pocket to measure 5-5/8" wide, 6" deep. Each breast pocket to have 1-1/2" pencil stitch.

Each pocket to have hook Velcro, 1" long by 1" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.
- P. Flaps: Two piece deep scalloped design to measure 5-7/8" across and 2-3/4" in depth at center point, 2-1/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Each flap to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.)

Flaps to be 1/8" double needle topstitched. Flaps to have woven interlining of #250 Dacron. Creased and edge stitched pocket flap construction unacceptable. Under side of the flap to have looped Velcro 1" long by 1" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.
- Q. Sleeves: Sleeves are to be straight and whole and to have a 3/4" hem and to finish at a minimum of 9-1/2" long from shoulder seam.
- R. Buttons: First grade 22-ligne melamine.
- S. Sewing: Collar, shoulder straps and pocket flaps to be topstitched with 1/8" double needle stitching. Sleeve inserting is with 1/8" double needle seams. Side close felling seams are to be safety stitched.
- T. Thread: All sewing threads to be color fast polyester wrap to match.

- U. Interlinings: Collar, Pocket flaps, Shoulder straps and top center to be interlined with #250 Dacron.
- V. Military Creases: There shall be five sharp silicone military creases on all shirts. One crease on each front to be centered vertically. Front creases shall be through pockets and flaps. Spacing for three military creases across shirt back to be proportionate to the size of the shirt.
- W. Construction: Collars, flaps, and shoulder straps are made with conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned right side out and finally topstitched.
- X. Stock Sizes:

Shirts must be available in the following sizes: Alpha sizes: S - 6XL

XVII. Women’s Short Sleeve Shirt Specifications

Flying Cross by Fechheimer Item# F1 FX7000W

Female shirts shall be constructed the same as the male shirts but cut on female patterns.

- A. Fabric:

Content: 65% Polyester / 35% Cotton
Weight: 5.8 oz. / square yard
Weave: Mini Ripstop with Stretch
- B. Color: French Navy
- C. Stock Sizes:

Shirts must be available in the following sizes:

Bust Sizes: 26 - 54

XVIII. Class “C” Patrol/Judicial/K-9 Shirts Specifications

Men & Women Long Sleeve Shirt Specifications

Vertx Phantom LT Long Sleeve Shirt, F1 VTX8120

Uniform performance with the Vertx Phantom LT shirt. Delivered as a complement to the Phantom LT pants, this functional shirt is enhanced with Lycra knit side panels to provide cool, stretchable comfort during the hottest of days. Lightweight, mini rip-stop fabric resists tears without added bulk for durability through the toughest of situations.

Vendor will be asked to size employees while providing a complete fit for customer to ensure proper sizing.

- A. Emblems: On all Sheriff's Patrol/Judicial/K-9 class "C" uniform shirts, a regulation Washington County Sheriff Emblem shall be attached to each sleeve, set 1" below shoulder seam. The emblem will match the current emblem division in always and will be provided by the vendor (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve an emblem that is acceptable to the Sheriff's Office). All emblems must be attached at no extra charge. Where needed, a regulation Washington County Sheriff's Office Chevron shall be attached to both sleeves, placed directly below the shoulder emblem. The Chevron will match the current Chevron in all ways and will be provided by the vendor (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve a Chevron that is acceptable to the Sheriff's Office). The emblems and chevrons must be attached at no extra charge and shall be provided by the vendor. (See Attachments for illustration)
- B. Star Emblems: On all class "C" uniform shirts, a Washington County Sheriff Star Emblem shall be attached to the left breast, center above the pocket, and centered in the space. The emblem shall be a six-point star. The Star Emblem will match the current Star Emblem in all ways and will be provided by the vendor (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve a Star Emblem that is acceptable to the Sheriff's Office). The Star Emblems for class "C" will have MD under WASHINGTON CO., while the K-9 shirt will have K9. The Star Emblem will be attached at no extra charge and shall be provided by the vendor. (See Attachment for illustration)
- C. Name Strip: On Class "C" uniform shirts there will be a Velcro strip added above the front right pocket so a Velcro name strip with ID# can be attached to the shirt. The name strip will be made of the same material and color as the shirt with white writing to include the name and ID#. Vendor will ensure the proper Velcro is used for on the shirt and attaching name strip. At no extra charge to the County, all name strips must be approved by the County and attached to the uniform part.
- D. Epaulet: An epaulet made of the same shirt material will be attached to the shoulder piece of the shirt.
- E. Sizes: Small all the way to 5XL
- F. Sleeve Length: Long, Short, X-long, Regular
- G. Colors: Navy, OD Green, Black, Desert Tan, Smoke Grey
- H. Features:

- Vented back yoke on outside with mesh facing inside keeps wearers cool, dry, and comfortable.
- Faux buttons on pockets maintain a professional look while VELCRO Brand hook and loop closures allow for easy access.
- Convenient vertical map pockets with VELCRO Brand hook and loop closure provide storage for important documents.
- Lycra stretch side panel leads into shoulder for ultimate mobility.

XIX. Men & Women Short Sleeve Shirt Specifications

Vertx Phantom LT Short Sleeve Shirt, F1 VTX8100

Uniform performance with the Vertx Phantom LT shirt. Delivered as a complement to the Phantom LT pants, this functional shirt is enhanced with Lycra knit side panels to provide cool, stretchable comfort during the hottest of days. Lightweight, mini rip-stop fabric resists tears without added bulk for durability through the toughest of situations.

Vendor will be asked to size employees while providing a complete fit for customer to ensure proper sizing.

- A. Emblems: On all Sheriff's Patrol / Judicial class "C" uniform shirts, a regulation Washington County Sheriff Emblem shall be attached to each sleeve, set 1" below shoulder seam. The emblem will match the current emblem division in all ways and will be provided by the vendor (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve an emblem that is acceptable to the Sheriff's Office). All emblems must be attached at no extra charge. Where needed, a regulation Washington County Sheriff's Office Chevron shall be attached to both sleeves, placed directly below the shoulder emblem. The Chevron will match the current Chevron in all ways and will be provided by the vendor (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve a Chevron that is acceptable to the Sheriff's Office). The emblems and chevrons must be attached at no extra charge and shall be provided by the vendor. (See Attachments for illustration)
- B. Star Emblems: On all class "C" uniform shirts, a Washington County Sheriff Star Emblem shall be attached to the left breast, center above the pocket, and centered in the space.

The emblem shall be a six-point star. The Star Emblem will match the current Star Emblem in all ways and will be provided by the vendor (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve a Star Emblem that is acceptable to the Sheriff's Office).

The Star Emblems for class “C” will have MD under WASHINGTON CO., while the K-9 shirt will have K9. The Star Emblem will be attached at no extra charge and shall be provided by the vendor. (See Attachment for illustration)

- C. Name Strip: On Class “C” uniform shirts there will be a Velcro strip added above the front right pocket so a Velcro name strip with ID# can be attached to the shirt. The name strip will be made of the same material and color as the shirt with white writing to include the name and ID#. Vendor will ensure the proper Velcro is used for on the shirt and attaching name strip. At no extra charge to the County, all name strips must be approved by the County and attached to the uniform part.
- D. Epaulet: An epaulet made of the same shirt material will be attached to the shoulder piece of the shirt.
- E. Sizes: Small all the way to 5XL
- F. Colors: Navy, OD Green, Black, Desert Tan, Smoke Grey
- G. Features:
 - Vented back yoke on outside with mesh facing inside keeps wearers cool, dry, and comfortable.
 - Faux buttons on pockets maintain a professional look while VELCRO Brand hook and loop closures allow for easy access.
 - Convenient vertical map pockets with VELCRO Brand hook and loop closure provide storage for important documents.
 - Lycra stretch side panel leads into shoulder for ultimate mobility.

XX. Men & Women Phantom OPS Pant Specifications

Vertx Phantom OPS Men’s Tactical Pants, VTX8600

The Phantom OPS Pants deliver world-class comfort with optimal capacity. Made of 6.5 oz. Poly / Cotton Mini-Ripstop fabric treated with a water-repelling finish, they provide maximum durability plus a bonus triple-bellowed insert cargo pocket for added discreet storage.

- A. Waist: 28,29,30,31,32,33,34,35,36,38,40,42,44,46,48,50,52,54
Inseam: 30, 32, 34, 36
- B. Colors: OD Green, Navy, Black, Heather Grey, Desert Tan, Khaki
- C. Features:

- Flexible waistband and higher rise in the back ensures a comfortable fit.
- Back pocket flaps keep items secure without adding bulk.
- Concealed zipper pockets on both sides sized for tactical storage.
- Discreet, streamlined pockets on both sides sized for smaller gear.
- Triple-bellowed inset cargo pockets expand for additional capacity.
- Articulated double-reinforced knees allow freedom of movement while standing up to excess wear and tear.
- Mini-Ripstop fabric delivers exceptional durability and resists damage from rugged environments.
- Gusseted crotch provides extra flexibility and durability in any position.
- Reinforced six (6) belt loops sized to accommodate tactical belt: 1/4" width and 1-1/2" length.
- Wrinkle resistant.

XXI. Men & Women Fusion Light Weight Pant Specifications

Vertx Fusion LT Stretch Tactical Pants, VTX1200

The Fusion LT Stretch Tactical Pants are the perfect storm of fit, function and comfort. While the Fusion Pants embrace classic Vertx features such as the inset cargo pockets, a full gusset, and articulated knees – they have been elevated with innovative features demanded by modern operators.

Like fourteen (14) unique pockets, including mesh lining in the front and cargo pockets for added breathability.

Part of the VaporCore line, powered by 37.5 Technology, the Fusion works with you to keep you dry and comfortable, no matter the weather. From range day to tactical operations, the Fusion LT Pants provide everything needed to maximize performance.

- A. Waist: 28,30,32,34,36,38,40,42,44,46,48,50,52,54
- B. Inseam: 30, 32, 34, 36
- C. Colors: OD Green, Navy, Black, Desert Tan, Khaki
- D. Features:
 - 14 pockets keep essential items handy and organized.

- Articulated back yoke with two utility pockets.
- Lowered front hand pockets for easy access with or without a holster.
- Vertical zippered pockets behind inset cargo pockets for added storage and ease of access when sitting.
- Two utility pockets above cargo pockets.
- Angled back pockets with credential flaps for ease of access and securing valuables.
- Mesh-lined pockets for breathability and prevents heat spots: front hand pockets, utility pockets and zippered pockets behind cargo pocket.

E. Construction:

- Relax fit features side stretch waistband to maintain proper fit.
- Articulated knees enable dynamic mobility and prevent cuff creep when sitting.
- Fully gusseted crotch increases mobility and prevents rips or tears.
- Contoured higher back rise improves weight distribution from duty belt and provides full coverage when bending.
- Eight (8) belt loops are 0.875” wide and fit up to 1.75” belts.
- Open cuffs easily slip over boots.
- All heavy-wear seams are double-stitched.
- Bar tacks or YKK® rivets at critical stress points.

F. Fabric and Technology:

- 5 oz: 40% Polyester, 24% 37.5® Polyester, 36% Cotton
- 37.5® Technology promotes active temperature regulation and rapid drying

XXII. SRT Shirts Specifications

Recon Combat Shirt

Vertex Recon Combat Shirt, VTX8528

The RECON Combat Shirt provides high-performance design features and durability in the field. Double-reinforced elbows and Mini Ripstop weave fabric hold up to crawling, shooting, and climbing. The inclusion of VaporCore, powered by 37.5 Technology in the body allows you to perform better, longer. This is accomplished by its evaporative cooling properties and ability to dry up to 5x faster than traditional fabrics.

- A. Sizes: Small, Medium, Large, X-Large, 2XL, 3XL
- B. Sleeve: Regular, Long
- C. Colors: OD Green, Navy, Desert Tan, Black, Smoke Grey
- D. Features:
 - Traditional military style cuffs allow for sleeves to be rolled up easily.
 - Adjustable VELCRO Brand hook and loop wrist closure.
 - Double-reinforced and double-articulated elbows enhance durability with maximum resistance against wear, tear and fading for crawling, shooting, reaching, and climbing.
 - Dual bicep pockets with VELCRO Brand loop provide large storage capacity for extra carrying materials and patching purposes.
 - Easy access pen pocket inside each bicep pocket.
 - Quarter-zip suede collar yields extra neck and throat protection against chaffing from slings, packs, and body armor.

XXIII. Recon Combat Pants Specifications

Vertex Recon Combat Pants, VTX1901

The Recon pant offers maximum storage ability for units who need to balance loading and packing, with the ability to remain mobile and functional. Its 65 / 35 Poly / Cotton Mini Ripstop design provides reinforced durability for even the toughest missions.

- A. Waist : 30, 32, 34, 36, 38, 40, 42, 44
- B. Inseam : 30, 32, 34, 36
- C. Colors: OD Green, Navy, Black
- D. Features:
 - Relaxed waistband to optimize comfort.

- KK zipper and Vertx-branded button closure.
- Concealed zipper right pocket.
- Tool pockets on each hip.
- Inset back pockets with VELCRO® Brand closure flaps.
- Thigh possible pockets with inverted pleat, slightly angled for ease of entry.
- Triple bellowed cargo pocket with VELCRO® Brand closure.
- Elastic bands on interior of cargo pockets to prevent contents from sliding.
- Double reinforced knee with knee pad pouch and VELCRO® Brand closure.
- Fully gusseted crotch cut at 180 angles.
- Inverted pleat calf pockets on both sides with VELCRO® Brand closure.
- Draw cord eyelets on inside bottom hem of each leg.

XXIV. Phantom Ops Pants Specifications

Vertx Phantom OPS Men's Tactical Pants, VTX8600

The Phantom OPS Pants deliver world-class comfort with optimal capacity. Made of 6.5 oz. Poly / Cotton Mini-Ripstop fabric treated with a water-repelling finish, they provide maximum durability plus a bonus triple-bellowed insert cargo pocket for added discreet storage.

- A. Waist: 28,29,30,31,32,33,34,35,36,38,40,42,44,46,48,50,52,54
- B. Inseam: 30, 32, 34, 36
- C. Colors: OD Green, Navy, Black, Heather Grey, Desert Tan, Khaki
- D. Features:
 - Flexible waistband and higher rise in the back ensures a comfortable fit.
 - Back pocket flaps keep items secure without adding bulk.
 - Concealed zipper pockets on both sides sized for tactical storage.
 - Discreet, streamlined pockets on both sides sized for smaller gear.

- Triple-bellowed inset cargo pockets expand for additional capacity.
- Articulated double-reinforced knees allow freedom of movement while standing up to excess wear and tear.
- Mini-ripstop fabric delivers exceptional durability and resists damage from rugged environments.
- Gusseted crotch provides extra flexibility and durability in any position.
- Reinforced 6 belt loops sized to accommodate tactical belt: 1/4" width and 1 1/2" length.
- Wrinkle resistant.

XXV. Fusion Light Weight Pant

Vertx Fusion LT Stretch Tactical Pants, VTX1200

The Fusion LT Stretch Tactical Pants are the perfect storm of fit, function and comfort. While the Fusion Pants embrace classic Vertx features such as the inset cargo pockets, a full gusset, and articulated knees – they have been elevated with innovative features demanded by modern operators. Like fourteen (14) unique pockets, including mesh lining in the front and cargo pockets for added breathability.

Part of the VaporCore line, powered by 37.5 Technology, the Fusion works with you to keep you dry and comfortable, no matter the weather. From range day to tactical operations, the Fusion LT Pants provide everything needed to maximize performance.

- A. Waist: 28,30,32,34,36,38,40,42,44,46,48,50,52,54
- B. Inseam: 30, 32, 34, 36
- C. Colors: OD Green, Navy, Black, Desert Tan, Khaki
- D. Features:
 - Fourteen (14) pockets keep essential items handy and organized.
 - Articulated back yoke with two utility pockets.
 - Lowered front hand pockets for easy access with or without a holster.
 - Vertical zippered pockets behind inset cargo pockets for added storage and ease of access when sitting.

- Two (2) utility pockets above cargo pockets.
- Angled back pockets with credential flaps for ease of access and securing valuables.
- Mesh-lined pockets for breathability and prevents heat spots: front hand pockets, utility pockets and zippered pockets behind cargo pocket.

E. Construction:

- Relax fit features side stretch waistband to maintain proper fit.
- Articulated knees enable dynamic mobility and prevent cuff creep when sitting.
- Fully gusseted crotch increases mobility and prevents rips or tears.
- Contoured higher back rise improves weight distribution from duty belt and provides full coverage when bending.
- Eight (8) belt loops are 0.875” wide and fit up to 1.75” belts.
- Open cuffs easily slip over boots.
- All heavy-wear seams are double-stitched.
- Bar tacks or YKK® rivets at critical stress points.

F. Fabric and Technology:

- 5 oz: 40% Polyester, 24% 37.5® Polyester, 36% Cotton.
- 37.5® Technology promotes active temperature regulation and rapid drying.

XXVI. Outerwear All Division – Patrol, Judicial, Detention, SRT

Vertex Integrity Shell Jacket, VTX8800

Detention & SRT: If divisions should purchase jacket, then vendor will work with that division in a collaborative relationship to achieve an acceptable design when concerning the pull-out flaps.

In the Vertex Integrity Shell Jacket you’ll be more than ready to tackle the elements. Every aspect of the Integrity is focused on keeping elite operators and their gear at peak efficiency, regardless of the weather. The detachable hood has multiple adjustment points and is articulated so it moves with you without blocking your field of vision.

Waterproof zippers on the front closure, right forearm pocket and handwarmer pockets provide maximum protection from rain and snow. Part of the VaporCore line, powered by 37.5 Technology, the Integrity works with you to keep warm and dry when needed, and works to reduce humidity when things start to heat up. The jacket's large two-way zippered side vents extend from the snaps at the hem to the upper arms and provide quick access to sidearms and other critical gear. Patrol & Judicial: On back pullout flap reflective "SHERIFF DEPUTY" and pull outs on front reflective "SHERIFF" (right chest) and DEPUTY (left chest).

- A. Size: X-Small, Small, Medium, Large, X-Large, 2XL, 3XL, 4XL, 5XL, 6XL
- B. Length: Regular, Long
- C. Colors: Black, Ranger Green, Navy
- D. Features:
 - Wind- and water-proof breathable shell with taped seams.
 - Detachable hood with visor has girth and front opening adjustments.
 - Hood and hem adjust with locking shock cords.
 - Zip-through storm collar with zipper garage.
 - Front pockets lined with fleece for warmth and waterproof zipper closure.
 - Left chest pocket with storm flap and removable credential pull-out.
 - Zippered back opening for credential pull-out and hood storage.
 - 2-way side zippers with hem snaps for ventilation and easy access to weapon or tools.
 - 3" x 5" pocket with waterproof zipper on right forearm for small tools or ID.
 - Extended tail maintains coverage during strenuous activities.
- E. Construction:
 - All seams are taped for 100% waterproof protection.
 - Storm flaps protect side zippers from rain and wind.
 - Waterproof YKK® self-repairing nylon coil zippers.
 - Locking shock cord adjustments.

- VELCRO® Brand adjustment tabs on stretch cuffs and sleeve patch for long-lasting durability and a clean look.

F. Fabric and Technology:

- Waterproof / breathable tri-laminate 100% Ripstop Polyester shell.
- Hook and loop on stretch cuffs and sleeve patch.
- 37.5® Technology lining actively works with the wearer to keep your body temperature comfortable, dry, and odor-free.

XXVII. Vertx Integrity Shell Pant, VTX8815

A. Small, Medium, Large, X-Large, 2XL, 3XL

B. Length: Regular, Long

C. Colors: Black, Ranger Green, Navy

Waterproof, windproof and comfortable, the Integrity Shell Pant provides unmatched functionality when the weather gets rough. The 37.5 Active Particles elevate moisture evaporation while zippered inside thigh vents enable increased airflow through hotspots, keeping you cool and dry in any condition.

Mobility and comfort are key for any bad-weather mission, so the integrity is designed with our standard articulated knee and contoured back rise. The generous fly and ankle zippers easily allow donning and doffing without wrestling the pants or removing your boots. And unlike other slip-on rain pants, the Integrity Shell Pant is tactical belt compatible. Just thread through the five (5) belt loops and cinch the elastic waist tabs for a custom fit.

Outfitted with covered front pocket pass-throughs and six (6) protected external pockets, the Integrity Shell Pant provides easy, dry access to essential gear no matter what storm comes your way.

D. Features:

- Wind- and waterproof 37.5® laminated shell with taped seams.
- High-rise rear waistband with polyester suede lining for added coverage and a more comfortable fit.
- Waistband has five (5) 2” belt loops and elasticized adjustment straps with hook and loop tabs.
- Zippered fly with two (2) waistband snaps and storm flap.

- Pass-throughs with hook and loop tab–secured storm flaps allow access to pants pockets.
- Two (2) angled front pockets with zipper and storm flaps.
- Waterproof-zippered thigh pockets with internal pocket for phone, notepad, or like-size items.
- Rear zippered pockets with hook and loop tab–secured storm flaps.
- Inside the thighs zippered vents for airflow.
- Polyester oxford fabric wrapped around bottom legs provides abrasion resistance and durability.
- Articulated knees improve comfort and agility when on the move.
- Ankle-height zippers with storm flaps allow easy donning and doffing over boots.

E. Construction:

- All seams are taped for 100% waterproof protection.
- Storm flaps protect fly and zippers from rain and wind.
- YKK® waterproof and standard self-repairing nylon coil zippers.
- Hook and loop waist adjustments for a tailored fit.

F. Fabric and Technology:

- 100% Polyester shell with 37.5 laminate.
- 100% Polyester Oxford, 600D x 600D.

XXVIII. Duty Guard HT Pullover - Men

Flying Cross by Fechheimer, F1 57100

- A. Fabric: The upper front fabric shall be 100% Polyester with a DWR finish bonded to micro polyester. The lower front fabric shall be 50% Polyester / 42% 37.5® Technology / 8% Spandex. The back fabric shall be 100% Polyester jersey knit.
- B. Colors: Black (10), OD Green (27), LAPD Navy (86)

- C. Style: The pullover shall be manufactured from new up-to-date pattern with an articulated sleeve, gusseted underarms, and mandarin style collar. The shoulder and chest area shall be of a waterproof polyester fabric. The torso shall be of a knit stretch fabric. The pullover shall have two (2) upper hand warmer pockets. Sleeve cuff has partial Nylon Spandex for a comfort fit.
- D. Pocket Lining: The hand warmer pockets lining shall consist of a micro fleece material.
- E. Collar: The pullover collar shall be a mandarin style with the front zip extending to the top of the collar allowing it too fully close.
- F. Zippers: The center front zipper shall be a 12.5” YKK™ #3 Nylon reverse Closed End. A zipper “garage” shall be located at top of the zipper.
- G. Optional Badge Tab, Epaulet and Seam Tape: There shall be one (1) badge tab 3-3/8” L X 1” W with two (2) metal eyelets spaced 1 1/2” apart center to center. There shall be a pair of pointed badge tabs (separate) 1-3/4” wide at point, 2” wide at straight raw edge and 9” long from point to straight raw edge. There shall be a 5” roll of seam tape. Badge tab, epaulet and seam tape shall be packaged in a clear 4-1/4” x 5” zip top bag and attached beneath the hang tag.

Optional Customization for the Duty Guard HT 1/4 Zip Jacket to include a Washington County Sheriff’s Office Division emblem (all divisions) shall be attached to both sleeves and be provided by the vendor, (the successful vendor and the Sheriff’s Office will work in a collaborative relationship to achieve an emblem that is acceptable to the Sheriff’s Office).

- H. Construction: Stitching - The pullover shall be constructed using a serge and top stitch method. Stitching shall be 10 to 12 Stitches per Inch for increased durability. Topstitching will be omitted where waterproof fabric is sewn together. These areas shall have seam tape only.
- I. Stock Sizes:

Pullover is available from stock in the following sizes:

Short Length: XS – L
 Regular Length: XS – 5XL
 Long Length: M– 5XL

XXIX. Duty Guard HT Pullover - Female Style will be F1 57100W

Female shirts shall be constructed the same as the male shirts but cut on female patterns.

- A. Fabric: The upper front fabric shall be 100% Polyester with a DWR finish bonded to micro polyester. The lower front fabric shall be 50% Polyester / 42% 37.5® Technology / 8% Spandex. The back fabric shall be 100% Polyester jersey knit.

- B. Colors: Black (10), OD Green (27), LAPD Navy (86)
- C. Stock Sizes: Pullover is available from stock in the following sizes:
 - Short Length: XS – 2XL
 - Regular Length: XS – 5XL
 - Long Length: M– 5XL

XXX. Duty Guard HT+ Pullover, Men’s and Women’s

Flying Cross by Fechheimer, A - F1 57300 & B - F1 57300W

- A. Fabric: The upper front fabric shall be 100% Polyester fully lined and insulated including 37.5 technology (waterproof, windproof and breathable membrane). The lower front fabric shall be 50% Polyester / 42% 37.5® Technology / 8% Spandex.
- B. Style: The pullover shall be manufactured from new up to-date pattern with an articulated sleeve, gusseted underarms, half-zip design and mandarin style collar. The shoulder and chest area shall be of an insulated and waterproof polyester fabric. The torso shall be of a woven stretch fabric. The pullover shall have two (2) upper hand warmer pockets. Sleeve cuff has partial Nylon Spandex for a comfort fit.
- C. Colors: Navy, Black, Olive Drab
- D. Sizes: X-Small, Small, Medium, Large, X-Large, 2XL, 3XL, 4XL, 5XL
- E. Length: Short, Regular, Long
- F. Pocket Lining: The hand warmer pockets lining shall consist of a brushed tricot material.
- G. Collar: The pullover collar shall be a mandarin style with the front zip extending to the top of the collar allowing it too fully close.
- H. Zippers: The center front zipper shall be a 12.5” YKK™ #3 Nylon reverse Closed End. A zipper “garage” shall be located at top of the zipper.
- I. Optional Badge and Microphone Hanger: There shall be one (1) badge tab 2-1/4” L X 3/4” W with two (2) metal eyelets spaced 1-1/4” apart center to center. There shall be two (2) microphone tabs 1-3/4” L X 1/2” W. They shall be supplied with the pullover, placed in a Ziploc bag and swift tacked to the zipper pull.

Optional Customization for the Duty Guard HT 1/4 Zip Insulated Jacket to include a Washington County Sheriff’s Office Division emblem (all divisions) shall be attached to both sleeves and be provided by the vendor, (the successful vendor and the Sheriff’s Office will work in a collaborative relationship to achieve an emblem that is acceptable to the Sheriff’s Office).

J. Construction: Stitching - The pullover shall be constructed using a serge and top stitch method. Stitching shall be 10 to 12 Stitches per Inch for increased durability. Topstitching will be omitted where waterproof fabric is sewn together. These areas shall have seam tape only.

K. Stock Sizes:

Pullover is available from stock in the following sizes:

Short Length: XS – L

Regular Length: XS – 5XL

Long Length: M– 5XL

XXXI. Duty Guard ST Outer Shell Jacket, Flying Cross by Fechheimer, F1 56100

A. Fabric: The shell fabric shall be 50% Polyester / 42% 37.5® Technology / 8% Spandex with a DWR finish bonded to micro polyester, 10 oz. per sq. yd.

B. Color: LAPD Navy (86) & Black (10)

* Extraordinary comfort and performance are achieved with an active particle embedded polyester that is permanently embedded at the fiber level of continuous filament and staple filament polyester yarns capturing and releasing moisture vapor.

C. Style: The jacket shall be manufactured from new up-to-date pattern with an articulated sleeve, pleated back and mandarin style collar. The center front zipper shall be concealed with a storm flap secured by six (6) hidden snaps. The jacket shall have two (2) upper napoleon pockets, two (2) lower horizontal dump in pockets with zipper closures, and two (2) hand warmer pockets. There shall be (2) side zippers with adjustable snap closure and reversible pulls. Sleeve cuffs have 3/4” elastic on the inside of the cuff and self-fabric Velcro adjustable straps for a comfort fit. The back panel hem contains elastic. The jacket also contains two (2) mic clips on the upper chest.

D. Pocket Lining: The lower drop in dump pockets and the hand warmer pockets lining shall consist of a micro fleece material.

E. Collar: The jacket collar shall be a mandarin style with the front zip extending to the top of the collar allowing it too fully close.

F. Zippers: The center front zipper shall be an YKK™ #5 Vislon. The chest pocket zippers shall be a YKK #3 Nylon with matching pull slide. The dump pocket zippers shall be a YKK #5 Nylon with matching pull slide. A zipper “garage” shall be located at top of each pocket zipper. There shall be laminated pocket flap concealing each pocket zipper. There shall be two (2) 22” Aqua guard Vislon waterproof side zippers extending from under the arm to the bottom of the side hem with an adjustable elastic tab and snap closure.

HEM Drawcord: There shall be two (2) draw-cords located in the hem of the front panels. Each draw-cord shall have barrel locks and a cloth loop to secure the draw-cord to the jacket on the inside of the hand warmer pockets.

Optional Badge and Microphone Hanger: There shall be one (1) badge tab 2-1/4" L X 3/4" W with two (2) metal eyelets spaced 1-1/4" apart center to center. There shall be two (2) microphone tabs 1-3/4" L X 1/2" W. They shall be supplied with the jacket, placed in a Ziploc bag and swift tacked to the zipper pull.

Optional Customization for the Duty Guard ST Outer Shell Jacket to include a Washington County Sheriff's Office Division emblem (all divisions) shall be attached to both sleeves and be provided by the vendor, (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve an emblem that is acceptable to the Sheriff's Office).

Construction: Stitching - The jacket shall be constructed using a serge and top stitch method. Stitching shall be 10 to 12 Stitches per Inch for increased durability.

Reinforcements – Snaps shall consist of 24L plain nylon cap and socket studs shall consist of 20L plain metal cap and stud.

Stock Sizes: Jacket is available from stock in the following sizes:

Short Length: XS – L

Regular Length: XS – 5XL

Long Length: M– 5XL

XXXII. Softshell Jacket, Flying Cross by Fechheimer, 54100A

- A. Style Number: 54100A - LAPD Navy, Black, Brown
- B. Fabric: The shell fabric shall be 88% Polyester / 12% Spandex with a DWR finish bonded to micro polyester, 10 oz. per sq. yd.
- C. Style: The jacket shall be manufactured from new up-to-date pattern with an articulated sleeve, gusseted underarms, and mandarin style collar. The jacket shall have two (2) upper napoleon pockets and two (2) lower vertical pockets with exposed zippers. There shall be two (2) side zippers with adjustable snap closure and adjustable drawcord. Sleeve cuff has partial Nylon Spandex for a comfort fit. Loops at back sleeve cuff seam and outside neck seam coordinate with snap tabs on several Flying Cross outerwear styles (73160, 78140 & 79900GTX).
- D. Pocket Lining Sleeve Lining: The upper napoleon pocket and lower vertical pocket lining shall extend from the hem to the chest and from the side seam to the front zipper edge. Pocket lining shall consist of a mesh material for better breathability. The lining shall extend across the back yoke and down the top sleeve. The lining for the under sleeve shall be out of micro fleece material.

- E. Collar: The jacket collar shall be a mandarin style with the front zip extending to the top of the collar allowing it too fully close. The inner collar shall be lined with micro fleece.
- F. Zippers: The center front zipper shall be an YKK™ #5 Vislon. Pocket zippers shall be a YKK #5 concealed coil zipper with matching pull slide. A zipper “garage” shall be located at top of each zipper. There shall be (2) 10” coil side zippers with zipper welt and adjustable elastic tab and snap closure.
- G. Hem Drawcord: There shall be draw-cord located in the hem of the back panel. The draw-cord shall have barrel locks and a cloth loop to secure the draw-cord to the jacket.
- H. Optional Badge and Microphone Hanger: There shall be one (1) badge tab 2-1/4” L X 3/4” W with two (2) metal eyelets spaced 1-1/4” apart center to center. There shall be two (2) microphone tabs 1-3/4” L X 1/2” W. They shall be supplied with the jacket, placed in one of the lower vertical pockets.

Optional Customization for the Soft-Shell Jacket to include a Washington County Sheriff’s Office Division emblem (all divisions) shall be attached to both sleeves and be provided by the vendor, (the successful vendor and the Sheriff’s Office will work in a collaborative relationship to achieve an emblem that is acceptable to the Sheriff’s Office).

- I. Construction: Stitching - The jacket shall be constructed using a serge and top stitch method. Stitching shall be 10 to 12 Stitches per Inch for increased durability.

Reinforcements – Snaps shall consist of 24L plain nylon cap and socket studs shall consist of 20L plain metal cap and stud

- J. Stock Sizes: Jacket is available from stock in the following sizes:

Regular Length: XS – 6XL

Long Length: M– 6X

XXXIII. Optional Items All Division – Patrol, Judicial, Detention, SRT

Men’s ColdBlack Short Sleeve Polo, VTX4000P

The Vertx ColdBlack polo allows users to stay cool while wearing dark colors in the sunlight. Exclusive ColdBlack Technology, combined with moisture-wicking fabric, reflects 80% of the sun’s UV rays and lessens heat absorption-resulting in a light, breathable shirt ideal for warm weather. Streamlined design, convenient sleeve pockets for pens and pencils, and a no-roll collar give this shirt a professional look with all the tactical functionality to get the job done.

To include Sheriff’s Office embroidered logo.

- A. Colors: Black, Tan, Navy, Red, White, Spruce Green, Grey, LT Grey

B. Size: X-Small, Small, Medium, Large, X-Large, 2XL, 3XL, 4XL

C. Features:

- Relaxed fit with side gussets and raglan sleeves construction for added comfort and mobility.
- No-roll collar for a consistent professional appearance.
- 3-button front placket with a loop for mic or glasses.
- Two 7/8” W x 5” L pencil pocket on the left sleeve keeps writing instruments handy.
- Superior moisture transport wicks sweat away so you can stay cool and comfortable.
- Permanent ColdBlack® Technology treatment keeps wearer cool even in dark-colored fabrics.
- Reflects 80% of the sun’s UV rays.
- Minimum UPF 30+
- Fade-resistant.
- Anti-microbial treatment for long-lasting odor control (EPA registration # 91742-6).

D. Construction:

- Pique knit polyester fabric.
- Raglan sleeves.
- Gusseted side.

E. Fabric and Technology:

- 100% Polyester with ColdBlack ® Technology.
- ColdBlack® Technology is a breathable UVA- and UVB-protection textile finish designed to protect from harmful UV rays as well to reduce heat absorption in dark fabric by reflecting visible and invisible sunlight. By reducing the absorption of thermal radiation (heat), it keeps wearer noticeably COOLER and COMFORTABLE.

- Reflects 80% of heat rays keeping you noticeably COOLER.
- Minimum UPF 30+
- Breathable.
- Never washes off.
- Protects the fabric from fading.

XXXIV. Mock Turtleneck, Flying Cross, 52600

Mock turtleneck made of 82% cotton and 8% lycra. This police shirt is made with a blend of fabrics that stretch and fit well under other apparel for comfort on the job. The shirt comes in LAPD navy, white, and black; and has interlined cuffs and collars for the ultimate level of comfort. The same fabric is used on the collars and cuffs as the rest of the shirt to offer perfect color matching. It also has a long tail to prevent it from pulling out of your pants.

- A. Colors: Black, LAPD Navy
- B. Size: X-Small, Small, Medium, Large, X-Large, 2XL, 3XL, 4XL, 5XL
- C. Features:
 - Created using a blend of Lycra® and polyester for stretch.
 - Offers asset of interlined cuffs and collar for comfort.
 - Made with matching fabric on the collar, cuff, and body for a professional look.
 - Features a long tail to prevent shirt pulling out of pants.
 - Comes in an LAPD navy, white, and black that matches other apparel.

XXXV. Mock Dickey, Flying Cross, 52100

This is a 92% cotton and 8% Lycra® mock Dickey shirt with long sleeves for use in cool weather from a top uniform distributor. The shirt is made in black and comes with comfortable material for long days of work. The shirt has interlined cuffs and collars so it can be worn for hours without feeling uncomfortable. It has a stretch design and can easily be worn with other police apparel depending on the weather and location where officers are working. The collar and the rest of the shirt have the same color to create a professional look.

- A. Colors: Black, LAPD Navy
- B. Sizes: SM/MD, LG/XL, 2XL/3XL

C. Features:

- Includes a popular design in a black hue.
- Features a cotton and Lycra® construction with plenty of stretch.
- Two (2) upper vertical storage pockets with zipper closure and zipper pulls.
- Offers a set of interlined cuffs and collars for comfort.
- Two (2) lower vertical fleece-lined hand warmer pockets with zipper closure.
- Works well when paired with other police officer apparel.

XXXVI. Justice V-Neck Sweater Flying Cross, 790

The Justice V-neck sweater is offered in black or LAPD navy with a rib knit. It is made of 30% polyester, 33% wool, and 37% acrylic to ensure comfort and performance in any environment. The V-neck sweater has a contemporary professional style while being breathable, wind resistant, and warm.

It doesn't have the bulk of many sweaters and has color matching with other apparel for a put-together look. This sweater offers the option to add mic, badge, and name patches.

Optional Customization for the Justice V-Neck Sweater to include a Washington County Sheriff's Office Division patches/emblems (all divisions) shall be attached to both sleeves and be provided by the vendor, (the successful vendor and the Sheriff's Office will work in a collaborative relationship to achieve an emblem that is acceptable to the Sheriff's Office).

A. Color: LAPD Navy, Black

B. Sizes: Small, Medium, Large, X-Large, 2XL, 3XL

C. Features:

- Features a contemporary style that is comfortable in any environment.
- Made with a V-neck opening in an LAPD navy color.
- Offers a wind resistant, warm, and breathable garment without bulk.
- Includes a rib knit that incorporates bonded micro fleece.
- Constructed using 30% polyester, 33% wool, and 37% acrylic.

XXXVII. Flying Cross Hybrid LS Shirt Specifications - Mens, X1 305VS8426

- A. Fabric (A) Upper Body Sleeves, Collar:
- Content: 75% Dacron Polyester / 25% Wool with Natural Stretch
Weight: 9.0 to 9.50 oz. / linear yard
Color: French Blue
- B. Fabric (B) 37.5 Polyester:
- Content: 65% Dacron Polyester / 35% 37.5 Polyester
Weight: 10.5 oz / linear yard
Color: Navy
- C. Style: The Hybrid Shirt shall be manufactured from an up-to-date form fitting Shirt pattern. The Hybrid Shirt styling shall have Freedom Collar and a 1-1/4" front placket with button and buttonhole closure.
- D. Collar & Stand: Collar points to measure 3" long with ultrasonically fused-in Mylar stays positioned along the edge. Collar to have woven fusible interlining. Stays to be 2" long, 3/8" minimum width and to be fused to the bottom ply of the collar and shall be positioned along the leading edge. Stays applied directly to collar material itself unacceptable. Collar height at rear 1-1/2". Collar topstitched 1/4" along the edge. Collar stand to measure 1-5/16" at rear and band to be interlined with "Crease-N-Tack".
- E. Freedom Collar Feature: Material consisting of self-goods and lining material forming the neckband and the collar must be arranged with the weave thereof on a bias so that it is stretchable in the direction parallel to the circumferential direction of the collar. This expandable collar will allow for slight variations in neck size and make it easier to button because of the stretch or yield of the material.
- F. Upper Front: Each upper front shall have a full facing. The left front shall have a top center placket 1-1/2" wide with two (2) double rows of stitching. Stitching on top center is not to be visible on the turn-back facing. The shirt will have three (3) buttons and buttonholes on the upper front; spacing between each will be 3-3/4" except the spacing between the neck button and the first button on the front, which will be approximately 2-1/2". Top center placket to have woven fusible interlining. Non-woven interlining unacceptable and shall be cause for rejection. The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three (3) are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable. Back yoke to be 2-ply lined with shirt material.
- G. Lower Body, Side Panels and Under Arm Gussets: Lower body, side panels and underarm gussets are made from 37.5TM Polyester fabric for ease of movement and comfort.

- H. Sleeves: Sleeve vent shall be a minimum of 4-1/2" long with one-piece top and bottom facings. Facing to measure 1-1/8" wide point blocked at top.
- I. Cuffs: Two-piece 1/2" hemmed cuff, 1/4" topstitched along the edge. Cuffs to measure 3" in depth with rounded corners (barrel cuffs). Cuffs to be two (2) button adjustable with one (1) button and buttonhole in center of facing. Cuffs to have woven fusible interlining.
- J. Buttons: First grade 20-ligne melamine.
- K. Sewing: Collar, cuffs, and top center placket to be 1/4" topstitched. Sleeve inserting and side close felling seams are to be safety stitched.
- L. Thread: All sewing threads to be color fast polyester wrap to match.
- M. Interlinings: Collar, cuffs, and top center to be interlined with woven fusible.
- N. Available Sizes:

Alpha Body	Sleeve Lengths
X-Small through Small	X-Short
X-Small through X-Large	Short
Small through 4XL	Regular
Medium through 4XL	Long
Large through 4XL	X-Long

XXXVIII. Flying Cross Hybrid LS Shirt Specifications - Female Style, X1 205VS8426

Female shirts shall be constructed the same as the male shirts but cut on female patterns.

- A. Fabric (A) Upper Body, Sleeves, Collar:

Content: 75% Dacron Polyester / 25% Wool with Natural Stretch
 Weight: 9.0 to 9.50 oz. / linear yard
 Color: French Blue

- B. Fabric (B) 37.5 Polyester:

Content: 65% Dacron Polyester / 35% 37.5 Polyester
 Weight: 10.5 oz / linear yard
 Color: Navy

- C. Stock Sizes:

Shirts must be available in the following sizes:

Alpha Size X-Small through 4XL
Long Sleeve Lengths: Regular = 33" & Long = 35"

XXXIX. Flying Cross Hybrid SS Shirt Specifications – Men's, X1 655VS8426

- A. Fabric (A) Upper Body, Sleeves, Collar:
- Content: 75% Dacron Polyester / 25% Wool with Natural Stretch
Weight: 9.0 to 9.50 oz. / linear yard
Color: French Blue
- B. Fabric (B) 37.5 Polyester:
- Content: 65% Dacron Polyester / 35% 37.5 Polyester
Weight: 10.5 oz / linear yard
Color: Navy
- C. Style: The Hybrid Shirt shall be manufactured from an up-to-date form fitting Shirt pattern. The Hybrid Shirt styling shall have Freedom Collar and a 1-1/4" front placket with button and buttonhole closure.
- D. Collar & Stand: Collar points to measure 3" long with ultrasonically fused-in Mylar stays positioned along the edge. Collar to have woven fusible interlining. Stays to be 2" long, 3/8" minimum width and to be fused to the bottom ply of the collar and shall be positioned along the leading edge. Stays applied directly to collar material itself unacceptable. Collar height at rear 1-1/2". Collar topstitched with 1/4" along the edge. Collar stand to measure 1-5/16" at rear and band to be interlined with "Crease-N- Tack".
- E. Freedom Collar Feature: Material consisting of self-goods and lining material forming the neckband and the collar must be arranged with the weave thereof on a bias so that it is stretchable in the direction parallel to the circumferential direction of the collar. This expandable collar will allow for slight variations in neck size and make it easier to button because of the stretch or yield of the material.
- F. Upper Front: Each upper front shall have a full facing. The left front shall have a top center placket 1-1/2" wide with two (2) double rows of stitching. Stitching on top center is not to be visible on the turn-back facing. The shirt will have three (3) buttons and buttonholes on the upper front; spacing between each will be 3-3/4" except the spacing between the neck button and the first button on the front, which will be approximately 2-1/2". Top center placket to have woven fusible interlining. Non-woven interlining unacceptable and shall be cause for rejection.
- The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable. Back yoke to be 2-ply lined with shirt material.

Lower Body, Side Panels and Under Arm Gussets:

Lower body, side panels and underarm gussets are made from 37.5™ Polyester fabric for ease of movement and comfort.

- G. Sleeves: Sleeves are to be straight and whole and to have a 3/4” hem and to finish at a minimum of 9-1/2” long from shoulder seam.
- H. Buttons: First grade 20-ligne melamine.
- I. Sewing: Collar and top center placket to be topstitched 1/4” off the edge. Sleeve inserting and side close felling seams are to be safety stitched.
- J. Thread: All sewing threads to be color fast polyester wrap to match.
- K. Interlinings: Collar and top center to be interlined with woven fusible.
- L. Available Sizes: Hybrid shirt is available to order in the following sizes:
X-Small – 4XL

XL. Flying Cross Hybrid SS Shirt Specifications - Female Style, X1 255VS8426

Female shirts shall be constructed the same as the male shirts but cut on a female pattern.

- A. Fabric (A) Upper Body, Sleeves, Collar:

Content: 75% Dacron Polyester / 25% Wool with Natural Stretch

Weight: 9.0 to 9.50 oz. / linear yard

Color: French Blue

- B. Fabric (B) 37.5 Polyester:

Content: 65% Dacron Polyester / 35% 37.5 Polyester

Weight: 10.5 oz / linear yard

Color: Navy

- C. Stock Sizes:

Shirts must be available in the following sizes:

Alpha Sizes X-Small through 4XL

XLI. Neckties All Divisions - Patrol, Judicial, Detention

The vendor shall provide a clip-on necktie, with buttonholes. Color to match the Class “A-B” uniform trousers – LAPD Navy. The necktie shall be a polyester / wool blend. The vendor shall provide the various necktie lengths – neckties 18” and 20” in length and shorter, the wide part of the necktie shall be 3” in width. Neckties 22” in length and longer, the wide part of the necktie shall be 3-1/2” in width.

XLII. Straw Hats

Straw Hats: Navy blue campaign triple brim straw hats as manufactured by the Stratton Company. Front eyelet for hat badge is required.

A black 3/8” hat strap will be required with each hat. Custom fit hats are to be made to individual measurements and fittings. Measurements shall be taken at the Washington County Sheriff’s Office by vendor.

XLIII. Felt Hats

Navy blue campaign style 3X beaver felt hats as manufactured by the Stratton Company. Front eyelet for hat badge is required. A black 3/8” hat strap will be required with each hat. Custom hats are to be made to individual measurements and fittings. Measurements shall be taken at the Washington County Sheriff’s Office by vendor.

XLIV. Three (3) Piece Leather Strap

Black with Brass Buckles, Stratton SKU: ST-3P-BRSBUC-BK

A Three (3) Piece Leather Strap will also be provided by the vendor for each new hat ordered. Depending on rank the plain black straps will come with either silver or brass buckles. These are two (2) straps that are 1/2” wide. The ends are 3/8” wide with a snap-type swivel and closure. One of these straps comes with a leather keeper which together make three (3) pieces.



XLV. Three (3) Piece Leather Strap

Black with Silver Buckles, Stratton SKU: ST-3P-BK

A Three (3) Piece Leather Strap will also be provided by the vendor for each new hat ordered. Depending on rank the plain black straps will come with either silver or brass buckles. These are two straps that are 1/2" wide. The ends are 3/8" wide with a snap-type swivel and closure. One of these straps comes with a leather keeper which together make three (3) pieces.



POLICY TITLE: **Insurance Requirements for Independent Contractors**

ADOPTION DATE: August 29, 1989

EFFECTIVE DATE: September 1, 1989

FILING INSTRUCTIONS: _____

I. PURPOSE

To protect Washington County, Maryland against liability, loss or expense due to damaged property, injury to or death of any person or persons and for care and loss of services arising in any way, out of, or in connection with or resulting from the work or service performed on behalf of Washington County, Maryland.

II. ACTION

The following should be inserted in all Independent Contractor Contracts:

"The Contractor shall procure and maintain at his sole expense and until final acceptance of the work by the County, insurance as hereinafter enumerated in policies written by insurance companies admitted in the State of Maryland, have A.M. Best rating of A- or better or its equivalent, and acceptable to the County."

1. **Workers Compensation:** The Contractor agrees to comply with Workers Compensation laws of the State of Maryland and to maintain a Workers Compensation and Employers Liability Policy.

Minimum Limits Required:

Workers Compensation -	Statutory
Employers' Liability -	\$100,000 (Each Accident)
	\$500,000 (Disease - Policy Limit)
	\$100,000 (Disease - Each Employee)

2. **Comprehensive General Liability Insurance:** The Contractor shall provide Comprehensive General Liability including Products and Completed Operations.

Minimum Limits Required:

\$1,000,000 combined single limit for Bodily Injury and Property Damage.

Such insurance shall protect the County, its agents, elected and appointed officials, commission members and employees, and name the Board of County Commissioners of Washington County, Maryland on the policy as additional insured against liability, loss or expense due to damaged property (including loss of use), injury to or death of any person or persons and for care and loss of services arising in any way, out of, or in connection

Comprehensive General Liability Insurance (continued)

with or resulting from the work of service performed on behalf of Washington County, Maryland.

The Contractor is ultimately responsible that Subcontractors, if subcontracting is authorized, procure, and maintain at their sole expense and until final acceptance of the work by the County, insurance as hereinafter enumerated in policies written by insurance companies admitted in the State of Maryland, have A.M. Best rating of A- or better or its equivalent, and acceptable to the County.

3. **Business Automobile Liability:** The Contractor shall provide Business Auto Liability including coverage for all leased, owned, non-owned and hired vehicles.

Minimum Limits Required:

\$1,000,000 combined single limit for Bodily Injury or Property Damage.

Certificate(s) of Insurance: The Contractor shall provide certificates of insurance requiring a 30-day notice of cancellation to the Purchasing Department, Board of County Commissioners of Washington County, Maryland prior to the start of the applicable project.

Approval of the insurance by the County shall not in any way relieve or decrease the liability of the Contractor. It is expressly understood that the County does not in any way represent that the specified limits of liability or coverage or policy forms are sufficient or adequate to protect the interest or liabilities of the Contractor.

All responsibility for payment of any sums resulting from any deductible provisions, corridor, or self-insured retention conditions of the policy or policies shall remain with the Contractor.

General Indemnity: The Contractor shall indemnify, defend and save harmless the Board of County Commissioners of Washington County, Maryland, its appointed or elected officials, commission members, employees and agents for any and all suits, legal actions, administrative proceedings, claims, demands, damages, liabilities, interest, attorney's fees, costs and expenses of whatsoever kind of nature, whether arising before or after final acceptance and in any manner directly or indirectly caused, occasioned or contributed to in whole or in part by reason of any act, error or omission, fault or negligence whether active or passive by the Contractor, or any one acting under its direction, control or on its behalf in connection with or incident to its performance of the Contract.

Revision Date: August 27, 1991
Effective Date: August 27, 1991
Revision Date: March 4, 1997
Effective Date: March 4, 1997

**BOARD OF COUNTY COMMISSIONERS
OF WASHINGTON COUNTY, MARYLAND
WASHINGTON COUNTY PURCHASING DEPARTMENT**

PROVISIONS FOR OTHER AGENCIES

All items, conditions and pricing shall be made available to the entities listed below if authorized by the Bidder. Authorization is to be indicated by a check mark in the appropriate column. A negative reply will not adversely affect consideration of the bid. Any jurisdiction using this contract shall place its own order with the successful Bidder(s). There is no obligation on the lead jurisdiction for agreements made with other jurisdictions.

<u>YES</u>	<u>NO</u>	<u>JURISDICTION</u>
___	___	WASHINGTON COUNTY PUBLIC SCHOOLS
___	___	WASHINGTON COUNTY HEALTH DEPARTMENT
___	___	OTHER WASHINGTON COUNTY MUNICIPALITIES
___	___	HAGERSTOWN COMMUNITY COLLEGE
___	___	CITY OF HAGERSTOWN
___	___	FREDERICK COUNTY COMMISSIONERS
___	___	OTHER FREDERICK COUNTY MUNICIPALITIES
___	___	ALLEGANY COUNTY COMMISSIONERS
___	___	BOARD OF EDUCATION OF ALLEGANY COUNTY
___	___	OTHER ALLEGANY COUNTY MUNICIPALITIES
___	___	ALLEGANY COMMUNITY COLLEGE
___	___	CITY OF FROSTBURG
___	___	CITY OF CUMBERLAND
___	___	GARRETT COUNTY - GENERAL SERVICES
___	___	BOARD OF EDUCATION OF GARRETT COUNTY
___	___	OTHER GARRETT COUNTY MUNICIPALITIES
___	___	GARRETT COUNTY COMMUNITY COLLEGE
___	___	WASHINGTON COUNTY VOLUNTEER FIRE & RESCUE COMPANIES

SIGNATURE TO BIDS

NOTE: Bidders shall use this page as a cover page when submitting his / her bid.

Each bid must show the full business address and telephone number of the Bidder and be signed by the person legally authorized to sign contracts. All correspondence concerning the bid and contract, including notice of award, copy of contract and purchase order, will be mailed, or delivered to the address shown on the bid in the absence of written instructions from the Bidder to the contrary. Bids by partnerships must be signed in the partnership name by one of the members of the partnership or by an authorized representative, followed by the signature and designation of the person signing, who shall also state the names of the individuals composing the partnership. Bids by corporations must be signed with the name of the corporation, followed by the signature and designation of the officer having authority to sign. When requested, satisfactory evidence of authority of the officer signing in behalf of the corporation shall be furnished. Anyone signing the bid as agent shall file satisfactory evidence of his / her authority to do so.

All documents, materials, or data developed as a result of this contract are the County’s property. The County has the right to use and reproduce any documents, materials, and data, including confidential information, used in or developed as a result of this contract. The County may use this information for its own purposes or use it for reporting to Federal agencies. The Bidder warrants that it has title to or right of use of all documents, materials, or data used or developed in connection with this contract. The Bidder must keep confidential all documents, materials, and data prepared or developed by the Bidder or supplied by the County. All erasures and / or changes shall be initialed by the individual making modifications to the proposal.

BIDDER MUST SIGN HERE AND RETURN THIS PAGE AND THE PROPOSAL FORM IN ADDITION TO SUBMITTING ANY DOCUMENTS CALLED FOR BY THE GENERAL CONDITIONS AND INSTRUCTIONS TO BIDDERS, SPECIFICATIONS, AND ANY OTHER DOCUMENTS HEREIN CONTAINED.

By signing here, Bidder does hereby attest that he / she has read fully the general conditions and instructions, specifications, and any other documents herein contained, and does understand them and will furnish and deliver all labor and materials in accordance with the specifications for the price as listed on the proposal form.

Bidder acknowledges receipt of Addenda by initialing the following:

Addendum No. 1 _____ Addendum No. 2 _____ Addendum No. 3 _____
Addendum No. 4 _____ Addendum No. 5 _____ Addendum No. 6 _____

AFFIRMATION REGARDING COLLUSION

I AFFIRM THAT:

Neither I nor, to the best of my knowledge, information, and belief, the below stated business has:

- (a) Agreed, conspired, connived, or colluded to produce a deceptive show of competition in the compilation of the accompanying bid or offer that is being submitted.

- (b) In any manner, directly or indirectly, entered into any agreement of any kind to fix the bid price or price proposal of the Bidder or Offeror or of any competitor, or otherwise taken any action in restraint of free competitive bidding in connection with the contract for which the accompanying bid or offer is submitted.

AFFIRMATION REGARDING BRIBERY CONVICTIONS

I FURTHER AFFIRM:

Neither I nor, to the best of my knowledge, information, and belief, the below business (as is defined in Section 16-101 (b) of the State Finance and Procurement Article of the Annotated Code of Maryland), or any of its officers, directors, partners, or any of its employees directly involved in obtaining or performing contracts with public bodies (as is defined in Section 16-101(f) of the State Finance and Procurement Article of the Annotated Code of Maryland), has been convicted of, or has had probation before judgment imposed pursuant to Criminal Procedure Article, Section 6-220 of the Annotated Code of Maryland, or has pleaded nolo contendere to a charge of, bribery, attempted bribery, or conspiracy to bribe in violation of Maryland law, or of the law of any other State or federal law, **except as follows** (indicate the reasons why the affirmation cannot be given and list any conviction, plea, or imposition of probation before judgment with the date, court, official or administrative body, the sentence or disposition, the name(s) of person(s) involved, and their current positions and responsibilities with the business):

Bidder's Company/Firm: _____

Address: _____

Authorized Signature: _____

Name and Title Printed: _____

Telephone & Fax Number: _____ / _____

E-Mail Address: _____

Date: _____ Federal Employer's Identification No. _____

For Informational Purposes Only: Has your company / firm been certified by the State of Maryland as a Minority Business Enterprise? (Please check below)

_____ Yes _____ No

**PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF'S OFFICERS**

FORM OF PROPOSAL

Item No.	Description / Written Unit Price	Unit	Est. Qty	Price Per Unit	Total Price
1	Uniform Dress Blouses <hr/> <div style="text-align: right;">Dollars</div> <div style="text-align: center;">(written)</div> <hr/> <div style="text-align: right;">Cents per</div> <div style="text-align: center;">(written)</div>	Ea.	20	\$ <hr/> (Figures)	\$ <hr/> (Figures)
2	Class "A-B" Trousers – Patrol, Judicial & Detention – F1 47780 86 <hr/> <div style="text-align: right;">Dollars</div> <div style="text-align: center;">(written)</div> <hr/> <div style="text-align: right;">Cents per</div> <div style="text-align: center;">(written)</div>	Ea.	75	\$ <hr/> (Figures)	\$ <hr/> (Figures)
3	Women's Trouser, Option 1 – F1 47780W 86 <hr/> <div style="text-align: right;">Dollars</div> <div style="text-align: center;">(written)</div> <hr/> <div style="text-align: right;">Cents per</div> <div style="text-align: center;">(written)</div>	Ea.	75	\$ <hr/> (Figures)	\$ <hr/> (Figures)
4	Men's Trousers Option 2 – F1 47280 <hr/> <div style="text-align: right;">Dollars</div> <div style="text-align: center;">(written)</div> <hr/> <div style="text-align: right;">Cents per</div> <div style="text-align: center;">(written)</div>	Ea.	100	\$ <hr/> (Figures)	\$ <hr/> (Figures)

**PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF’S OFFICERS**

FORM OF PROPOSAL

Item No.	Description / Written Unit Price	Unit	Est. Qty	Price Per Unit	Total Price
5	Women’s Trouser, Option 2 – F1 47280W _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
6	Class “A-B” Shirt, Long Sleeve – Mens – Patrol, Judicial & Detention – 05W84 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
7	Women’s Long Sleeve Shirt – 105W84 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)

**PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF'S OFFICERS**

FORM OF PROPOSAL

Item No.	Description / Written Unit Price	Unit	Est. Qty	Price Per Unit	Total Price
8	Men's Short Sleeve Shirt – 55R84 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
9	Women's Short Sleeve Shirt - 155R84 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
10	Class "C" Men's Trouser - Detention - Option 1 – FX77400 _____ Dollars (written) _____ Cents per (written)	Ea.	100	\$ _____ (Figures)	\$ _____ (Figures)
11	Women's Trouser, Option 1 – FX77400W _____ Dollars (written) _____ Cents per (written)	Ea.	100	\$ _____ (Figures)	\$ _____ (Figures)

**PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF'S OFFICERS**

FORM OF PROPOSAL

Item No.	Description / Written Unit Price	Unit	Est. Qty	Price Per Unit	Total Price
12	Men's Trousers Option 2 – FX77300 _____ Dollars (written) _____ Cents per (written)	Ea.	100	\$ _____ (Figures)	\$ _____ (Figures)
13	Women's Trousers Option 2 – FX77300W _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
14	Class "C" Detention Long Sleeve Shirts Mens – F1 FX7020 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
15	Women's Long Sleeve Shirt – F1 FX7020W _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)

**PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF'S OFFICERS**

FORM OF PROPOSAL

Item No.	Description / Written Unit Price	Unit	Est. Qty	Price Per Unit	Total Price
16	Men's Short Sleeve Shirt – F1 FX7000 <hr style="width: 80%; margin-left: 0;"/> _____ Dollars (written) <hr style="width: 80%; margin-left: 0;"/> _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
17	Women's Short Sleeve Shirt – F1 FX7000W <hr style="width: 80%; margin-left: 0;"/> _____ Dollars (written) <hr style="width: 80%; margin-left: 0;"/> _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
18	Men's and Women's Class "C" Patrol/Judicial/K-9 Long Sleeve Shirt – F1 VTX8120 <hr style="width: 80%; margin-left: 0;"/> _____ Dollars (written) <hr style="width: 80%; margin-left: 0;"/> _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
19	Men's and Women's Short Sleeve Shirt – F1 VTX8100 <hr style="width: 80%; margin-left: 0;"/> _____ Dollars (written) <hr style="width: 80%; margin-left: 0;"/> _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)

**PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF'S OFFICERS**

FORM OF PROPOSAL

Item No.	Description / Written Unit Price	Unit	Est. Qty	Price Per Unit	Total Price
20	Men's and Women's Phantom OPS Pants – VTX8600 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
21	Men's and Women's Fusion Light Weight Pants – VTX1200 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
22	SRT Recon Combat Shirt - VTX8528 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
23	Recon Combat Pants - VTX1901 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)

**PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF'S OFFICERS**

FORM OF PROPOSAL

Item No.	Description / Written Unit Price	Unit	Est. Qty	Price Per Unit	Total Price
24	Phantom Ops Pants -VTX8600 <hr/> _____ Dollars (written) <hr/> _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
25	Fusion Light Weight Pants - VTX1200 <hr/> _____ Dollars (written) <hr/> _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
26	Outerwear - Jacket – Patrol / Judicial / Detention / SRT - VTX8800 <hr/> _____ Dollars (written) <hr/> _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
27	Vertx Integrity Shell Pants - VTX8815 <hr/> _____ Dollars (written) <hr/> _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)

**PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF'S OFFICERS**

FORM OF PROPOSAL

Item No.	Description / Written Unit Price	Unit	Est. Qty	Price Per Unit	Total Price
28	Duty Guard HT Pullover - Men's - F1 57100 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
29	Duty Guard HT Pullover - Women's - F1 57100W _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
30A	Duty Guard HT + Pullover Men's - F1 57300 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
30B	Duty Guard HT + Pullover Women's - F1 57300W _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)

**PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF'S OFFICERS**

FORM OF PROPOSAL

Item No.	Description / Written Unit Price	Unit	Est. Qty	Price Per Unit	Total Price
31	Duty Guard ST Outer Shell Jacket - F1 56100 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
32	Softshell Jacket - 54100A _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
33	Men's Cold Black Short Sleeve Polo - Patrol/Judicial/ Detention/SRT - VTX4000P _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
34	Mock Turtleneck – 52600 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)

**PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF'S OFFICERS**

FORM OF PROPOSAL

Item No.	Description / Written Unit Price	Unit	Est. Qty	Price Per Unit	Total Price
35	Mock Dickie – 52100 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
36	Justice V-Neck Sweater – 790 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
37	Hybrid Long Sleeve Shirt - Men's - X1 305VS8426 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
38	Hybrid Long Sleeve Shirt - Women's - X1 205VS8426 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)

**PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF'S OFFICERS**

FORM OF PROPOSAL

Item No.	Description / Written Unit Price	Unit	Est. Qty	Price Per Unit	Total Price
39	Hybrid Short Sleeve Shirt - Men's - X1 655VS8426 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
40	Hybrid Short Sleeve Shirt - Women's - X1 255VS8426 _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
41	Neckties _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
42	Straw Hats _____ Dollars (written) _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)

**PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF'S OFFICERS**

FORM OF PROPOSAL

Item No.	Description / Written Unit Price	Unit	Est. Qty	Price Per Unit	Total Price
43	Felt Hats <hr/> _____ Dollars (written) <hr/> _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
44	3 Piece Leather Strap - Black with Brass Buckles - ST-3P-BRSBUC-BK <hr/> _____ Dollars (written) <hr/> _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)
45	3 Piece Leather Strap – Black with Silver Buckles – ST-3P-BK <hr/> _____ Dollars (written) <hr/> _____ Cents per (written)	Ea.	25	\$ _____ (Figures)	\$ _____ (Figures)

**PUR-1569
UNIFORMS FOR
WASHINGTON COUNTY SHERIFF'S OFFICERS**

FORM OF PROPOSAL

Item No.	Description / Written Unit Price	Unit	Est. Qty	Price Per Unit	Total Price
TOTAL SUM BID (GRAND TOTAL OF ITEMS 1 through 46)					
_____ Dollars				\$ _____	
(written)					(Figures)
_____ Cents					
(written)					

REMARKS/EXCEPTIONS:

Background and Applicability:

In conjunction with the Office of Management and Budget and other affected Federal agencies, DOT published an update to 49 CFR Part 29 on November 26, 2003. This government-wide regulation implements Executive Order 12549, *Debarment and Suspension*, Executive Order 12689, *Debarment and Suspension*, and 31 U.S.C. 6101 note (Section 2455, Public Law 103-355, 108 Stat. 3327).

The provisions of Part 29 apply to all grantee contracts and subcontracts at any level expected to equal or exceed \$25,000 as well as any contract or subcontract (at any level) for Federally required auditing services, 49 CFR 29.220(b). This represents a change from prior practice in that the dollar threshold for application of these rules has been lowered from \$100,000 to \$25,000. These are contracts and subcontracts referred to in the regulation as “covered transactions.”

Grantees, Contractors, and Subcontractors (at any level) that enter into covered transactions are required to verify that the entity (as well as its principals and affiliates) they propose to contract or subcontract with is not excluded or disqualified. They do this by (a) Checking the Excluded Parties List System, (b) Collecting a certification from that person, or (c) Adding a clause or condition to the contract or subcontract. This represents a change from prior practice in that certification is still acceptable but is no longer required, 49 CFR 29.300.

Grantees, Contractors, and Subcontractors who enter into covered transactions also must require the entities they contract with to comply with 49 CFR 29, Subpart C and include this requirement in their own subsequent covered transactions (i.e., the requirement flows down to subcontracts at all levels).

This contract is a covered transaction for purposes of 49 CFR Part 29. As such, the Contractor is required to verify that none of the Contractor, its principals, as defined at 49 CFR 29.995, or affiliates, as defined at 49 CFR 29.905, are excluded or disqualified as defined at 49 CFR 29.940 and 29.945.

The Contractor is required to comply with 49 CFR 29, Subpart C and must include the requirement to comply with 49 CFR 29, Subpart C in any lower tier covered transaction it enters into.

By signing and submitting its bid or proposal, the Bidder or proposer certifies as follows: The certification in this clause is a material representation of fact relied upon by the *County*. If it is later determined that the Bidder or proposer knowingly rendered an erroneous certification, in addition to remedies available to the *County*, the Federal Government may pursue available remedies, including but not limited to suspension and/or debarment.

The Bidder agrees to comply with the requirements of 49 CFR 29, Subpart C while this offer is valid and throughout the period of any contract that may arise from this offer.

The Bidder or proposer further agrees to include a provision requiring such compliance in its lower tier covered transactions.

Company Name _____

Signature of Contractor’s Authorized Official _____

Printed Name of Contractor’s Authorized Official _____

Printed Title of Contractor’s Authorized Official _____

Date _____